
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID : M13.192.1
PRODUCT CLASS : PAINT, SOLVENT BASE
TRADE NAME : INT/EXT ALKYD SATIN BLACK
MSDS PREPARATION DATE : 09/09/2009

MANUFACTURER IDENTIFICATION:

NAME : COMPLEMENTARY COATINGS CORP
dba INSL-X
ADDRESS : 101 PARAGON DRIVE
MONTVALE, NJ 07645
TELEPHONE : (800) 225-5554
EMERGENCY CONTACT : CHEMTREC
EMERGENCY TELEPHONE . . . (US) . . : (800) 424-9300
EMERGENCY TELEPHONE (OUTSIDE US) : (703) 527-3887

SECTION 2 - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

1

CAS# 1333-86-4
CARBON BLACK
PCT BY WT: 1.6020
EXPOSURE LIMIT:
ACGIH TLV/TWA: 3.5 mg/cu m - TWA
OSHA PEL/TWA: 3.5 mg/cu m - TWA
LD50: Oral (Rat) - > 8,000 mg/kg
CA PROPOSITION 65: YES

2

CAS# 136-52-7
COBALT 2-ETHYLHEXANOATE
PCT BY WT: .1440
EXPOSURE LIMIT:
ACGIH TLV/TWA: NOT ESTAB.
ACGIH CEILING: NOT ESTAB.

3 MINERAL SPIRITS

CAS# 8052-41-3
ALIPHATIC HYDROCARBONS (STODDARD TYPE)
PCT BY WT: 10 - 30 VAPOR PRESSURE: .540 MMHG @ 20C
EXPOSURE LIMIT:
ACGIH TLV/TWA: 100 ppm TWA
OSHA PEL/TWA: 500 ppm TWA
LC50: Inhalation (rat) 5500 ppm, 4h
LD50: Oral (Rat) - 5000mg/kg Dermal (Rabbit) - 3000mg/kg

4

CAS# 95-63-6
1,2,4-TRIMETHYLBENZENE
PCT BY WT: .05 - 1.5
EXPOSURE LIMIT:
ACGIH TLV/TWA: TWA 25 ppm
OSHA PEL/TWA: TWA 25 ppm
LC50: Inhalation - 18 g/cu m (Rat/4H)

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

LD50: Oral, Rat - 5 g/kg

5

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: .1280 VAPOR PRESSURE: 7.000 MMHG @ 20C

EXPOSURE LIMIT:

ACGIH TLV/TWA: TWA 100 ppm

ACGIH TLV/STEL: STEL 25 ppm

OSHA PEL/TWA: TWA 100 ppm

OSHA STEL: 125 ppm

LD50: Oral, Rat - 3500 mg/kg

CA PROPOSITION 65: Yes

6 TALC

MAGNESIUM SILICATE HYDRATE

PCT BY WT: 1 - 5

EXPOSURE LIMIT:

ACGIH TLV/TWA: 2 mg/cu m TWA (Respirable fraction)

OSHA PEL/TWA: 2 mg/cu m TWA (Respirable dust)

7 GROUND LIMESTONE

CAS# 1317-65-3

CALCIUM CARBONATE

PCT BY WT: 10 - 30

EXPOSURE LIMIT:

ACGIH TLV/TWA: 2 mg/m3 TLV

8

CAS# 14808-60-7

CRYSTALLINE SILICA - QUARTZ

PCT BY WT: .1120

EXPOSURE LIMIT:

ACGIH TLV/TWA: TWA 0.10 mg/cu m (Respirable Dust)

OSHA PEL/TWA: TWA 0.10 mg/cu m (Respirable Fraction)

CA PROPOSITION 65: Yes

This product contains one or more reported carcinogens or suspected
carcinogens which are noted in Section 3, Hazards Identification,
CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Exposure to liquid may cause mild eye irritation. Symptoms may include stinging, tearing, and redness.

SKIN: May cause skin defatting with prolonged exposure. Exposure may cause skin irritation. Prolonged or repeated exposure may dry the skin.

INHALATION: Causes mild respiratory irritation. Breathing large amounts may be harmful. Symptoms of exposure may include irritation (nose, throat, respiratory tract) and CNS depression.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC EFFECTS

Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

Long term overexposure to crystalline silica causes silicosis, a form of pulmonary fibrosis. Continued overexposure to silica can lead to cardiopulmonary impairment.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Conditions aggravated by exposure may include skin disorders and respiratory (asthma-like) disorders.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. IARC has classified ethylbenzene as a possible human carcinogen, Group 2B.

IARC and NTP have reviewed crystalline silica. Crystalline silica is listed with IARC as Group 1 (carcinogenic to humans). IARC found sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources.

Based on an IARC conclusion that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "carbon black is possibly carcinogenic to humans", Group 2B. Carbon black has not been listed as a carcinogen by the NTP or OSHA. NIOSH criteria document recommends that only carbon black with PAH (polynuclear aromatic hydrocarbons) levels > 0.1% be considered suspect carcinogens.

IARC lists cobalt and cobalt compounds as possible human carcinogens

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

(Group 2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

ACGIH has given cobalt a rating of A3, animal carcinogen. They state that available epidemiological studies do not confirm an increased risk of cancer in exposed humans.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT

If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water, holding eyelids apart. If symptoms persist, seek medical attention.

SKIN CONTACT

Remove contaminated shoes and clothing, and flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area thoroughly by washing with mild soap and water. If irritation or redness develops, seek medical attention. Launder clothing before reuse.

INHALATION

If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention. Keep person warm & quiet.

INGESTION: Aspiration hazard. Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If the victim is drowsy or unconscious, place on left side with head down. If possible, do not leave victim unattended. Seek immediate medical attention.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : Combustible Liquid-Class II

Flashpoint : > 100 Deg. F, but < 140 Deg. F.

Explosion Level : Low - .9

High - 6.8

EXTINGUISHING MEDIA

Use National Fire Protection Association (NFPA) Class B extinguisher (carbon dioxide, dry chemical or foam).

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

FIRE-FIGHTING INSTRUCTIONS

During fire, a water spray can scatter flames and should be used by experienced firefighters. Firefighters should wear self-contained breathing apparatus with a full face piece operated in the positive pressure mode when fighting fires. Isolate damage area, keep unauthorized personnel out. Avoid spreading burning liquid with water used for cooling purposes.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Combustible liquid. Forms combustible mixtures with air at or above the flash point. This product can accumulate static charges, which can cause fire or explosion. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode and flash back.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Spilled material may be absorbed into an appropriate absorbent material. Prevent spilled material from entering sewers, storm drains, other authorized treatment drainage systems, and natural waterways. Stop spill/release if it can be done, and stay away from spill. Isolate danger and keep unauthorized personnel out. Use non-sparking tools and explosion-proof equipment.

CLEAN-UP

Warn occupants in surrounding and downwind areas of fire and explosion hazard to stay clear. Remove from surface with suitable absorbents. If allowed by local authorities, sinking and/or suitable dispersants may be used in non-confined waters.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep container closed. Handle and open container with care. Open container slowly to relieve any pressure. Do NOT cut, weld or puncture on or near container.

STORAGE

Keep container(s) tightly closed. Use and store this product in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Keep away from any incompatible material. Protect container(s) against physical damage.

SPECIAL COMMENTS

WARNING: Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures and pressures, or sudden ingress of air into vacuum equipment, may result in ignitions

M13.192.1

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

Appropriate disposable gloves are acceptable, such as, Nitrile rubber gloves.

Physical State	:	LIQUID		
Vapor Pressure	:	7.00		
Vapor Density	:	4.90		
Boiling Point Range	:	Lower -	277.0	°F
		Higher -	400.0	°F
Specific Gravity	:	1.166		
Weight per Volume	:		9.7074	LB/GL
VOC - Total (lb/gal)	:	3.180		
Evaporation Rate	:	.130	(n-Butyl Acetate = 1)	
Volatile by Weight	:	32.8175		
Volatile by Volume	:	49.9025		

HAZARDOUS POLYMERIZATION

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

Will not occur.
CONDITIONS TO AVOID

Avoid heat, sparks, open flames and other sources of ignition.

HAZARDOUS PRODUCTS OF DECOMPOSITION

Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : NOT REGULATED (In containers less than 119 gallons or 450 liters via surface transportation).
COMBUSTIBLE LIQUID (In containers of more than 119 gallons capacity) for surface shipments within the U.S. and Canada, and apply the DOT information, listed below:

DOT PACKAGING GROUP : PG III
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

COBALT 2-ETHYLHEXANOATE

CAS# 136-52-7 PCT BY WT: .1440

1,2,4-TRIMETHYLBENZENE

CAS# 95-63-6 PCT BY WT: .05 - 1.5

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: .1280

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 09/09/2009
Last Revision Date : 09/09/2009
MSDS Prepared for :
MSDS Last Prepared : NONE
HMIS Rating: Health- 2 Flammability- 2
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA -

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

M13.192.1

Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable
IARC - International Agency for Research on Cancer; NE - Not established
NTP - National Toxicological Program; CFR - Code of Federal Regulations;
OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC -
Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram
per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts
per million; NIOSH - National Institute of Occupational Safety and Health;
MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.