

FPPF CHEMICAL CO., INC.



SAFETY DATA SHEET

Issue Date 01-Jun-2015

Revision Date 05-Jun-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Custom Formula Year Round

Other Means Of Identification

Product Code Various

Recommended use of the Chemical and Restrictions on Use

Recommended Use Diesel fuel treatment

Uses Advised Against No restrictions on use known

Chemical Family Mixture

Details of the Supplier of the Safety Data Sheet

Supplier Address FPPF Chemical Co.,Inc., 117 West Tupper St., Buffalo, N.Y. 14201, 716-856-9607

Emergency Telephone Chemtrec 1-800-424-9300(U.S.) 703-527-3887(Outside U.S.)

2. HAZARDS IDENTIFICATION

Classification Colorless to slightly hazy liquid. Amber liquid. Solvent Odour. .

This Chemical is considered Hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)(Hazcom 2012) & Canadian WHMIS reg. (hazardous Product Regulations)(WHNIS 2015)

Flammable Liquid	Category 3
Acute Toxicity-Inhalation	Category 4(Vapor)
Aspiration Toxicity	Category 1
Reproductive Toxicity	Category 2(Developmental)
Specific Target Organ Toxicity (Single Exposure)	Category 3 (CNS)
Specific Target Organ Toxicity, Single Exposure	Category 3(Respiratory)
Carcinogenicity	Category 2
Acute toxicity -Dermal	Category 4
Skin Irritation	Category 2
Eye Damage/Irritation	Category 2A



Label Elements Hazard pictogram(s)

Emergency Overview

Danger

Hazard Statements

Flammable Liquid & Vapor

Toxic if inhaled

May be fatal if swallowed and enters airways

May cause respiratory irritation

Harmful in contact with skin

May cause drowsiness & dizziness

Suspected of damaging the unborn child

Suspected of causing cancer

Causes skin & eye irritation

SAFETY DATA SHEET*Precautionary statement(s)*

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks and open flame. - No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors or mists. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash hands and face thoroughly after handling.

In case of fire, use water fog, dry chemical, CO2 or 'alcohol' foam.

If exposed or concerned: Call a POISON CENTER or doctor/physician.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: May be sensitive to static discharge. Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration</u>
Light aromatic solvent naphtha	Aromatic solvent naphtha Solvent Naphtha (Petroleum) Light Aromatic	64742-95-6	2.0 - 10.0
2-Butoxy ethanol	Ethylene Glycol Monobutyl Ether EGBE	111-76-2	15.0 - 25.0
Naphthalene	Moth balls Moth flakes Tar camphor	91-20-3	0.1 - 0.5
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	0.5 - 2.5
1,3,5-Trimethyl benzene	Trimethylbenzol Mesitylene	108-67-8	0.2 - 1.0
Xylene (mixed isomers)	Dimethylbenzene Methyltoluene Xylol	1330-20-7	0.1 - 0.5
Cumene	Isopropyl benzene Cumol 2-Phenyl propane	98-82-8	0.1 - 0.5
oleic acid	Oleic acid; 9-Octadecenoic acid; Elaic acid	112-80-1	1.0 - 5.0
Propylbenzene	N-Propylbenze Isocumene 1-Propylbenzene	103-65-1	0.2 - 1.0
1,2,3-Trimethylbenzene	Hemellitol Hemimellitene	526-73-8	0.1 - 0.5
stoddard solvent	Mineral spirits White spirit	8052-41-3	55.0 - 60.0
Heavy aromatic solvent naphtha	Aromatic solvent naphtha Heavy Aromatic Naphtha	64742-94-5	1.0 - 5.0

SAFETY DATA SHEET

2-Ethylhexyl nitrate	Ethylhexyl nitrate Nitric acid, 2-ethylhexyl ester	27247-96-7	3.0 - 5.0
2-Ethylhexanol	2-Ethylhexyl Alcohol	104-76-7	3.0 - 8.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES**Description of first aid measures**

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Aspiration hazard Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.
- Skin contact* : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs, get medical advice/attention.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : IF exposed or concerned: Get medical attention/advice.
- Harmful in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation.
- Toxic if inhaled. Symptoms may include coughing, choking and wheezing. May cause respiratory impairment and lung damage.
- May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties.
- May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
- Causes skin irritation. Symptoms may include redness, itching and swelling.
- Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.
- May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.
- Symptoms include coughing, shortness of breath and wheezing.
- Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.
- Suspected of damaging the unborn child. Symptoms in offspring may include reduced fetal weight, behavioral effects, delayed skeletal formation and hearing loss.

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage, based on animal data. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Provide general supportive measures and treat symptomatically. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES**Extinguishing media***Suitable extinguishing media*

- : Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

SAFETY DATA SHEET

- : Flammable liquid and vapour Keep away from heat, sparks, and open flames. This product will accumulate static charge by flow, splashing or agitation. After prolonged storage, may release explosive peroxides in the presence of air. Vapors may travel considerable distance to a source of ignition and flash back. Vapours may be heavier than air and may collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquid - Category 3

Hazardous combustion products

- : Carbon oxides. Nitrogen oxides. Reactive hydrocarbons. Aldehydes. Other irritating fumes and smoke.

Special protective equipment and precautions for firefighters*Protective equipment for fire-fighters*

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labelled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

Special spill response procedures

- : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ):
Naphthalene (100 lbs / 45.4 kg);
Xylene (100 lbs / 45.4 kg);
Cumene (5000 lbs / 2270 kg).

SECTION 7. HANDLING AND STORAGE**Precautions for safe handling**

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Avoid breathing mist or vapours. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

SAFETY DATA SHEET

- Conditions for safe storage** : Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store away from incompatibles and out of direct sunlight. After prolonged storage, may release explosive peroxides in the presence of air. Direct sunlight or heat may accelerate the release of peroxides. Rate of peroxide formation is not known. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials** : Strong oxidizing agents; Acids; Perchloric acid; Alkalies ; Bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
2-Butoxy ethanol	20 ppm	N/Av	50 ppm (skin)	N/Av
Naphthalene	10 ppm (skin)	N/Av	10 ppm ; 50 mg/m ³	15ppm; 75mg/m ³
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
Cumene	50 ppm	N/Av	50 ppm ; 245 mg/m ³ (Skin)	N/Av
oleic acid	N/Av	N/Av	N/Av	N/Av
Propylbenzene	N/Av	N/Av	N/Av	N/Av
1,2,3-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	ppm (trimethylbenzene) (final rule limit)	N/Av
stoddard solvent	100 ppm	N/Av	500 ppm (2900 mg/m ³)	N/Av
Heavy aromatic solvent naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av
2-Ethylhexyl nitrate	N/Av	N/Av	N/Av	N/Av
2-Ethylhexanol	N/Av	N/Av	N/Av	N/Av

Exposure controls**Ventilation and engineering measures**

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

SAFETY DATA SHEET

- Skin protection** : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye / face protection** : Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.
- Other protective equipment** : Other protective equipment, such as an eyewash station and safety shower, may be required depending on exposure and on workplace standards. Other equipment may be required depending on workplace standards.
- General hygiene considerations** : Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Clear to slightly hazy amber liquid.
- Odour** : Solvent odor.
- Odour threshold** : N/Av
- pH** : N/Av
- Melting/Freezing point** : N/Av
- Initial boiling point and boiling range** : >149°C / >300°F
- Flash point** : 38.3°C / 101°F
- Flashpoint (Method)** : Tag closed cup
- Evaporation rate (BuAe = 1)** : N/Av
- Flammability (solid, gas)** : N/Av
- Lower flammable limit (% by vol.)** : N/Av
- Upper flammable limit (% by vol.)** : N/Av
- Oxidizing properties** : None known.
- Explosive properties** : N/Av
- Vapour pressure** : <3mm Hg @ 20°C
- Vapour density** : >1
- Relative density / Specific gravity** : 0.83
- Solubility in water** : Partially soluble.
- Other solubility(ies)** : N/Av
- Partition coefficient: n-octanol/water or Coefficient of water/oil distribution** : N/Av
- Auto-ignition temperature** : N/Av
- Decomposition temperature** : N/Av
- Viscosity** : N/Av
- Volatiles (% by weight)** : 87%(approximately)
- Volatile organic Compounds (VOC's)** : N/Av
- Absolute pressure of container** : N/Av
- Flame projection length** : N/Av
- Other physical/chemical comments** : None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

- Reactivity** : Not normally reactive.
- Chemical stability** : Stable under normal conditions.

SAFETY DATA SHEET**Possibility of hazardous reactions**

- : Hazardous polymerization will not occur. May be sensitive to static discharge. May form explosive peroxides during prolonged exposure to air and heat. Rate of peroxide formation is not known.

Conditions to avoid

- : Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.

Incompatible materials

- : Strong oxidizing agents; Acids; Perchloric acid; Alkalies ; Bases.

Hazardous decomposition products

- : None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure:**

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: YES

Potential Health Effects:**Signs and symptoms of short-term (acute) exposure***Sign and symptoms Inhalation*

- : Toxic if inhaled. Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowsiness, slurred speech, nausea, and possible nervous system depression.

Sign and symptoms ingestion

- : Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

Sign and symptoms skin

- : Harmful in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation. Causes skin irritation. Symptoms include: Dryness, itching, cracking, burning, redness and swelling.

Sign and symptoms eyes

- : Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

- : Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification Carcinogenicity- Category 2 Suspected of causing cancer.

Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated).

Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B).

Reproductive effects & Teratogenicity

SAFETY DATA SHEET

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification Reproductive Toxicity - Category 2 Suspected of damaging the unborn child. Developmental

Contains Xylene (mixed isomers) Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.

Sensitization to material

: Not expected to be a skin sensitizer.
Not expected to be a respiratory sensitizer.

Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system, blood system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Specific target organ toxicity - single exposure Category 3 May cause drowsiness and dizziness. May cause respiratory irritation.

Not classified as a specific target organ toxicity-repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None reported by the manufacturer.

Toxicological data

: The calculated ATE values for this mixture are:

ATE oral = 246mg/kg

ATE dermal = 1430mg/kg

ATE inhalation (vapours) = 7.99mg/L/4H

ATE inhalation (mists) = 25.6mg/L/4H

See below for individual ingredient acute toxicity data.

Chemical name	LC ₅₀ (4hr)	LD ₅₀	
	inh. rat	(Oral, rat)	(Rabbit, dermal)
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg
2-Butoxy ethanol	450 ppm (2.175 mg/L)	530 mg/kg	400 - 500 mg/kg
Naphthalene	No information available.	490 mg/kg	>20,000 mg/kg
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethyl benzene	24 mg/L	23 000 mg/kg	>3160mg/kg
Xylene (mixed isomers)	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
Cumene	8000 ppm; 39 mg/L	2260 mg/kg	10 627 mg/kg
oleic acid	N/Av	>19200 mg/kg	>3000mg/kg guinea pig
Propylbenzene	159.25mg/L	6040 mg/kg	N/Av
1,2,3-Trimethylbenzene	18 - 24mg/L/4H (based on similar substances)	4472mg/kg	>3160mg/kg
stoddard solvent	> 5.5 mg/L (vapour)	> 5000 mg/kg	> 3000 mg/kg
Heavy aromatic solvent naphtha	> 17.1 mg/L/4 hours	> 6000 mg/kg	> 3160 mg/kg
2-Ethylhexyl nitrate	> 14 mg/L	>10mg/L (>9600mg/kg)	>5 mL/kg (>4800mg/kg)
2-Ethylhexanol	≥1.2 - <5.3 mg/L	2052mg/kg	No information available.

SAFETY DATA SHEET

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

Ingredients	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.
2-Butoxy ethanol	111-76-2	1490 mg/L (Lepomis macrochirus)	>100mg/L (Zebra fish)	none
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	0.12mg/L (40 days) (pink salmon)	none
1,2,4-Trimethylbenzene	95-63-6	7.19 - 8.28 mg/L (Fathead minnow)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.
Xylene (mixed isomers)	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Cumene	98-82-8	4.5mg/L (Rainbow trout)	0.38mg/L QSAR	None.
oleic acid	112-80-1	205 mg/L (Fathead minnow)	N/Av	None.
Propylbenzene	103-65-1	1.55mg/L (Rainbow trout)	N/Av	None.
1,2,3-Trimethylbenzene	526-73-8	7.8mg/L (Species not specified)	N/Av	None.
stoddard solvent	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Heavy aromatic solvent naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	none
2-Ethylhexyl nitrate	27247-96-7	2 mg/L (Zebra fish)	N/Av	None.
2-Ethylhexanol	104-76-7	2 mg/L (Zebra fish)	N/Av	None.

SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.
2-Butoxy ethanol	111-76-2	835mg/L (Daphnia magna)	100mg/L (Daphnia magna)	none
Naphthalene	91-20-3	3.4 mg/L/ (Water flea)	0.6mg/L	none
1,2,4-Trimethylbenzene	95-63-6	6.14 mg/L (Daphnia magna)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna)	0.4mg/L	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Cumeme	98-82-8	2.14 mg/L (Daphnia magna)	0.35mg/L	None.
oleic acid	112-80-1	N/Av	N/Av	None.
Propylbenzene	103-65-1	2mg/L/24hr	N/Av	None.
1,2,3-Trimethylbenzene	526-73-8	2.7mg/L (Water flea)	N/Av	None.
stoddard solvent	8052-41-3	0.42 - 2.3 mg/L (Daphnia magna) (Closed systems - low end; Open systems - high end)	0.1 - 0.37 mg/L	None.
Heavy aromatic solvent naphtha	64742-94-5	1.1 mg/L (Water flea)	N/Av	none
2-Ethylhexyl nitrate	27247-96-7	> 12.6 mg/L [Daphnia magna (Water flea)]	N/Av	None.
2-Ethylhexanol	104-76-7	>12.6mg/L (Daphnia magna)	N/Av	None.

SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av
2-Butoxy ethanol	111-76-2	911mg/L/72hr	286mg/L/72hr	none
Naphthalene	91-20-3	0.4mg/L/72hr (Marine diatom)	N/Av	none
1,2,4-Trimethylbenzene	95-63-6	N/Av	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	3.191mg/L QSAR	N/Av	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Cumeme	98-82-8	1.29mg/L/72hr (Green algae)	0.73mg/L	None.
oleic acid	112-80-1	N/Av	N/Av	None.
Propylbenzene	103-65-1	1.8mg/L/72hr (Green algae)	N/Av	None.
1,2,3-Trimethylbenzene	526-73-8	5.7mg/L	N/Av	None.
stoddard solvent	8052-41-3	0.58 - 1.2 mg/L/72hr (Green algae) (Closed systems - low end; Open systems - high end)	0.16 mg/L/72hr	None.
Heavy aromatic solvent naphtha	64742-94-5	7.2 mg/L/72 hours (Green algae)	0.22 mg/L/72 hours (Green algae)	none
2-Ethylhexyl nitrate	27247-96-7	1.57 mg/L/72hr (Green algae)	12.6mg/L/72hr	None.
2-Ethylhexanol	104-76-7	1.57mg/L/72hr (Green algae)	12.6mg/L/72hr	None.

Persistence and degradability

: No data is available on the product itself. The following ingredients are considered to be readily biodegradable: 2-butoxyethanol, 2-Ethylhexanol

Bioaccumulation potential

: No data is available on the product itself.

See the following data for ingredient information.

SAFETY DATA SHEET

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Light aromatic solvent naphtha (CAS 64742-95-6)	2.1 - 6(calculated)	
2-Butoxy ethanol (CAS 111-76-2)	0.81 at 25 °C	
Naphthalene (CAS 91-20-3)	3.7	30 - 430 species: fish
1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78	
1,3,5-Trimethyl benzene (CAS 108-67-8)	3.6 - 3.93	
Xylene (mixed isomers) (CAS 1330-20-7)	3.12 - 3.2	0.6 - 15
Cumene (CAS 98-82-8)	3.55 at 23 °C	35.5 species: fish
oleic acid (CAS 112-80-1)	7.64	
Propylbenzene (CAS 103-65-1)	3.68	
1,2,3-Trimethylbenzene (CAS 526-73-8)	3.76	
stoddard solvent (CAS 8052-41-3)	3.16 - 7.06	No information available.
Heavy aromatic solvent naphtha (CAS 64742-94-5)	2.9 - 6.1	No information available.
2-Ethylhexyl nitrate (CAS 27247-96-7)	5.24	No information available.
2-Ethylhexanol (CAS 104-76-7)	5.24	No information available.

Mobility in soil : No data is available on the product itself.



Other Adverse Environmental effects

: The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Aromatic naphtha)	3	III	
49CFR/DOT Additional information	This material may be reclassified as a 'Combustible liquid', when shipping by ground within the United States only. Combustible liquids may be shipped as non-hazardous material when shipped in non-bulk containers (450 L / 119 Gallons or less). Refer to 49 CFR Section 173.150. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (stoddard solvent; Aromatic naphtha)	3	III	

SAFETY DATA SHEET

TDG This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met.

Additional information This product meets the criteria for an environmentally hazardous material according to the IMDG Code.

Special precautions for user : Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	<u>CAS #</u>	<u>TSCA Inventory</u>	<u>CERCLA Reportable Quantity(RQ) (40 CFR 117.302):</u>	<u>SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:</u>	<u>SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical</u>	<u>de minimus Concentration</u>
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	N/Ap
2-Butoxy ethanol	111-76-2	Yes	N/Ap	N/Av	No	N/Ap
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	N/Av	Yes	0.1%
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	1%
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Av	No	N/Ap
Xylene (mixed isomers)	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%
Cumene	98-82-8	Yes	5000 lb/ 2270 kg	N/Ap	Yes	1%
oleic acid	112-80-1	Yes	N/Ap	N/Av	No	N/Ap
Propylbenzene	103-65-1	Yes	N/Ap	N/Av	No	N/Ap
1,2,3-Trimethylbenzene	526-73-8	Yes	N/Ap	N/Av	No	N/Ap
stoddard solvent	8052-41-3	Yes	None.	None.	No	N/Ap
Heavy aromatic solvent naphtha	64742-94-5	Yes	N/Ap	N/Av	No	N/Ap
2-Ethylhexyl nitrate	27247-96-7	Yes	N/Ap	N/Av	No	N/Ap
2-Ethylhexanol	104-76-7	Yes	N/Ap	N/Av	No	N/Ap

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS #</u>	<u>California Proposition 65</u>		<u>State "Right to Know" Lists</u>					
		<u>Listed</u>	<u>Type of Toxicity</u>	<u>CA</u>	<u>MA</u>	<u>MN</u>	<u>NJ</u>	<u>PA</u>	<u>RI</u>
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No
2-Butoxy ethanol	111-76-2	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
Naphthalene	91-20-3	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No
Xylene (mixed isomers)	1330-20-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
Cumene	98-82-8	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
oleic acid	112-80-1	No	Not listed	No	No	No	No	Yes	No
Propylbenzene	103-65-1	No	Not listed	No	Yes	No	Yes	Yes	No
1,2,3-Trimethylbenzene	526-73-8	No	Not listed	No	No	No	No	No	No
stoddard solvent	8052-41-3	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
Heavy aromatic solvent naphtha	64742-94-5	No	Not listed	No	No	No	No	No	No
2-Ethylhexyl nitrate	27247-96-7	No	Not listed	No	No	No	No	No	No
2-Ethylhexanol	104-76-7	No	Not listed	No	Yes	No	No	Yes	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

SAFETY DATA SHEET

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard
2-Butoxy ethanol	111-76-2	203-905-0	Present	Present	(7)-97; (2)-407	KE-04134	Present	HSR001154
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
Xylene (mixed isomers)	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Cumene	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184
oleic acid	112-80-1	204-007-1	Present	Present	(2)-975; (2)-609	KE-26450	Present	HSR003153
Propylbenzene	103-65-1	203-132-9	Present	Present	(3)-21	KE-29781	Present	HSR005222
1,2,3-Trimethylbenzene	526-73-8	208-394-8	Present	Present	(3)-7; (3)-3427	KE-34409	Present	HSR004095
stoddard solvent	8052-41-3	232-489-3	Present	Present	(9)-1702	KE-32199	Present	HSR001498
Heavy aromatic solvent naphtha	64742-94-5	265-198-5	Present	Present	(3)-7	KE-31656	Present	May be used as a single component chemical under an appropriate group standard
2-Ethylhexyl nitrate	27247-96-7	248-363-6	Present	Present	(2)-3598	KE-13803	Present	May be used as a single component chemical under an appropriate group standard
2-Ethylhexanol	104-76-7	203-234-3	Present	Present	(2)-217	KE-13766	Present	HSR001386

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- ATE: Acute Toxicity Estimate
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CNS: Central Nervous System
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%.
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- IMDG: International Maritime Dangerous Goods
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose

SAFETY DATA SHEET

MA: Massachusetts
MN: Minnesota
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
NJ: New Jersey
NOEC: No observable effect concentration
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

: Canadian Centre for Occupational Health and Safety (CCOHS), CCInfoWeb databases, 2015 (CHEMINFO, HSDB and RTECS). OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015 European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer Information taken from reference works and the literature.

Preparation Date (mm/dd/yyyy)

: 05/26/2015

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

FPPF Chemical Company, Inc.
117 West Tupper Street
Buffalo, NY, USA 14201
Telephone: 1-800-735-3773
Please direct all enquiries to FPPF Chemical Company

Prepared by:

ICC The Compliance Center Inc.
Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)
<http://www.thecompliancecenter.com>



DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

END OF DOCUMENT