

MATERIAL SAFETY DATA SHEET

Product Trade Name: **DCA-31003**

Revision Date: 09-Dec-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DCA-31003
Synonyms: None
Chemical Family: Blend
Application: Solvent

Manufacturer/Supplier: Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Ethylene glycol monobutyl ether	111-76-2	60 - 100%	TWA: 20 ppm	50 ppm
Ethoxylated hexanol	68439-45-2	10 - 30%	Not applicable	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory burns. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. Combustible.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion If swallowed, induce vomiting immediately by giving two glasses of water and sticking fingers down throat; never give anything to an unconscious person. Get medical attention.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	152
Flash Point/Range (C):	66
Flash Point Method:	Not Determined
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	1.1
Flammability Limits in Air - Upper (%):	10.6

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 2, Reactivity 0
HMIS Ratings: Health 2, Flammability 2, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Store in a well ventilated area. Store locked up. Product has a shelf life of 60 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Not normally needed. But if significant exposures are possible then the following respirator is recommended:
Organic vapor respirator.

Hand Protection Impervious rubber gloves. Nitrile gloves. Neoprene gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Clear colorless
Odor:	Mild
pH:	Not Determined
Specific Gravity @ 20 C (Water=1):	0.9
Density @ 20 C (lbs./gallon):	7.55
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	340
Boiling Point/Range (C):	171
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	5
Vapor Density (Air=1):	<1
Percent Volatiles:	50
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Miscible
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

Causes eye irritation. May cause severe eye irritation.

Skin Contact

Causes moderate skin irritation. May cause skin burns. May be absorbed through the skin and contribute to the symptoms listed under ingestion.

Ingestion

May affect the blood and blood system. Coma, shock and death may occur.

Chronic Effects/Carcinogenicity

Prolonged or repeated exposure may cause fetal damage and testicular effects. Prolonged or repeated exposure may cause kidney, lung and blood effects. May contain ethylene oxide in the headspace of the drum. Ethylene oxide is a cancer and reproductive hazard.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol monobutyl ether	111-76-2	470 mg/kg (Rat) 1414 mg/kg (Guinea pig) 1746 mg/kg (Rat)	220 mg/kg (Rabbit) 2270 mg/kg (Rat) 200 mg/kg (Guinea pig) >2000 mg/kg (Rabbit) 841 mg/kg (Rabbit) 435 mg/kg (Rabbit) >2000 mg/kg (Guinea pig) >2000 mg/kg (Rat)	450 ppm (Rat) 4 h 2.174 mg/L (Rat) 4 h
Ethoxylated hexanol	68439-45-2	500 mg/kg	No data available	No data available

12. ECOLOGICAL INFORMATION**Ecotoxicological Information****Ecotoxicity Product**

Acute Fish Toxicity: Not determined
Acute Crustaceans Toxicity: TLM96: 100-330 ppm (Crangon crangon)
Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethylene glycol monobutyl ether	111-76-2	EC50: 839.56 mg/l (Skeletonema costatum) EC50(72h): 911 mg/L (biomass) EC50: > 500 mg/l (Scenedesmus subspicatus) NOEC(72h): 88 mg/L (biomass)(Pseudokirchnerella subcapitata)	LC50: > 1000 mg/l (Scophthalmus maximus juvenile) LC50(96h): 1474 mg/L (Oncorhynchus mykiss) NOAC(21d): > 100mg/L (Danio rerio)	TT/EC3(48h): 463 mg/L (Uronema parduzci) TT/EC3(72h): 73 mg/L (Entosiphon sulcatum) TT/EC3(16h): 700 mg/L (Pseudomonas putida)	EC50: >1000 mg/L (Daphnia magna) EC50 (48h): 1800 mg/L (Daphnia magna) EC50: 1875 mg/l (Daphnia magna) NOEC(21d)(reproduction) : 100 mg/L (Daphnia magna)
Ethoxylated hexanol	68439-45-2	No information available	No information available	No information available	No information available

12.2 Persistence and degradability

Readily biodegradable

12.3 Bioaccumulative potential

Does not bioaccumulate

Substances	Log Pow
Ethylene glycol monobutyl ether	0.81

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects**13. DISPOSAL CONSIDERATIONS**

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations. Incineration recommended in approved incinerator according to federal, state, and local regulations. Substance should NOT be deposited into a sewage facility.
Contaminated Packaging	Follow all applicable national or local regulations. Contaminated packaging may be disposed of by: rendering packaging incapable of containing any substance, or treating packaging to remove residual contents, or treating packaging to make sure the residual contents are no longer hazardous, or by disposing of packaging into commercial waste collection.

14. TRANSPORT INFORMATION

Land Transportation

DOT

Not restricted

DOT (Bulk)

NA1993, Combustible Liquid, N.O.S., Combustible Liquid, III
(Contains Ethylene Glycol Monobutyl Ether)

Canadian TDG

Not restricted

ADR

Not restricted

Air Transportation

ICAO/IATA

Not restricted

Sea Transportation

IMDG

Not restricted

Other Transportation Information

Labels: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Glycol Ethers//111-76-2
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	B3 Combustible Liquids D1A Very Toxic Materials D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

END OF MSDS