

MATERIAL SAFETY DATA SHEET

Product Trade Name: DCA-31007

Revision Date: 06-Jan-2015

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DCA-31007
Synonyms: None
Chemical Family: Glycol Ether
Application: Solvent

Manufacturer/Supplier Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Ethylene glycol monobutyl ether	111-76-2	60 - 100%	TWA: 20 ppm Skin	TWA: 50 ppm Skin

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. May be absorbed through the skin. Combustible

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	153
Flash Point/Range (C):	67
Flash Point Method:	DIN 51758
Autoignition Temperature (F):	446
Autoignition Temperature (C):	230
Flammability Limits in Air - Lower (%):	1.1
Flammability Limits in Air - Upper (%):	10.6

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 2, Reactivity 0
HMIS Ratings: Health 2, Flammability 2, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from oxidizers. Store in a cool well ventilated area. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 60 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection If engineering controls and work practices cannot keep exposure below occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified professional.
Organic vapor respirator.

Hand Protection	Chemical-resistant protective gloves (EN 374) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Nitrile gloves. (>= 0.65 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. Manufacturer's directions for use should be observed because of great diversity of types.
Skin Protection	Rubber apron.
Eye Protection	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Colorless
Odor:	Mild
pH:	Not Determined
Specific Gravity @ 20 C (Water=1):	0.9
Density @ 20 C (lbs./gallon):	7.51
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	340
Boiling Point/Range (C):	171
Freezing Point/Range (F):	-94
Freezing Point/Range (C):	-70
Vapor Pressure @ 20 C (mmHg):	0.76
Vapor Density (Air=1):	4.1
Percent Volatiles:	100
Evaporation Rate (Butyl Acetate=1):	0.06
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	0.8
Molecular Weight (g/mole):	118.2

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	None anticipated
Incompatibility (Materials to Avoid)	Strong oxidizers. Peroxides. Amphoteric metals such as aluminum, magnesium, lead, tin, or zinc.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

May cause eye irritation

Skin Contact

May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause skin irritation.

Ingestion

May cause abdominal pain, vomiting, nausea, and diarrhea. May produce nervous system effects such as feeling of weakness, unsteady walk, and dilation of blood vessels.

Chronic Effects/Carcinogenicity

Prolonged or repeated exposure may cause fetal damage and testicular effects.

LD50 Oral: 1746 mg/kg; (rat)

LD50 Dermal: 2270 mg/kg; (rat)

LC50 Inhalation: 2.21 mg/L; (rat); (4-hr)

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol monobutyl ether	111-76-2	470 mg/kg (Rat) 1414 mg/kg (Guinea pig) 1746 mg/kg (Rat) 320 mg/kg (Rabbit) 530 mg/kg (Rat) 560 mg/kg (Rat) 3000 mg/kg (Rat) 2400 mg/kg (Rat)	220 mg/kg (Rabbit) 2270 mg/kg (Rat) 200 mg/kg (Guinea pig) >2000 mg/kg (Rabbit) 841 mg/kg (Rabbit) 435 mg/kg (Rabbit) >2000 mg/kg (Guinea pig) >2000 mg/kg (Rat) 100 mg/kg (Rabbit) 207 mg/kg (Guinea pig) 400-500 mg/kg (Rabbit)	450 ppm (Rat) 4h 2.174 mg/L (Rat) 4h 2.21 mg/L (Rat) 4h 450-486 ppm (Rat) 4h 925 ppm (Rat) 4h >633 ppm (Guinea pig) 1h

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: LC50(96h): > 1000 mg/l (Scophthalmus maximus juvenile)

Acute Crustaceans Toxicity: EC50: 1875 mg/l (Daphnia magna)

Acute Algae Toxicity: EC50: > 500 mg/l (Scenedesmus subspicatus)

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Ethylene glycol monobutyl ether	111-76-2	EC50: 839.56 mg/l (Skeletonema costatum) EC50(72h): 911 mg/L (biomass) EC50: > 500 mg/l (Scenedesmus subspicatus) NOEC(72h): 88 mg/L (biomass)(Pseudokirchnerella subcapitata)	LC50: > 1000 mg/l (Scophthalmus maximus juvenile) LC50(96h): 1474 mg/L (Oncorhynchus mykiss) NOEC(21d): > 100mg/L (Danio rerio)	TT/EC3(48h): 463 mg/L (Uronema parduzci) TT/EC3(72h): 73 mg/L (Entosiphon sulcatum) TT/EC3(16h): 700 mg/L (Pseudomonas putida)	EC50: >1000 mg/L (Daphnia magna) EC50 (48h): 1800 mg/L (Daphnia magna) EC50: 1875 mg/l (Daphnia magna) NOEC(21d)(reproduction): 100 mg/L (Daphnia magna)

12.2. Persistence and degradability

Readily biodegradable

Substances	CAS Number	Persistence and Degradability
------------	------------	-------------------------------

Ethylene glycol monobutyl ether	111-76-2	Readily biodegradable (75-88% @ 28d)
---------------------------------	----------	--------------------------------------

12.3. Bioaccumulative potential

Does not bioaccumulate

Substances	CAS Number	Log Pow
Ethylene glycol monobutyl ether	111-76-2	0.81

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).

12.6. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations. Incineration recommended in approved incinerator according to federal, state, and local regulations. Substance should NOT be deposited into a sewage facility.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

US DOT Bulk

DOT (Bulk) NA1993, Combustible Liquid, N.O.S., Combustible Liquid, III
(Contains Ethylene Glycol Monobutyl Ether)

Canadian TDG ul0

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

IMDG/IMO

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

IATA/ICAO

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	Not applicable
EPA SARA (311,312) Hazard Class	Acute Health Hazard Chronic Health Hazard Fire Hazard
EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Glycol Ethers//111-76-2
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.

Canadian Regulations

Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	B3 Combustible Liquids D1A Very Toxic Materials D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional information For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

END OF MSDS

DCA-31007

Page 6 of 7