

MATERIAL SAFETY DATA SHEET

Product Trade Name: **DISPOSAL WELL ACID**

Revision Date: 03-Jan-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DISPOSAL WELL ACID
Synonyms: None
Chemical Family: Inorganic acid
Application: Acid

Manufacturer/Supplier: Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Hydrofluoric acid	7664-39-3	1 - 5%	0.5 ppm	3 ppm
Hydrochloric acid	7647-01-0	10 - 30%	2 ppm	5 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory burns. May be fatal if swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse. Wearing protective gloves, apply 2.5% calcium gluconate gel at burn site rubbing continuously.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Apply 1 to 2 drops of 0.5% Pontocaine Hydrochloride into open eye. Irrigate with 1.0% calcium gluconate in normal saline for 1 to 2 hours.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	Not Determined
Flash Point/Range (C):	Not Determined
Flash Point Method:	Not Determined
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media All standard firefighting media.

Special Exposure Hazards Decomposition in fire may produce toxic gases. Reaction with steel and certain other metals generates flammable hydrogen gas. Do not allow runoff to enter waterways.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 4, Flammability 0, Reactivity 1
HMS Ratings: Health 4, Flammability 0, Reactivity 0,

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear full protective gear. Reaction can be violent and harmful vapors may be released.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Neutralize to pH of 6-8. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from alkalis. Store in a cool well ventilated area. Keep container closed when not in use. Do not store in containers made of fiberglass.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Acid gas respirator.

Hand Protection Impervious rubber gloves.

Skin Protection Full protective chemical resistant clothing. Rubber boots.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear colorless
Odor:	Pungent irritating
pH:	0.5
Specific Gravity @ 20 C (Water=1):	1.09
Density @ 20 C (lbs./gallon):	9.08
Bulk Density @ 20 C (lbs/ft ³):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	100
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	None anticipated
Incompatibility (Materials to Avoid)	Silicone bearing materials. Strong alkalis. Contact with metals.
Hazardous Decomposition Products	Flammable hydrogen gas. Chlorine. Hydrogen fluoride. Hydrogen sulfide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	May cause lungs to fill with fluids. Causes severe respiratory burns.
Skin Contact	Effects on skin may be delayed for 24-48 hours. Harmful if absorbed through the skin. Causes skin burns which may not be immediately painful or visible.
Eye Contact	Causes eye burns.
Ingestion	May cause damage to bones and teeth. Causes burns of the mouth, throat and stomach.
Aggravated Medical Conditions	Skin disorders.
Chronic Effects/Carcinogenicity	Prolonged or repeated exposure may result in fluorosis. Symptoms include nausea, vomiting, loss of appetite, diarrhea, and/or constipation. Fluorosis also results in bone density increase. Prolonged, excessive exposure may cause erosion of the teeth.
Other Information	None known.

Toxicity Tests

Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined
Carcinogenicity	Not determined
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined
Persistence/Degradability	Not determined
Bio-accumulation	Not determined

Ecotoxicological Information

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	TLM96: 200 ppm (Ceriodaphnia dubia)
Acute Algae Toxicity:	Not determined

Chemical Fate Information	Not determined
Other Information	Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN3264, Corrosive Liquid, Acidic, Inorganic, N.O.S. (Contains Hydrochloric Acid, Hydrofluoric Acid), 8, II
RQ (Hydrochloric Acid - 2273 kg., Hydrofluoric Acid - 45.4 kg.)
NAERG 154

Canadian TDG

Corrosive Liquid, Acidic, Inorganic, N.O.S. (Contains Hydrochloric Acid, Hydrofluoric Acid), 8, UN3264, II

ADR

UN3264, Corrosive Liquid, Acidic, Inorganic, N.O.S. (Contains Hydrochloric Acid, Hydrofluoric Acid), 8, II

Air Transportation

ICAO/IATA

UN3264, Corrosive Liquid, Acidic, Inorganic, N.O.S., 8, II
(Contains Hydrochloric Acid, Hydrofluoric Acid)
RQ (Hydrochloric Acid - 2273 kg., Hydrofluoric Acid - 45.4 kg.)

Sea Transportation

IMDG

UN3264, Corrosive Liquid, Acidic, Inorganic, N.O.S. (Contains Hydrochloric Acid, Hydrofluoric Acid), 8, II
RQ (Hydrochloric Acid - 2273 kg., Hydrofluoric Acid - 45.4 kg.)
EmS F-A, S-B

Other Transportation Information

Labels: Corrosive

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	CAS: 7664-39-3//Chemical Name: Hydrogen Fluoride//TPQ: 500
EPA SARA (311,312) Hazard Class	Acute Health Hazard
EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Hydrogen Fluoride//7664-39-3
EPA CERCLA/Superfund Reportable Spill Quantity	EPA Reportable Spill Quantity is 367 Gallons based on Hydrofluoric acid (CAS: 7664-39-3).
EPA RCRA Hazardous Waste Classification	Corrosivity D002 If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.

WHMIS Hazard Class

E Corrosive Material
D1B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****