HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: DOC-3 SURFACTANT

Revision Date: 04-Jan-2011

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DOC-3 SURFACTANT

Synonyms:NoneChemical Family:BlendApplication:Surfactant

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Imidazoline		60 - 100%	Not applicable	Not applicable
Isopropanol	67-63-0	10 - 30%	200 ppm	400 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye and skin burns. May cause respiratory irritation. May cause

headache, dizziness, and other central nervous system effects. May be harmful if swallowed. Repeated overexposure may cause liver and kidney effects. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15

minutes. Get medical attention. Remove contaminated clothing and launder before

reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

FIRE FIGHTING MEASURES

Flash Point/Range (F): 54 Flash Point/Range (C): 12 **Flash Point Method: PMCC**

Autoignition Temperature (F): Not Determined **Autoignition Temperature (C):** Not Determined

Flammability Limits in Air - Lower (%): 2 Flammability Limits in Air - Upper (%): 12.7

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed

surfaces. Closed containers may explode in fire. Decomposition in fire may produce

toxic gases.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

NFPA Ratings: Health 3, Flammability 3, Reactivity 0 Health 3, Flammability 3, Reactivity 0 **HMIS Ratings:**

ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in

enclosed areas.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate spill and stop leak where safe. Remove ignition sources and work with nonsparking tools. Contain spill with sand or other inert materials. Scoop up and

remove.

HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after

use. Launder contaminated clothing before reuse. Ground and bond containers

when transferring from one container to another.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container

closed when not in use.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas

without good cross ventilation.

Organic vapor/acid gas respirator with a dust/mist filter. **Respiratory Protection**

Hand Protection Impervious rubber gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:LiquidColor:Brown

Odor: Musty alcohol

 pH:
 11-12

 Specific Gravity @ 20 C (Water=1):
 0.9

 Density @ 20 C (lbs./gallon):
 7.50

Bulk Density @ 20 C (lbs/ft3):

Boiling Point/Range (F):

Not Determined

Vapor Pressure @ 20 C (mmHg):

Not Determined

Percent Volatiles: 25

Evaporation Rate (Butyl Acetate=1):

Solubility in Water (g/100ml):

Not Determined
Insoluble

Solubility in Solvents (g/100ml): Not Determined VOCs (lbs./gallon): Not Determined

Viscosity, Dynamic @ 20 C (centipoise): 40-60

Viscosity, Kinematic @ 20 C (centistrokes):

Partition Coefficient/n-Octanol/Water:

Molecular Weight (g/mole):

Not Determined

Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid Keep away from heat, sparks and flame.

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong alkalis.

Hazardous Decomposition

Products

Oxides of nitrogen. Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Inhalation Causes severe respiratory irritation. May cause central nervous system depression

including headache, dizziness, drowsiness, incoordination, slowed reaction time.

slurred speech, giddiness and unconsciousness.

Skin ContactCauses severe skin irritation. May cause skin burns. May be absorbed through the

skin and produce effects similar to those caused by inhalation and/or ingestion.

Eye Contact May cause eye burns.

Ingestion Irritation of the mouth, throat, and stomach. May cause abdominal pain, vomiting,

nausea, and diarrhea. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatique blurred vision, slurred speech, giddiness, tremors and

convulsions.

Aggravated Medical Conditions Skin disorders. Eye ailments.

Chronic Effects/Carcinogenicity Repeated overexposure may cause liver and kidney effects.

Other Information None known.

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Draize Rating (Eye): 110/110 (Rabbit) Corrosive Draize Rating (Skin): 8.0/8.0

(Rabbit) Corrosive

Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

Developmental Toxicity:

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Slowly biodegradable

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal MethodDisposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

Not determined

14. TRANSPORT INFORMATION

Land Transportation

Chemical Fate Information

DOT

UN1219, Isopropanol Solution, 3, II, (12.2 C) NAERG 129

Canadian TDG

Isopropanol Solution, 3, UN1219, II, (12.2 C)

ADR

UN1219, Isopropanol Solution, 3, II

Air Transportation

ICAO/IATA

UN1219, Isopropanol Solution, 3, II

Sea Transportation

IMDG

UN1219, Isopropanol Solution, 3, II, (12.2 C) EmS F-E, S-D

Other Shipping Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard Chronic Health Hazard

Fire Hazard

EPA SARA (313) Chemicals This product contains toxic chemical(s) listed below which is(are) subject to the

reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Isopropanol//67-63-0

EPA CERCLA/Superfund Reportable Spill Quantity

Not applicable.

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does meet the criteria of a hazardous waste as

defined by the US EPA, because of:

Ignitability D001

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law
One or more components listed.

NJ Right-to-Know Law
One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory

All components listed on inventory.

WHMIS Hazard Class

B2 Flammable Liquids D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

END OF MSDS