

Product name:	DP-LUBRICANT BROWN	Page:	1/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0118	SDS-ID:	AU-EN/15.0

---

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product name: DP-LUBRICANT BROWN  
Cat. No. 40700028

Container size: 1 l

### Relevant identified uses of the substance or mixture and uses advised against

Application: For materialographic preparation

### Details of the supplier of the safety data sheet

Supplier: Struers Australia  
27 Mayneview Street  
Milton QLD 4064, Australia

Responsible for safety data sheet authoring: Responsible for safety data sheet authoring: DHI  
Any questions to the contents of this safety data sheet should be sent to:  
Lisbeth.Mygind@struers.dk

### Emergency telephone number

Emergency telephone: +61 7 3512 9600  
(Only during office hours)

---

# SAFETY DATA SHEET

Product name: DP-LUBRICANT BROWN Page: 2/9  
Revision Date: 2014-09-24 Print date: 2014-09-24  
Document No.: M0118 SDS-ID: AU-EN/15.0

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the substance or mixture

This product is classified as hazardous according to criteria of NOHSC:  
HAZARDOUS SUBSTANCES. DANGEROUS GOODS

67/548/EEC / 1999/45/EC: F;R11

GHS: Flam. Liq. 2;H225 - Eye Irrit. 2;H319 (\*)

### Label elements

(\*)



Danger

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves, eye and face protection.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P501 Dispose of contents/container in accordance with local regulations.

### Other hazards

PBT/vPvB: Not relevant.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

The product contains: organic solvents and pigments.

67/548/EEC:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
70-85	64-17-5	200-578-6	-	Ethanol	F;R11	
5-<10	67-63-0	200-661-7	01-2119457558-25-xxxx	Propan-2-ol	F;R11 Xi;R36 R67	
10-20	-	-	-	Glycol	-	
<0,1	-	-	-	Pigment	-	

# SAFETY DATA SHEET

Product name: DP-LUBRICANT BROWN Page: 3/9  
Revision Date: 2014-09-24 Print date: 2014-09-24  
Document No.: M0118 SDS-ID: AU-EN/15.0

---

## GHS:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
70-85	64-17-5	200-578-6	-	Ethanol	Flam. Liq. 2;H225 Eye Irrit. 2;H319	
5-<10	67-63-0	200-661-7	01-2119457558-25-xxxx	Propan-2-ol	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
10-20	-	-	-	Glycol	-	
<0,1	-	-	-	Pigment	-	

References: The full text for all R-phrases and hazard statements are displayed in section 16.

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move into fresh air and keep at rest.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

### Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

### Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

## SECTION 5: FIREFIGHTING MEASURES

### Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

### Special hazards arising from the substance or mixture

Specific hazards: The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures. Vapours may be ignited by a spark, a hot surface or an ember.

### Advice for firefighters

Protective equipment for fire-fighters: Use air-supplied respirator during fire fighting.

---

# SAFETY DATA SHEET

Product name:	DP-LUBRICANT BROWN	Page:	4/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0118	SDS-ID:	AU-EN/15.0

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not smoke or use open fire, or other sources of ignition. Avoid inhalation of vapours and contact with skin and eyes.

### Environmental precautions

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

### Methods and material for containment and cleaning up

Methods for containment: Large quantities of concentrate should not be discharged into the drain but removed with absorbing material. Do not use sawdust or other combustible material.

### Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Safe handling advice: Avoid inhalation of vapours and contact with skin and eyes. Observe good chemical hygiene practices. Take precautionary measures against static discharges.

Technical measures: Do not smoke or use open fire or other sources of ignition.

Technical precautions: Local exhaust is recommended.

### Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids. Large amounts and storages should be stored in accordance with national regulation on storage of flammable liquids.

Storage conditions: Store in a cool and well-ventilated place. Avoid contact with oxidising agents.

### Specific end use(s)

Specific use(s): Not relevant.

---

# SAFETY DATA SHEET

Product name: DP-LUBRICANT BROWN Page: 5/9  
Revision Date: 2014-09-24 Print date: 2014-09-24  
Document No.: M0118 SDS-ID: AU-EN/15.0

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>		<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
67-63-0	Isopropyl alcohol	-	400 ppm	983 mg/m3	TWA	-	NOHSC
		-	500 ppm	1230 mg/m3	STEL	15min	
64-17-5	Ethyl alcohol	-	1000 ppm	1880 mg/m3	TWA	-	NOHSC

### Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Personal protection: Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with gas filter, type A2.

Hand protection: Wear protective gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection: Wear goggles/face shield. (\*)

Skin protection: No special precautions.

Environmental Exposure Controls: Not available.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance: brown liquid

Odour: odour of alcohol

pH: Not available.

Boiling point: 85°C

Flash point: 13°C

Relative density: 0,8

Solubility: Miscible with water.

### Other information

Other data: Volatile Organic Compound (VOC): 696 g/l (calculated)

---

# SAFETY DATA SHEET

Product name:	DP-LUBRICANT BROWN	Page:	6/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0118	SDS-ID:	AU-EN/15.0

---

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

Reactivity: None known.

### Chemical stability

Stability: Stable under normal temperature conditions.

### Possibility of hazardous reactions

Hazardous Reactions: None known.

### Conditions to avoid

Conditions/materials to avoid: Direct sunlight. Heating. Oxidizing agents.

### Incompatible materials

Incompatible materials: None known.

### Hazardous decomposition products

Hazardous decomposition products: None in particular.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on toxicological effects

In case of insufficient ventilation, extensive use may cause the damage described below.

Inhalation: Small quantities: Vapours may irritate throat and respiratory system and cause coughing.  
Large quantities: Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. In serious cases, unconsciousness and permanent damage to the nervous system, including the brain, and liver may be seen.

Skin contact: Prolonged contact may cause redness, irritation and dry skin.  
Contains 2-propanol which may penetrate the skin.

Eye contact: Causes serious eye irritation. (\*)

Ingestion: May irritate and cause malaise.

Specific effects: Frequent inhalation of even small concentrations may cause irritability, fatigue, memory failure and in time permanent damage to the nervous system, including the brain, and possibly liver and kidneys, too.

Carcinogenicity:  
National Toxicology Program (NTP): No.  
I.A.R.C. Monographs: No.

---

# SAFETY DATA SHEET

Product name: DP-LUBRICANT BROWN  
Revision Date: 2014-09-24  
Document No.: M0118

Page: 7/9  
Print date: 2014-09-24  
SDS-ID: AU-EN/15.0

---

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

Ecotoxicity: The product is not expected to be hazardous to the environment.

### Persistence and degradability

Degradability: The product is 80% biodegradable.

### Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

### Mobility in soil

Mobility: No data available.

### Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

### Other adverse effects

Other adverse effects: None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 16 05 08

---

# SAFETY DATA SHEET

Product name:	DP-LUBRICANT BROWN	Page:	8/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0118	SDS-ID:	AU-EN/15.0

---

## SECTION 14: TRANSPORT INFORMATION

### UN number

UN-No: 1993

### UN proper shipping name

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S (Ethanol, Isopropylalcohol Mixture)

Additional IMDG information:

EmS: F-E , S-E

MFAG: 1

### Transport hazard class(es)

Class: 3

### Packing group

PG: II

### Environmental hazards

Marine pollutant: No.

Environmentally Hazardous substance: No.

### Special precautions for user

Special precautions: None known.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: AICS: Listed.

National regulation: National Standard: Approved criteria for classifying hazardous substances [NOHSC:1008(2004)]. 3rd Edition.  
National model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals (2011).  
National Exposure Standard [NOHSC:1003(1995)].  
The Industrial Chemicals (Notification and Assessment) Act 1989 (Commonwealth), including listing on the Australian Inventory of Chemical Substances (AICS).  
Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.

### Chemical Safety Assessment

CSA status: Not relevant.

---

# SAFETY DATA SHEET

Product name:	DP-LUBRICANT BROWN	Page:	9/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0118	SDS-ID:	AU-EN/15.0

---

## SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 2, 8, 11.  
The (\*) indicates the changes made with respect to the previous version.

Approved by DHI.

Allan Vorup

Additional information: Classification according to Regulation (EC) No. 1272/2008:  
Calculation method.

Wording of R-phrases and  
H-statements:

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

---

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.  
[www.dhigroup.com](http://www.dhigroup.com).

---