

SAFETY DATA SHEET



Product name:	DP-LUBRICANT PURPLE	Page:	1/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name: DP-LUBRICANT PURPLE
Cat. No. 40700059, 40700060, 40700061

Container size: 1, 5, 10 l

Relevant identified uses of the substance or mixture and uses advised against

Application: For materialographic preparation

Details of the supplier of the safety data sheet

Supplier: Struers A/S
Pederstrupvej 84
DK-2750 Ballerup
Tel: +45 44 600 800

Responsible for material safety data sheet authoring: Responsible for material safety data sheet authoring: DHI
Any questions to the contents of this material safety data sheet should be sent to:
Lisbeth.Mygind@struers.dk

Emergency telephone number

Emergency telephone: Infotrac:
1-800-535-5053
Struers US:
1-440-871-0071

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	2/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

The product is classified:

67/548/EEC / 1999/45/EC: F;R11

GHS: Flam. Liq. 2;H225 - Eye Irrit. 2;H319 (*)

Label elements

(*)



Danger

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, eye and face protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local regulations.
	NFPA Rating: Health:1 Fire:3 Reactivity:0 Other:-

Other hazards

PBT/vPvB: Not relevant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

The product contains: organic solvents and pigments.

67/548/EEC:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
70-85	64-17-5	200-578-6	-	Ethanol	F;R11	
5-<10	67-63-0	200-661-7	01-2119457558-25-xxxx	Propan-2-ol	F;R11 Xi;R36 R67	
5-15	57-55-6	200-338-0	-	Propylene glycol	-	
<0.1	81457-64-9	279-766-5	-	Blue dye	-	
<0.1	130-22-3	204-981-8	-	Red dye (C. I. Acid Red 211)	-	

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	3/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

GHS:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
70-85	64-17-5	200-578-6	-	Ethanol	Flam. Liq. 2;H225 Eye Irrit. 2;H319	
5-<10	67-63-0	200-661-7	01-2119457558- 25-xxxx	Propan-2-ol	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
5-15	57-55-6	200-338-0	-	Propylene glycol	-	
<0.1	81457-64-9	279-766-5	-	Blue dye	-	
<0.1	130-22-3	204-981-8	-	Red dye (C. I. Acid Red 211)	-	

References: The full text for all R-phrases and hazard statements are displayed in section 16.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move into fresh air and keep at rest.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	4/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Special hazards arising from the substance or mixture

Specific hazards: The product is highly flammable, and explosive vapors/air mixtures may be formed even at normal room temperatures. Vapors may be ignited by a spark, a hot surface or an ember.

Advice for firefighters

Protective equipment for fire-fighters: Use air-supplied respirator during fire fighting.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not smoke or use open fire, or other sources of ignition. Avoid inhalation of vapors and contact with skin and eyes.

Environmental precautions

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Spill Cleanup Methods: Large quantities of concentrate should not be discharged into the drain but removed with absorbing material. Do not use sawdust or other combustible material.

Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Safe handling advice: Avoid inhalation of vapors and contact with skin and eyes. Observe good chemical hygiene practices. Take precautionary measures against static discharges.

Technical measures: Do not smoke or use open fire or other sources of ignition.

Technical precautions: Local exhaust is recommended.

Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids.

Storage conditions: Store in a cool and well-ventilated place. Avoid contact with oxidizing agents.

Specific end use(s)

Specific use(s): Not relevant.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	5/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

CAS-No.:	Chemical name:	As:	Exposure limits:	Type:	Notes:	References:
67-63-0	Isopropyl alcohol	-	400 ppm	980 mg/m ³	TWA	-
64-17-5	Ethyl alcohol	-	1000 ppm	1900 mg/m ³	TWA	-
64-17-5	Ethanol	-	1000 ppm		STEL	A3; 15min
67-63-0	2-Propanol	-	200 ppm		TWA	A4; BEI
		-	400 ppm		STEL	A4; BEI; 15min

Notes:
A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans.
A4: Not Classifiable as a Human Carcinogen.

Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

Personal protection: Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with gas filter, type A2.

Hand protection: Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection: Wear goggles/face shield. (*)

Skin protection: No special precautions.

Environmental Exposure: Not available.

Controls:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: purple liquid

Odor: odor of alcohol

pH: Not relevant.

Boiling point: Not available.

Flash point: 13°C

Explosion limits: 3,2-19 %

Relative density: 0,81

Solubility: Miscible with water.

Other information

Other data: Volatile Organic Compound (VOC): 720 g/l (calculated)

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	6/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Reactivity: None known.

Chemical stability

Stability: Stable under normal temperature conditions.

Possibility of hazardous reactions

Hazardous Reactions: None known.

Conditions to avoid

Conditions/materials to avoid: Direct sunlight. Heating. Oxidizing agents.

Incompatible materials

Incompatible materials: None known.

Hazardous decomposition products

Hazardous decomposition products: None in particular.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

In case of insufficient ventilation, extensive use may cause the damage described below.

Inhalation: Small quantities: Vapors may irritate throat and respiratory system and cause coughing.

Large quantities: Vapors may irritate throat and respiratory system and cause headache, dizziness and dullness.

Skin contact: Prolonged contact may cause redness, irritation and dry skin. Contains 2-propanol which may penetrate the skin.

Eye contact: Causes serious eye irritation. (*)

Ingestion: May irritate and cause malaise.

Specific effects: Frequent inhalation of even small concentrations may cause irritability, fatigue and memory failure and eventually permanent damage to the nervous system, including the brain.

Carcinogenicity:

National Toxicology Program (NTP): No.

I.A.R.C. Monographs: No.

OSHA: No.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	7/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecotoxicity: The product is not expected to be hazardous to the environment.

Persistence and degradability

Degradability: The product is 80% biodegradable.

Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

Mobility in soil

Mobility: No data available.

Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 16 09 08

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	8/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 14: TRANSPORT INFORMATION

UN number

UN-No: 1993

UN proper shipping name

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S (Ethanol, Isopropylalcohol Mixture)

Additional IMDG information:

EmS: F-E , S-E

MFAG: 1

Transport hazard class(es)

Class: 3

Packing group

PG: II

Environmental hazards

Marine pollutant: No.

Environmentally Hazardous substance: No.

Special precautions for user

Special precautions: None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: TSCA: Listed.

National regulation: Europe/USA:
This Material Safety Data Sheet has been prepared according to the EU-regulation.
Threshold Limit Values (2014), ACGIH, by the American Conference on Governmental Industrial Hygienists.
The Code of Federal Regulation, Title 29, part 1910. Occupational Safety and Health Standards, Air contaminants (OSHA), with amendments.

Chemical Safety Assessment

CSA status: Not relevant.

SAFETY DATA SHEET

Product name:	DP-LUBRICANT PURPLE	Page:	9/9
Revision Date:	2014-09-24	Print date:	2014-09-24
Document No.:	M0147	SDS-ID:	US-EN/10.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 2, 8, 11.

The (*) indicates the changes made with respect to the previous version.

Approved by DHI.



Additional information: Classification according to Regulation (EC) No. 1272/2008:
Calculation method.

Wording of H-statements:

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapors may cause drowsiness and dizziness.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.