

# BEBBINGTON INDUSTRIES MATERIAL SAFETY DATA SHEET – DRY SOLV

## **SECTION 1: PRODUCT IDENTIFICATION.**

PRODUCT NAME : DRY SOLV  
INTENDED USE: SOLVENT CLEANER  
TDG SHIPPING NAME: PETROLEUM DISTILLATES NOS  
TDG CLASSIFICATION: CLASS 3  
WHMIS CLASSIFICATION: CLASS B3 D2B  
MANUFACTURER: BEBBINGTON INDUSTRIES  
44 WRIGHT AVENUE  
DARTMOUTH, NOVA SCOTIA B3B 1G6  
TELEPHONE: 902 468-8180 FAX: 902 468-8559  
EMERGENCY TELEPHONE: 613-996-6666

## **SECTION 2: INGREDIENTS - ALL INGREDIENTS LISTED**

PETROLEUM DISTILLATES	LD 50 DERMAL RABBIT > 3160 MG/KG
CAS 64742-48-9	LD 50 ORAL RAT > 5000 MG/KG

MANUFACTURER RECOMMENDS A TWA 1200 MG/M3 OR 175 PPM BASED ON TOTAL HYDROCARBON

## **SECTION 3: PHYSICAL DATA.**

A CLEAR COLORLESS LIQUID LOW ODOR  
SG 0.762 @ 15.6 C  
BOILING POINT 182 – 204 C  
FREEZING POINT - 78 C  
VAPOUR PRESSURE 0.09 KPA @ 20 C  
VAPOUR DENSITY 5.6 @ 101 KPA  
% VOLATILES BY VOLUME 100  
SOLUBILITY IN WATER NEGLIGIBLE  
FLASH POINT > 54 C

## **SECTION 4: FIRE AND EXPLOSION HAZARD DATA**

COMBUSTIBLE

## **SECTION 5: HEALTH HAZARD DATA.**

**SWALLOWING** – LOW TOXICITY. SMALL AMOUNTS ASPIRATED INTO LUNGS DURING INGESTION OR FROM VOMITING MAY CAUSE MILD TO SEVERE PULMONARY INJURY OR POSSIBLY DEATH

**INHALATION** – MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION RESULTING IN DROWSINESS, DIZZINESS AND UNCONSCIOUSNESS.

**SKIN CONTACT** – IRRITANT AND MAY CAUSE DERMITITIS.

**EYE CONTACT** - IRRITANT.

## **SECTION 6: FIRST AID PROCEDURES**

**SWALLOWING** - DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

**INHALATION** – MOVE PERSON TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF BREATHING STOPS. SEEK MEDICAL ATTENTION.

**SKIN CONTACT** - REMOVE CONTAMINATED CLOTHING AND WASH SKIN THOROUGHLY WITH WATER. SEEK MEDICAL ASSISTANCE IF SKIN REMAINS IRRITATED.

**EYE CONTACT** - RINSE EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION IF EYE BECOMES IRRITATED.

## **SECTION 7: REACTIVITY DATA**

NO INCOMPATIBLE KNOWN

## **SECTION 8: SPILL OR LEAK PROCEDURES**

ELIMINATE ALL SOURCES OF IGNITION.

PREVENT ENTRY INTO SEWERS OR WATER WAYS. ABSORB WITH SAND OR EARTH

## **SECTION 9: SPECIAL PROTECTION INFORMATION.**

PROTECTIVE GLOVES –USE PROTECTIVE GLOVES SUCH AS VINYL OR NITRILE  
EYE PROTECTION - THE USE OF CHEMICAL RESISTANT GOGGLES OR GLASSES IS RECOMMENDED

RESPIRATORY PROTECTION – NOT NORMALLY REQUIRED

## **SECTION 10: SPECIAL PRECAUTIONS.**

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS AFTER USE.

## **SECTION 11: WHMIS CLASSIFICATION**

B3 FLAMMABLE, D2B TOXIC

## **SECTION 12: PREPARATION DATA.**

PREPARED BY - BEBBINGTON INDUSTRIES

DATE – FEBRUARY 2015

FOR FURTHER INFORMATION CONTACT BEBBINGTON INDUSTRIES 902-468-8180.

## **DISCLAIMER:**

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. BEBBINGTON INDUSTRIES SHALL NOT BE HELD LIABLE FOR ANY DAMAGE OF INJURY RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT. ALL PERSONS USING THIS PRODUCT SHOULD BE TRAINED ACCORDING TO WHMIS REQUIREMENTS.