

SAFETY DATA SHEET

1. Identification

Product identifier Hercules Dark Cutting Oil

Other means of identification

7336E **Product code**

Synonyms Part Numbers: 40110, 40115, 40120, 40125, 40140

Recommended use Thread Cutting Oil **Recommended restrictions** None Known

Manufacturer/Importer/Supplier/Distributor information

Company Name HCC Holdings, Inc. an Oatey Affiliate

4700 West 160th Street **Address**

Cleveland, OH 44135

Telephone 216-267-7100 E-mail info@oatey.com

Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887) **Transport Emergency**

Emergency First Aid 1-877-740-5015 **Contact person MSDS** Coordinator

2. Hazard(s) identification

Physical hazards Not Classified. Not Classified Health hazards **OSHA** defined hazards Not Classified.

Label elements

Hazard symbol None. Signal word None

Hazard statement This product does not require any hazard statements.

Precautionary statement

Prevention This product does not require any precautionary statements. Response This product does not require any precautionary statements.

Storage Not applicable. Disposal Not applicable.

Hazard(s) not otherwise

classified (HNOC)

Used Oil may contain harmful impurities. Contaminated surfaces will be extremely slippery.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	70-80

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical

attention if symptoms occur.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get Skin contact

medical attention if symptoms occur.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Check for and remove any contact lenses. Get medical attention if irritation occurs.

Ingestion Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical

Hercules Dark Cutting Oil SDS US SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015 Page 1 of 6

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed.

personnel. Get medical attention if symptoms occur. Ingestion may result in nausea, vomiting, and or diarrhea.

Immediate medical attention is not required.

General information

Note to physician, treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for

small fires only.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Do not use water in a jet. Hazardous combustion products may include: A complex mixture of airborne solid and liquid

particulates and gases, oxides of sulfur and phosphorous (smoke). Carbon monoxide.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this

material must be contained and prevented from being discharged to any waterway, sewer or

drain. None

Specific methods General fire hazards

None

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Methods and materials for containment and cleaning up Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

7. Handling and storage

Precautions for safe handling

Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials to prevent fires. Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Hercules Dark Cutting Oil SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015 Page 2 of 6

US. ACGIH Threshold Limit Values

Туре	Value
TLV or PEL	5 mg/m3
Туре	Value
	TLV or PEL

Biological limit values Data Not available.

Appropriate engineering

controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment

indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Other

Hand Chemical-resistant, impervious gloves complying with an approved standard should be worn at

> all times when handling chemical products if a risk assessment indicates this is necessary. Appropriate footwear and any additional skin protection measures should be selected based on

the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Respiratory protection Use a properly fitted, particulate filter respirator complying with an approved standard if a risk

assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

Thermal hazards None

General hygiene considerations

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the layatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance

Physical state Liquid Form Liquid Color Dark brown Odor Slight hydrocarbon **Odor threshold** Not available. Not applicable Melting point/freezing point No data available. Initial boiling point and boiling Not determined

range

> 350 °F (> 177°C) Flash point

Upper/lower flammability or explosive limits Flammability limit - lower (%) Not available Flammability limit - upper (%) Not available Explosive limit - lower (%) Not available Explosive limit - upper (%) Not available Vapor pressure Not applicable Vapor density Not applicable 0.915

Relative density Solubility(ies)

Solubility (water) Negligible

Partition coefficient

(n-octanol/water) No information available.

Auto-ignition temperature Not applicable

Hercules Dark Cutting Oil SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015 Page 3 of 6 **Decomposition temperature**

Viscosity, kinematic Other information

Not available

35 - 42.5 mm2/s @ 40 °C

VOC (Weight %) < 1% by Weight, < 10 g/L

10. Stability and reactivity

Reactivity The product does not pose any further reactivity hazards in addition to those listed in the

following sub-paragraph...

Chemical stability The product is stable.

Possibility of hazardous

reaction

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Extreme temperature and direct sunlight.

Incompatible materials Strong Oxidizing Agents.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should not be

products produced.

11. Toxicological information

Information on likely routes of exposure

Inhalation Mist from processing.

Skin contact Skin contact. Eye contact Eye contact.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics No specific data.

Information on likely routes of exposure

Acute Toxicity

Components **Species** Results Distillates (petroleum), hydrotreated Rat LD 50 Oral > 5000 mg/kg light naphthenic 64742-53-6 Rabbit LD 50 Dermal > 2000 mg/kg

Skin corrosion/irritation May cause skin irritation after prolonged exposure. Prolonged exposure or repeated exposure

without proper cleaning can clog pores of the skin.

Serious eve damage/eve

irritation

Expected to be slightly irritating.

Respiratory or skin sensitization

Respiratory sensitization Inhalation of vapors or mists may cause irritation to the respiratory system.

This product is not expected to cause skin irritation. Skin sensitization

Germ cell mutagenicity Not considered a mutagenic hazard

No component of this product is identified as a probable, possible, or confirmed carcinogen by Carcinogenicity

IARC, NTP, Monographs, or OSHA.

Reproductive toxicity No known significant effects or critical hazards.

Specific target organ toxicity

Not expected to be a hazard. Single exposure Not expected to be a hazard. Repeated exposure

Aspiration Hazard Contains Distillates (petroleum), hydrotreated – Which is a category 1 Aspiration Hazard. The

likely hood of aspirating the product in this form is very low due to the high viscosity.

Chronic effects Not Classified.

Further information Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

12. Ecological information

Ecotoxicity

Product/ingredient name	Results	Species	Exposure
Distillates (petroleum), hydrotreated light	LC 50 > 5000 mg/L	Oncorhynchus mykiss ()	96 Hours
Naphthenic 64742-53-6	EC50 > 1000 mg/L	Daphnia magna	48 Hours
Hercules Dark Cutting Oil			SDS US

SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015 Page 4 of 6

Persistence and degradability Not Available.

Bio accumulative potential Not Available.

Mobility in soil Liquid under most conditions. Floats on water. If it enters soil, it will adsorb to soil particles and

will not be mobile.

Other adverse effects No known significant effects of critical hazards.

13. Disposal considerations

Disposal instructions The generation of waste should be avoided or minimized wherever possible. Disposal of this

product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers.

Local disposal regulations Not Applicable Hazardous waste code Not Applicable

14. Transportation information

DOT Not Regulated

UN number

UN Proper Shipping Name Transportation Hazard

classes

Packing group

IATA Not Regulated

UN number

UN Proper Shipping Name Transportation Hazard

classes

Packing group

IMDG Not Regulated

UN number

UN Proper Shipping Name Transportation Hazard

classes

Packing group

Environmental hazards Marine polluntant

15. Regulatory information

International Inventories All the substances contained in this product are listed or exempted from listing in the

following inventories:

U.S.A. (TSCA)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard no **Chronic Health Hazard** no Fire Hazard no

Hercules Dark Cutting Oil SDS US Page 5 of 6

SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015

Sudden Release of Pressure Hazard no **Reactive Hazard** no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations California Proposition 65

This product does not contain any Proposition 65 chemicals.

16. Other information, including date of preparation or last revision

Issue Date 12-May-2015

Revision Date -

Version # 01

HMIS Rating Health: 1

Flammability: 1 Physical Hazards: 0

Disclaimer HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information

and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Hercules Dark Cutting Oil

SDS US
SDS #7336E Version #: 01 Revision date: Issue date: 12-May-2015

SDS US
Page 6 of 6