

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016  
Supercedes Version: 1.13

SDS Number 300000000130  
Print Date 16.12.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier : Halocarbon 23

Chemical formula : CHF<sub>3</sub>

Synonyms : Trifluoromethane (R23), Halocarbon-23, Fluoroform

Refer to Section 3 for REACH information

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : General Industrial

Restrictions on Use : No data available.

1.3. Details of the supplier of the safety data sheet : Air Products Ireland Ltd  
Unit 950 Western Industrial Estate  
Kileen Road  
Dublin 12  
Ireland

Email Address – Technical Information : GASTECH@airproducts.com

Telephone : 1-4659650

1.4. Emergency telephone number : (01) 463 4200 / +353 1 463 4200

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Gases under pressure - Liquefied gas. H280:Contains gas under pressure; may explode if heated.

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

## 2.2. Label elements

Hazard pictograms/symbols



Signal Word: Warning

Hazard Statements:

H280: Contains gas under pressure; may explode if heated.

Precautionary Statements:

Storage : P403: Store in a well-ventilated place.

## 2.3. Other hazards

Can cause rapid suffocation.  
Compressed liquefied gas.  
Avoid breathing gas.  
Direct contact with liquid can cause frostbite.  
Self contained breathing apparatus (SCBA) may be required.

## SECTION 3: Composition/information on ingredients

Substance/Mixture : Substance

| Components       | EINECS / ELINCS Number | CAS Number | Concentration (Volume) |
|------------------|------------------------|------------|------------------------|
| Trifluoromethane | 200-872-4              | 75-46-7    | 100 %                  |

| Components       | Classification (CLP)    | REACH Reg. #     |
|------------------|-------------------------|------------------|
| Trifluoromethane | Press. Gas (Liq.) ;H280 | 01-2119971823-29 |

If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, or the registration date has not yet come due.  
Concentration is nominal. For the exact product composition, please refer to technical specifications.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General advice : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

|              |                                                                                                                                                                                                                                                                                 |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|              | if breathing stopped.                                                                                                                                                                                                                                                           |
| Eye contact  | : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Keep eye wide open while rinsing. Seek medical advice.                                                                                                                   |
| Skin contact | : Wash frost-bitten areas with plenty of water. Do not remove clothing. Cover wound with sterile dressing.                                                                                                                                                                      |
| Ingestion    | : Ingestion is not considered a potential route of exposure.                                                                                                                                                                                                                    |
| Inhalation   | : Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen. |

## 4.2. Most important symptoms and effects, both acute and delayed

|          |                                                                                                                                                      |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms | : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness. |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------|

## 4.3. Indication of any immediate medical attention and special treatment needed

|           |                                                          |
|-----------|----------------------------------------------------------|
| Treatment | : If exposed or concerned: Get medical attention/advice. |
|-----------|----------------------------------------------------------|

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                              |                                              |
|------------------------------|----------------------------------------------|
| Suitable extinguishing media | : All known extinguishing media can be used. |
|------------------------------|----------------------------------------------|

|                                                                |                      |
|----------------------------------------------------------------|----------------------|
| Extinguishing media which must not be used for safety reasons. | : No data available. |
|----------------------------------------------------------------|----------------------|

### 5.2. Special hazards arising from the substance or mixture

|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | : Exposure to high temperatures may yield toxic by- products which may be corrosive in the presence of moisture. Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is nonflammable and does not support combustion. Move away from container and cool with water from a protected position. If possible, stop flow of product. Keep adjacent cylinders cool by spraying with large amounts of water until the fire burns itself out. |
|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 5.3. Advice for firefighters

|  |                                                                                                                                                                                                                                                                                                                                                                                                   |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | : Wear self contained breathing apparatus for fire fighting if necessary. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 6: Accidental release measures

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

- 6.1. Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ventilate the area. Monitor oxygen level.
- 6.2. Environmental precautions : Should not be released into the environment. Do not discharge into any place where its accumulation could be dangerous. Prevent further leakage or spillage. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- 6.3. Methods and material for containment and cleaning up : Ventilate the area.
- Additional advice : If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.
- 6.4. Reference to other sections : For more information refer to Sections 8 & 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or guard. Always use backflow protective device in piping. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Never attempt to increase

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

liquid withdrawal rate by pressurizing the container without first checking with the supplier. Never permit liquefied gas to become trapped in parts of the system as this may result in hydraulic rupture.

## 7.2. Conditions for safe storage, including any incompatibilities

Full containers should be stored so that oldest stock is used first. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Return empty containers in a timely manner.

### Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material.

## 7.3. Specific end use(s)

Refer to section 1 or the extended SDS if applicable.

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

If applicable, refer to the extended section of the SDS for further information on CSA.

### 8.2. Exposure controls

#### Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

#### Personal protective equipment

- |                          |                                                                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Respiratory protection   | : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere.<br>Air purifying respirators will not provide protection. Users of breathing apparatus must be trained. |
| Hand protection          | : Wear working gloves when handling gas containers.<br>Standard EN 388 - Protective gloves against mechanical risk.                                                                                                                       |
| Eye/face Protection      | : Safety glasses recommended when handling cylinders.<br>Standard EN 166 - Personal eye-protection.                                                                                                                                       |
| Skin and body protection | : Safety shoes are recommended when handling cylinders.<br>Standard EN ISO 20345 - Personal protective equipment - Safety footwear.                                                                                                       |

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

Special instructions for protection and hygiene : Ensure adequate ventilation, especially in confined areas.

Environmental Exposure Controls : If applicable, refer to the extended section of the SDS for further information on CSA.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(a/b) Physical state/Colour : Liquefied gas. Colorless gas

(c) Odour : Ether-like. Poor warning properties at low concentrations.

(c) Odour : Mixture contains one or more component(s) which have the following odor: Ether-like.

(d) Density : 0.0029 g/cm<sup>3</sup> (0.181 lb/ft<sup>3</sup>) at 21 °C ( 70 °F)  
Note: (as vapor)

(e) Relative Density : 1.4 (water = 1)

(f) Melting point / freezing point : -247 °F (-155.2 °C)

(g) Boiling point/range : -116 °F (-82.2 °C)

(h) Vapor pressure : 603.34 psia (41.60 bara) at 68 °F (20 °C)

(i) Water solubility : 1.08 g/l

(j) Partition coefficient (n-octanol/water) : Not applicable.

(k) pH : Not applicable.

(l) Viscosity : Not applicable.

(m) Particle characteristics : No data available.

(n) Lower and upper explosion / flammability limits : No data available.

(o) Flash point : Not applicable.

(p) Autoignition temperature : No data available.

(q) Decomposition temperature : No data available.

9.2. Other information  
Explosive properties : No data available.

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

|                           |                                                                          |
|---------------------------|--------------------------------------------------------------------------|
| Oxidizing properties      | : No data available.                                                     |
| Molecular Weight          | : 70.01 g/mol                                                            |
| Odor threshold            | : No data available.                                                     |
| Evaporation rate          | : Not applicable.                                                        |
| Flammability (solid, gas) | : Refer to product classification in Section 2                           |
| Specific Volume           | : 0.3421 m <sup>3</sup> /kg (5.48 ft <sup>3</sup> /lb) at 21 °C ( 70 °F) |
| Relative vapor density    | : 2.417 (air = 1) Heavier than air.                                      |

## SECTION 10: Stability and reactivity

|                                          |                                                                                                  |
|------------------------------------------|--------------------------------------------------------------------------------------------------|
| 10.1. Reactivity                         | : Refer to possibility of hazardous reactions and/or incompatible materials sections.            |
| 10.2. Chemical stability                 | : Stable under normal conditions.                                                                |
| 10.3. Possibility of hazardous reactions | : Thermal decomposition yields toxic products that can be corrosive in the presence of moisture. |
| 10.4. Conditions to avoid                | : Alkali and alkaline earth metals - powdered aluminum, zinc, etc.                               |
| 10.5. Incompatible materials             | : No data available.                                                                             |
| 10.6. Hazardous decomposition products   | : No data available.                                                                             |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Likely routes of exposure

|                    |                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on Eye     | : Contact with liquid may cause cold burns/frostbite.                                                                                                                                                                                                                                                                                                                                             |
| Effects on Skin    | : Contact with liquid may cause cold burns/frostbite.                                                                                                                                                                                                                                                                                                                                             |
| Inhalation Effects | : Inhalation of high concentrations may also cause mild central nervous system depression and heartbeat irregularities. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves. |
| Ingestion Effects  | : Ingestion is not considered a potential route of exposure.                                                                                                                                                                                                                                                                                                                                      |

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

## Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

Acute Inhalation Toxicity : No data is available on the product itself.

Inhalation - Components  
Trifluoromethane (R23) LC50 (4 h) : > 663000 ppm Species : Rat.

Acute Dermal Toxicity : No data is available on the product itself.

Skin corrosion/irritation : No data available.

Serious eye damage/eye irritation : No data available.

Sensitization. : No data available.

## Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : This material has been evaluated in a battery of tests and has not caused mutations or chromosomal damage.

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : Animals exhibited anesthetic effects and weight loss from acute high level exposure to Trifluoromethane. Dogs that were exposed to 80% Trifluoromethane for five to ten minutes and then challenged with epinephrine did not exhibit cardiac sensitization. Baboons that were exposed to 70% Trifluoromethane before or after epinephrine challenge did not exhibit cardiac sensitization; they did exhibit a dose-related decrease in heart and respiratory rates during exposure. Cats exposed to 70% Trifluoromethane exhibited cardiac sensitization and moderate changes in cerebral electrical activity. Rats that were exposed six hours per day, for ninety days to 1% Trifluoromethane exhibited no toxic effects. The maternal and developmental "No Observed Adverse Effect Level" (NOAEL) is 50% Trifluoromethane. No developmental or reproductive effects were observed.

Aspiration hazard : No data available.



# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

## SECTION 12: Ecological information

### 12.1. Toxicity

Aquatic toxicity : No data is available on the product itself.

Toxicity to fish - Components  
Trifluoromethane (R23)

LC50 (96 h) : 633.26 mg/l

Species : Fathead  
minnow (Pimephales  
promelas).

Toxicity to daphnia - Components  
Trifluoromethane (R23)

EC50 (48 h) : 323.05 mg/l

Species : Daphnia  
magna.

Toxicity to algae - Components  
Trifluoromethane (R23)

EC50 (96 h) : 154.54 mg/l

Species : Algae.

Toxicity to other organisms : No data is available on the product itself.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

Refer to Section 9 "Partition Coefficient (n-octanol/water)".

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

If applicable, refer to the extended section of the SDS for further information on CSA.

### 12.6. Other adverse effects

Contains fluorinated greenhouse gases covered by Kyoto Protocol. For quantities see concentrations or cylinder contents. Not covered by the 'Montreal Protocol'.

Effect on the ozone layer

Ozone Depleting Potential : No data available.

Global Warming Potential : No data available.

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

## SECTION 13: Disposal considerations

13.1. Waste treatment methods : Contact supplier if guidance is required. Refer to the EIGA code of practice Doc. 30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods. List of hazardous waste codes: 14 06 01: Chlorofluorocarbons, HCFC, HFC.

Contaminated packaging : Return cylinder to supplier.

## SECTION 14: Transport information

### ADR

UN/ID No. : UN1984  
Proper shipping name : TRIFLUOROMETHANE  
Class or Division : 2  
Tunnel Code : (C/E)  
Label(s) : 2.2  
ADR/RID Hazard ID no. : 20  
Marine Pollutant : No

### IATA

UN/ID No. : UN1984  
Proper shipping name : Trifluoromethane  
Class or Division : 2.2  
Label(s) : 2.2  
Marine Pollutant : No

### IMDG

UN/ID No. : UN1984  
Proper shipping name : TRIFLUOROMETHANE  
Class or Division : 2.2  
Label(s) : 2.2  
Marine Pollutant : No  
Segregation Group: : None

### RID

UN/ID No. : UN1984  
Proper shipping name : TRIFLUOROMETHANE  
Class or Division : 2  
Label(s) : 2.2  
Marine Pollutant : No

### Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| Country     | Regulatory list | Notification           |
|-------------|-----------------|------------------------|
| USA         | TSCA            | Included on Inventory. |
| EU          | EINECS          | Included on Inventory. |
| Canada      | DSL             | Included on Inventory. |
| Australia   | AICS            | Included on Inventory. |
| Japan       | ENCS            | Included on Inventory. |
| South Korea | ECL             | Included on Inventory. |
| China       | SEPA            | Included on Inventory. |
| Philippines | PICCS           | Included on Inventory. |

#### Other Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Regulation (EC) No 1272/2008 the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

### 15.2. Chemical safety assessment

If this product does not contain exposure scenarios, the components in this product are either exempt from REACH, do not meet the minimum volume threshold for a CSA, or the CSA has not yet been completed.

## SECTION 16: Other information

Ensure all national/local regulations are observed.

#### Hazard Statements:

H280 Contains gas under pressure; may explode if heated.

# SAFETY DATA SHEET

Version 1.14  
Revision Date 03.08.2016

SDS Number 300000000130  
Print Date 16.12.2017

## Indication of Method:

Gases under pressure Liquefied gas. Contains gas under pressure; may explode if heated. Calculation method

## Abbreviations and acronyms:

ATE - Acute Toxicity Estimate  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
EINECS - European Inventory of Existing Commercial Chemical Substances  
ELINCS - European List of Notified Chemical Substances  
CAS# - Chemical Abstract Service number  
PPE - Personal Protection Equipment  
Kow - octanol-water partition coefficient  
DNEL - Derived No Effect Level  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)  
NOEC - No Observed Effect Concentration  
PNEC - Predicted No Effect Concentration  
RMM - Risk Management Measure  
OEL - Occupational Exposure Limit  
PBT - Persistent, Bioaccumulative and Toxic  
vPvB - Very Persistent and Very Bioaccumulative  
STOT - Specific Target Organ Toxicity  
CSA - Chemical Safety Assessment  
EN - European Standard  
UN - United Nations  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
WGK - Water Hazard Class

## Key literature references and sources for data:

ECHA - Guidance on the compilation of safety data sheets  
ECHA - Guidance on the application of the CLP Criteria  
ARIEL database

Prepared by : Air Products and Chemicals, Inc. Global EH&S Product Safety Department

For additional information, please visit our Product Stewardship web site at  
<http://www.airproducts.com/productstewardship/>

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws. COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

# SAFETY DATA SHEET

Version 1.14

Revision Date 03.08.2016

SDS Number 300000000130

Print Date 16.12.2017

---

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

---