

---

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015  
Supersedes Version: 2.0

SDS Number 300000003722  
Print Date 16.12.2017

---

## SECTION 1: Identification of the substance/mixture and the company/undertaking

1.1. Product identifier : Halocarbon 410A

Refer to Section 3 for REACH information

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : General Industrial

Restrictions on Use : No data available.

1.3 Details of the supplier of the safety data sheet : Air Products Plc  
2 Millennium Gate  
Westmere Drive  
Crewe  
Cheshire

Email Address – Technical Information : prodinfo@airproducts.com

Telephone : +44(0)3457 020202

1.4. Emergency telephone number : +44(0)8085 020202

---

## SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Gases under pressure - Liquefied gas. H280:Contains gas under pressure; may explode if heated.

2.2. Label elements

Hazard pictograms/symbols



# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

Signal Word: Warning

Hazard Statements:

H280:Contains gas under pressure; may explode if heated.

Precautionary Statements:

Storage : P403:Store in a well-ventilated place.

## 2.3 Other Hazards

Can cause rapid suffocation.  
Compressed liquefied gas.  
Avoid breathing gas.  
Direct contact with liquid can cause frostbite.  
Self contained breathing apparatus (SCBA) may be required.

## SECTION 3: Composition/information on ingredients

Substance/Mixture : Mixture

Components	EINECS / ELINCS Number	CAS Number	Concentration (Weight)
Pentafluoroethane	206-557-8	354-33-6	50 %
Difluoromethane	200-839-4	75-10-5	50 %

Components	Classification (CLP)	REACH Reg. #
Pentafluoroethane	Press. Gas (Comp.) ;H280	01-2119485636-2 5
Difluoromethane	Press. Gas (Liq.) ;H280 Flam. gas 1 ;H220	01-2119471312-4 7

If REACH registration numbers do not appear the substance is either exempt from registration, does not meet the minimum volume threshold for registration, or the registration date has not yet come due.  
Refer to section 16 for full text of each relevant R-phrase and H-phrases.

Concentration is nominal. For the exact product composition, please refer to Air Products technical specifications.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

- if breathing stopped.
- Eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Keep eye wide open while rinsing. Seek medical advice.
- Skin contact : Wash frost-bitten areas with plenty of water. Do not remove clothing. Cover wound with sterile dressing.
- Ingestion : Ingestion is not considered a potential route of exposure.
- Inhalation : Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen.

## 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms:  
Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

---

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : All known extinguishing media can be used.

Extinguishing media which must not be used for safety reasons. : No data available.

### 5.2 Special hazards arising from the substance or mixture

: Exposure to high temperatures may yield toxic by-products which may be corrosive in the presence of moisture. Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is nonflammable and does not support combustion. Move away from container and cool with water from a protected position. If possible, stop flow of product. Keep adjacent cylinders cool by spraying with large amounts of water until the fire burns itself out.

### 5.3 Advice for fire-fighters

: Wear self contained breathing apparatus for fire fighting if necessary. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

---

## SECTION 6: Accidental release measures

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

- 6.1 Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ventilate the area. Monitor oxygen level.
- 6.2 Environmental precautions : Should not be released into the environment. Do not discharge into any place where its accumulation could be dangerous. Prevent further leakage or spillage. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- 6.3 Methods and material for containment and cleaning up : Ventilate the area.
- Additional advice : If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.
- 6.4 Reference to Other Sections : For more information refer to Sections 8 & 13

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or guard. Always use backflow protective device in piping. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Never attempt to increase liquid withdrawal rate by pressurizing the container without first checking with the supplier. Never permit liquefied

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

gas to become trapped in parts of the system as this may result in hydraulic rupture.

## 7.2 Conditions for safe storage, including any incompatibilities

Full containers should be stored so that oldest stock is used first. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Return empty containers in a timely manner.

### Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material.

## 7.3 Specific end use(s)

Refer to section 1 or the extended SDS if applicable

---

## SECTION 8: Exposure controls / personal protection

### 8.1 Control parameters

If applicable, refer to the extended section of the SDS for further information on CSA.

### 8.2 Exposure controls

#### Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

#### Personal protective equipment

- |                          |   |
|--------------------------|---|
| Respiratory protection   | : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere.<br>Air purifying respirators will not provide protection. Users of breathing apparatus must be trained. |
| Hand protection          | : Wear working gloves when handling gas containers.<br>Standard EN 388 - Protective gloves against mechanical risk.   |
| Eye/face Protection      | : Safety glasses recommended when handling cylinders.<br>Standard EN 166 - Personal eye-protection.   |
| Skin and body protection | : Safety shoes are recommended when handling cylinders.<br>Standard EN ISO 20345 - Personal protective equipment - Safety footwear.   |

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

Special instructions for protection and hygiene : Ensure adequate ventilation, especially in confined areas.

Environmental Exposure Controls : If applicable, refer to the extended section of the SDS for further information on CSA.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

(a/b) Physical state/Colour : Liquefied gas. Colorless gas

(c) Odour : Ether-like.

(e) Relative Density : Heavier than air.

(f) Melting point / freezing point : No data available.

(g) Boiling point/range : -897 °F (-51,6 °C)

(h) Vapor pressure : 208.85 psia (14.40 bara)

(i) Water solubility : No reliable data available.

(j) Partition coefficient (n-octanol/water) : Not applicable.

(k) pH : Not applicable.

(l) Viscosity : Not applicable.

(m) Particle characteristics : No data available.

(n) Lower and upper explosion / flammability limits : No data available.

(o) Flash point : Not applicable.

(p) Autoignition temperature : No data available.

(q) Decomposition temperature : No data available.

### 9.2. Other information

Explosive properties : No data available.

Oxidizing properties : No data available.

Odor threshold : No data available.

Evaporation rate : Not applicable.

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

Flammability (solid, gas) : Refer to product classification in Section 2  
Relative vapor density : 2.5 (air = 1)

---

## SECTION 10: Stability and reactivity

10.1 Reactivity : Refer to possibility of hazardous reactions and/or incompatible materials sections.  
10.2. Chemical stability : Stable under normal conditions.  
10.3. Possibility of hazardous reactions : No data available.  
10.4. Conditions to avoid : No data available.  
10.5. Incompatible materials : No data available.  
10.6 Hazardous decomposition products : No data available.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Likely routes of exposure

Effects on Eye : Contact with liquid may cause cold burns/frostbite.  
Effects on Skin : Contact with liquid may cause cold burns/frostbite.  
Inhalation Effects : Inhalation of high concentrations may also cause mild central nervous system depression and heartbeat irregularities. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.  
Ingestion Effects : Ingestion is not considered a potential route of exposure.  
Symptoms : Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

#### Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

---

Acute Inhalation Toxicity : No data is available on the product itself.  
Acute Dermal Toxicity : No data is available on the product itself.  
Skin corrosion/irritation : No data available.  
Serious eye damage/eye irritation : No data available.  
Sensitization. : No data available.

## Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.  
Reproductive toxicity : No data is available on the product itself.  
Germ cell mutagenicity : No data is available on the product itself.  
Specific target organ systemic toxicity (single exposure) : No data available.  
Specific target organ systemic toxicity (repeated exposure) : Difluoromethane was not teratogenic in rats or rabbits. Minimal fetal and maternal toxicity in rats and maternal toxicity in rabbits were seen at a concentration of 5% Difluoromethane.  
Aspiration hazard : No data available.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Aquatic toxicity : No data is available on the product itself.  
Toxicity to other organisms : No data is available on the product itself.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data is available on the product itself.

### 12.4 Mobility in soil

No data available.

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

## 12.5 Results of PBT and vPvB assessment

If applicable, refer to the extended section of the SDS for further information on CSA.

## 12.6 Other adverse effects

Contains fluorinated greenhouse gases covered by Kyoto Protocol. For quantities see concentrations or cylinder contents.

Effect on the ozone layer

Ozone Depleting Potential : No data available.

Global Warming Potential : No data available.

---

## SECTION 13: Disposal considerations

13.1 Waste treatment methods : Contact supplier if guidance is required. Refer to the EIGA code of practice Doc. 30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods. List of hazardous waste codes: 14 06 01: Chlorofluorocarbons, HCFC, HFC.

Contaminated packaging : Return cylinder to supplier.

---

## SECTION 14: Transport information

### ADR

UN/ID No. : UN3163  
Proper shipping name : LIQUEFIED GAS, N.O.S., (Difluoromethane (R32), Pentafluoroethane (R125))  
Class or Division : 2  
Tunnel Code : (C/E)  
Label(s) : 2.2  
ADR/RID Hazard ID no. : 20  
Marine Pollutant : No

### IATA

UN/ID No. : UN3163  
Proper shipping name : Liquefied gas, n.o.s., (Difluoromethane (R32), Pentafluoroethane (R125))  
Class or Division : 2.2  
Label(s) : 2.2  
Marine Pollutant : No

### IMDG

UN/ID No. : UN3163  
Proper shipping name : LIQUEFIED GAS, N.O.S., (Difluoromethane (R32), Pentafluoroethane (R125))

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

Class or Division : 2.2  
Label(s) : 2.2  
Marine Pollutant : No

## RID

UN/ID No. : UN3163  
Proper shipping name : LIQUEFIED GAS, N.O.S., (Difluoromethane (R32), Pentafluoroethane (R125))  
Class or Division : 2  
Label(s) : 2.2  
Marine Pollutant : No

## Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Compliance with applicable regulations. Before transporting product containers ensure that they are firmly secured and: Cylinder valve is closed and not leaking. Valve outlet cap nut or plug (where provided) is correctly fitted. Valve protection device (where provided) is correctly fitted. Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

#### Other Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

---

Regulation (EC) No 1272/2008 the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

Health and Safety at Work etc. Act 1974

Management of Health and Safety at Work Regulations (Northern Ireland) 2000 c.388, and as amended

The Health and Safety at Work etc. Act 1974 (Application to Environmentally Hazardous Substances) Regulations 2002 (England and Wales and Scotland) 11 March 2002 c.282, and as amended

Health and Safety at Work Order (Application to Environmentally Hazardous Substances) Regulations (Northern Ireland) 2003 (Northern Ireland) 14 March 2003 c52, and as amended

The Control of Major Accident Hazards Regulations 2015 c483

The Control of Major Accident Hazards Regulations (Northern Ireland) 2015 c325

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2011 c1885, and as amended

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations with amendments (Northern Ireland) 2011 c365

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 c.407

The Water Environment Regulations (Northern Ireland) 2017 c.81

Pollution Prevention and Control Act 1999 c.24

The Fluorinated Greenhouse Gases Regulations 2015 c.310

The Fluorinated Greenhouse Gases Regulations (Northern Ireland) 2015 c.425

The Acetylene Safety (England and Wales and Scotland) Regulations 2014 c.1639

The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 c.917

The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

(Northern Ireland) 1975 c.256

Dangerous Substances and Explosive Atmospheres Regulations (Northern Ireland) 2003 c.152

The Dangerous Substances and Explosive Atmospheres Regulations 2002 c.2776

Pollution Prevention and Control Act 1999

The Environmental Permitting (England and Wales) Regulations 2016

Ozone Depleting Substances Regulations 2015

## 15.2 Chemical safety assessment

If this product does not contain exposure scenarios, the components in this product are either exempt from REACH, do not meet the minimum volume threshold for a CSA, or the CSA has not yet been completed.

---

## SECTION 16: Other information

Ensure all national/local regulations are observed.

Hazard Statements:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Indication of Method:

Gases under pressure Liquefied gas. Contains gas under pressure; may explode if heated. Calculation method

Abbreviations and acronyms:

ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

ELINCS - European List of Notified Chemical Substances

CAS# - Chemical Abstract Service number

PPE - Personal Protection Equipment

Kow - octanol-water partition coefficient

DNEL - Derived No Effect Level

LC50 - Lethal Concentration to 50 % of a test population

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)

NOEC - No Observed Effect Concentration

PNEC - Predicted No Effect Concentration

RMM - Risk Management Measure

OEL - Occupational Exposure Limit

PBT - Persistent, Bioaccumulative and Toxic

vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

Version 2.1  
Revision Date 04.06.2015

SDS Number 300000003722  
Print Date 16.12.2017

---

STOT - Specific Target Organ Toxicity  
CSA - Chemical Safety Assessment  
EN - European Standard  
UN - United Nations  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
WGK - Water Hazard Class

Key literature references and sources for data:  
ECHA - Guidance on the compilation of safety data sheets  
ECHA - Guidance on the application of the CLP Criteria  
ARIEL database

Prepared by : Air Products and Chemicals, Inc. Global EH&S Product Safety Department

For additional information, please visit our Product Stewardship web site at  
<http://www.airproducts.com/productstewardship/>

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws. Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

---