### MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

**Material name** Dynaflow® Flux

03 Version #

09-June-2011 Issue date 12-Sept-2014 **Revision date** Supersedes date 23-July-2014 CAS# Mixture

0134 **MSDS Number** 

Metal brazing operations. Product use

Manufacturer information

Manufacturer/Supplier Harris Products Group 4501 Quality Place Mason, Ohio 45040 US

custservmason@jwharris.com

Telephone number 513-754-2000

**Emergency Telephone** 

1-888-609-1762 (US, Canada, Mexico only)

**Numbers** 

Please quote 333988

#### 2. Hazards Identification

Physical state Solid.

White paste. **Appearance** CAUTION **Emergency overview** 

> May cause eye burns. Prolonged or repeated contact with the product may irritate the skin. Causes digestive tract burns. Dust is irritating to the eyes and respiratory tract. Fatal if swallowed. Harmful by inhalation and in contact with skin. May cause mild central nervous system effects. Possible adverse reproductive and developmental effects.

**OSHA** regulatory status

Potential health effects

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Routes of exposure

Inhalation. Ingestion. Skin contact. Eye contact.

May cause eye burns. Risk of serious damage to eyes. **Eyes** 

Skin Prolonged or repeated contact with the product may irritate the skin. Harmful if absorbed through

> the skin. Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through

systemic fluoride poisoning.

Inhalation Harmful by inhalation. Dust irritating to respiratory tract. May cause mild central nervous system

effects. Prolonged inhalation may be harmful.

Harmful if swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, Ingestion

esophagus and possibly the digestive tract.

**Target organs** Skin. Bone. Kidneys.

**Chronic effects** Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Sterility.

> Prolonged overexposure to fluorides may increase fluoride content of bones and teeth, and may result in fluorosis, and brittleness of bones. Prolonged or repeated contact may dry skin and cause dermatitis. Edema. Kidney injury may occur. Refer to Section 11 Toxicological Information for

more details.

Contact with this material may cause burns to the eyes. Symptoms include itching, burning, Signs and symptoms

redness, and tearing of eyes. Prolonged or repeated contact with the product may cause irritation of skin. Edema. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting.

Dynaflow® Flux **CPH MSDS NA** 

902336 Version #: 03  The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

# 3. Composition / Information on Ingredients

Components	CAS#	Percent	
Potassium difluorodihydroxyborate	85392-66-1	> 40	
Potassium fluoride	7789-23-3	20 - 30	
Methanol	67-56-1	1 - 3	

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First Aid Measures

First aid procedures

Immediately rinse eyes with water. Remove any contact lenses, and continue flushing eyes with Eye contact

running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of

the eye and lids with water. Get immediate medical attention.

Skin contact Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. A 2.5

pct calcium gluconate gel applied topically after skin has been thoroughly washed will help reduce

severity of symptoms. Get medical attention if irritation develops and persists.

Inhalation Remove person from contaminated area to fresh air. Apply artificial respiration if needed. Call a

physician if symptoms develop or persist.

Do NOT induce vomiting. Immediately rinse mouth and drink a cupful of water. Never give anything Ingestion

by mouth to an unconscious person. Get medical attention immediately.

Show this safety data sheet to the doctor in attendance. General advice

# 5. Fire Fighting Measures

Flammable properties

The product is not flammable.

**Extinguishing media** 

Suitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder

or carbon dioxide.

Protection of firefighters

Protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

#### 6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this MSDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment

Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Should not be released into the environment. Prevent product from entering drains. Do not allow material to contaminate ground water system.

Large Spills: Sweep up and place into a proper container for disposal. Avoid the generation of dusts during clean-up.

Small Spills: Wipe up spilled material and place in a suitable container for disposal.

Never return spills in original containers for re-use. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. For waste disposal, see Section 13 of the MSDS.

Other information

Clean up in accordance with all applicable regulations.

Dynaflow® Flux CPH MSDS NA

### 7. Handling and Storage

**Handling** Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8). Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to

the environment.

Storage Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed

container away from incompatible materials. Do not store in container made of glass or silicate-based material. Keep away from food, drink and animal feedingstuffs. Keep out of the

reach of children.

# 8. Exposure Controls / Personal Protection

#### Occupational exposure limits

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Fluorides (CAS 16984-48-8)	PEL	2.5 mg/m3	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Туре	Value	Form	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	Dust.	

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	
Methanol (CAS 67-56-1)	STEL	328 mg/m3	
		250 ppm	
	TWA	262 mg/m3	
		200 ppm	

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

Dynaflow® Flux CPH MSDS NA

#### Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	
Methanol (CAS 67-56-1)	STEL	328 mg/m3	
		250 ppm	
	TWA	262 mg/m3	
		200 ppm	
Mexico. Occupational Exposure Li	imit Values		

Components	Туре	Value	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	
Methanol (CAS 67-56-1)	STEL	310 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	

#### **Biological limit values**

# **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time	
Fluorides (CAS 16984-	48-8)3 mg/l	Fluoride	Urine	*	
	2 mg/l	Fluoride	Urine	*	
Methanol (CAS 67-56-	1) 15 mg/l	Methanol	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

**Engineering controls** 

Methanol (CAS 67-56-1) Can be absorbed through the skin. Canada - British Columbia OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. Canada - Manitoba OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. Canada - Ontario OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. Canada - Quebec OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. Canada - Saskatchewan OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. Mexico OELs: Skin designation Can be absorbed through the skin. Methanol (CAS 67-56-1) US - California OELs: Skin designation Methanol (CAS 67-56-1) Can be absorbed through the skin. **US - Tennesse OELs: Skin designation** 

Methanol (CAS 67-56-1)

**US ACGIH Threshold Limit Values: Skin designation** 

Methanol (CAS 67-56-1) **US. NIOSH: Pocket Guide to Chemical Hazards** 

Methanol (CAS 67-56-1)

US. OSHA Table Z-1-A (29 CFR 1910.1000)

Methanol (CAS 67-56-1)

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Shower, hand and eye washing facilities near the workplace are recommended.

4/9

Can be absorbed through the skin.

Dynaflow® Flux CPH MSDS NA Personal protective equipment

**Eye / face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Chemical resistant clothing is recommended.

**Respiratory protection**Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the

TLV. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR

1910.134; or in Canada with CSA Standard Z94.4.

**Hand protection** Wear protective gloves (i.e. latex, nitrile, neoprene).

**General hygiene**Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

# 9. Physical & Chemical Properties

Appearance White paste.

Physical state Solid. Form Paste. White. Color Odor Odorless. **Odor threshold** Not available. pН Not available. Not available. Vapor pressure Not available. Vapor density **Boiling point** Not available. Not available. Melting point/Freezing point Solubility (water) Moderate. 1.5 - 1.7 Specific gravity Not available. Flash point

Flammability limits in air,

upper, % by volume

Flammability limits in air,

lower, % by volume

n air, Not available.

Auto-ignition temperature Not available.

# 10. Chemical Stability & Reactivity Information

**Chemical stability** Material is stable under normal conditions. **Conditions to avoid** Contact with incompatible materials.

Not available.

Incompatible materials Strong oxidizing agents. Strong acids. Halogenated compounds. Silicate-based materials.

Hazardous decomposition

products

Hydrogen fluoride, fluorine-, boron- and potassium-containing compounds.

### 11. Toxicological Information

# Toxicological data

Components Species Test Results

Potassium difluorodihydroxyborate (CAS 85392-66-1)

Acute

Dermal

LD50 No data available

Oral

LD50 Rat 744 mg/kg

Dynaflow® Flux CPH MSDS NA

902336 Version #: 03 Revision date: 12-Sept-2014 Issue date: 09-June-2011

Components Species Test Results

Methanol (CAS 67-56-1)

Acute

Dermal

LD50 Rabbit 15800 mg/kg

Inhalation

LC50 Rat 64000 mg/l, 4 Hours

Oral

LD50 Rat 5628 mg/kg

Potassium fluoride (CAS 7789-23-3)

**Acute** Oral

LD50 Rat 245 mg/kg

Sensitization Not classified.

Acute effects May cause eye burns. Prolonged or repeated contact with the product may irritate the skin Dust

irritates the respiratory system, and may cause coughing and difficulties in breathing. Fatal if swallowed. Harmful if inhaled or absorbed through skin. May cause mild central nervous system

effects.

**Local effects** May cause eye burns. Prolonged or repeated contact with the product may irritate the skin.

Causes respiratory tract irritation.

**Chronic effects** Prolonged exposure may cause chronic effects. May cause damage to the kidneys. Repeated

exposure to fluorides may cause excessive calcification of the bone and calcification of ligaments of the ribs, pelvis and spinal column. Exposure to extremely high levels of fluorides can cause abdominal pain, diarrhea, muscular weakness, and convulsions. In extreme cases it can cause

loss of consciousness and death. Methanol:

Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage, and perhaps death after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little

as 30 mls.

**Subchronic effects** Kidney injury may occur.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**ACGIH Carcinogens** 

Potassium fluoride (CAS 7789-23-3) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Potassium fluoride (CAS 7789-23-3)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Epidemiology** No epidemiological data is available for this product.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Reproductive effects** Possible reproductive hazard.

**Teratogenicity** May cause birth defects. Avoid exposure to women during early pregnancy.

**Symptoms and target organs** May cause eye burns. Prolonged or repeated contact with the product may irritate the skin.

Symptoms include itching, burning, redness, and tearing of eyes. Itching, redness, burning of skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

6/9

Target organs: Skin. Bones. Kidney.

**Further information** Symptoms may be delayed.

Dynaflow® Flux CPH MSDS NA

### 12. Ecological Information

**Ecotoxicological data** 

Components Species Test Results

Potassium difluorodihydroxyborate (CAS85392-66-1)

Aquatic

Fish LC50 Brachydinio rerio 750 mg/l, 96 hours

Methanol (CAS 67-56-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Large amounts of the product may affect the acidity (pH-factor) in water with possible risk of

harmful effects to aquatic organisms.

**Environmental effects**An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Aquatic toxicity Not classified.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulation / accumulation

**Bioaccumulative potential** 

Octanol/water partition coefficient log Kow

Methanol (CAS 67-56-1) -0.77

Mobility in environmental

media

The product is partly soluble in water. May spread in the aquatic environment.

#### 13. Disposal Considerations

**Disposal instructions**Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all

applicable regulations.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

#### 14. Transport Information

DOT Product not regulated as Dangerous Good

IATA Product not regulated as Dangerous Good

IMDG Product not regulated as Dangerous Good

TDG Product not regulated as Dangerous Good

### 15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Methanol (CAS 67-56-1) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methanol (CAS 67-56-1) Listed.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Methanol: 5000

Dynaflow® Flux CPH MSDS NA

902336 Version #: 03 Revision date: 12-Sept-2014 Issue date: 09-June-2011

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed

SARA 311/312 Hazardous

chemical

Yes

**Drug Enforcement** Administration (DEA) (21 CFR

1308.11-15)

Not controlled

Inventory name

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS Canadian regulations

contains all the information required by the CPR.

WHMIS status Controlled WHMIS classification D2B - TOXIC

#### WHMIS labeling



#### Inventory status

**Philippines** 

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes

On inventory (yes/no)\*

Yes

No

8/9

(PICCS) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

WARNING: This product contains a chemical known to the State of California to cause cancer and State regulations

Philippine Inventory of Chemicals and Chemical Substances

birth defects or other reproductive harm.

#### US - California Hazardous Substances (Director's): Listed substance

Methanol (CAS 67-56-1) Listed. Potassium fluoride (CAS 7789-23-3) Listed.

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Methanol (CAS 67-56-1)

# US - California Proposition 65 - CRT: Listed date/Developmental toxin

Listed: March 16, 2012 Developmental toxin. Methanol (CAS 67-56-1)

Dynaflow® Flux **CPH MSDS NA** 

902336 Version #: 03 Revision date: 12-Sept-2014 Issue date: 09-June-2011

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **US. Massachusetts RTK - Substance List**

Methanol (CAS 67-56-1) Listed.

US. New Jersey Worker and Community Right-to-Know Act

Methanol (CAS 67-56-1)

Potassium fluoride (CAS 7789-23-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Methanol (CAS 67-56-1)

Potassium fluoride (CAS 7789-23-3)

Mexico regulations This safety data sheet was prepared in accordance with the Official Mexican Standard

(NOM-018-STPS-2000).

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 3\*

Flammability: 0 Physical hazard: 0

NFPA ratings

3 0

**Disclaimer**The information in the sheet was written based on the best knowledge and experience currently

available.

Prepared by Not available.

Dynaflow® Flux CPH MSDS NA

902336 Version #: 03 Revision date: 12-Sept-2014 Issue date: 09-June-2011