



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

Page 1 of 4

Material Safety Data Sheet

Reviewed on 4/15/13
Dtd. 2011

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Reorder # 4850-4851

Manufacturer: Dynarex Corporation

PRODUCT / TRADE NAME: Perineum Wash

EMERGENCY OR INFORMATION TELEPHONE NO: 845-365-8200 (M-F DAYTIME) AT OTHER TIMES, CONTACT
THE LOCAL POISON CONTROL CENTER

CHEMICAL NAME: Perineum Wash

SECTION 2: HAZARDOUS INGREDIENTS / IDENTIFICATION

PRODUCT NAME: Perineum Wash

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%(Optional)
TEA-Lauryl Sulfate CAS 139-96-8	N/A	N/A	N/A	
Cocamidopropyl Betaine CAS 61789-40-0	N/A	N/A		
Propylene Glycol CAS 57-55-6	N/A	N/A		
Lanolin	N/A	N/A		
DMDM Hydantoin	N/A	N/A		
Tetrasodium EDTA	N/A	N/A		
Citric Acid	N/A	N/A		
Fragrance	N/A	N/A		
FD&C Red #33	N/A	N/A		
FD&C Blue #1 CAS 2650-18-2	N/A	N/A		

N/A = Ingredient not usually considered hazardous; no TLV or PEL available

This product contains no SARA 313 reportable substances.

Hazard Rating Scale: Health = 1 Fire = 1 Reactivity = 0



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

Page 2 of 4

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	220°F	Specific Gravity (H ₂ O = 1)	1.0
Vapor Pressure (mm Hg.)	N/A	Melting Point	20°-25°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water Soluble

Appearance and Odor Violet liquid with pleasant odor

SECTION 4: FIRE and HAZARD DATA

Flash Point (Method Use) 200°F	Flammable Limits N/A	LEL None	UEL None
--------------------------------	----------------------	----------	----------

Extinguishing Media CO₂, foam

Special Fire Fighting Procedures None

Unusual Fire and Explosion Hazards None

(Reproduce locally)

OSHA 174, Sept. 1985

SECTION 5: REACTIVITY DATA

Stability	Unstable	Stable X	Conditions to Avoid
			Freezing, excessive heat
Incompatibility (Materials to Avoid)	Water reactive substances, acids, alkalis, oxidizers		
Hazardous Decomposition or Byproducts	CO, NO _x		
Hazardous Polymerization	May Occur	Will Not Occur X	Conditions to Avoid N.A.



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

Page 3 of 4

SECTION 6: HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation? Not Significant	Skin? Possible	Ingestion? No
Health Hazards (Acute and Chronic)	Frequent contact may cause slight skin irritation in very sensitive individuals		
Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? No
Signs and Symptoms of Exposure	Slight skin irritation in very sensitive individuals.		
Medical Conditions			
Generally Aggravated by Exposure	Pre-existing dermatitis		
Emergency and First Aid Procedures	Eye irritant: flush 15 minutes with water		

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled	Wipe up small amounts and flush area to drain; collect and return large amounts to container.
Waste Disposal Method	Dispose of in accordance with all applicable local, state, and federal regulations.
Precautions to be Taken in Handling and Storing	Store in cool, dry place
Other Precautions	N/A



Telephone: (845) 365-8200 * Website: www.dynarex.com
Toll Free: (888) DYNAREX * Website: www.thcnet.com
Fax: (845) 365-8201

Page 4 of 4

SECTION 8: CONTROL MEASURES

Respiratory Protection (Specific Type) None required				
Ventilation	Local Exhaust N/A	Mechanical (General) N/A	Special N/A	Other N/A
Protective Gloves Surgical			Eye Protection None required	
Other Protective Clothing or Equipment None required				
Work/Hygienic Practices None				

SECTION 9: OTHER INFORMATION

Disclaimer:

The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.

This MSDS has been compiled in accordance - EC Directive 91/155/EC - OSHA's Hazcom Standard (29 CFR 1910.1200)