

Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum naphtha		64742-94-5	40 - < 50
Tert-butylbenzene		98-06-6	10 - < 20
1,4-diethylbenzene		105-05-5	3 - < 5
1,2,3-trimethylbenzene		526-73-8	1 - < 3
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
1h-indene, 2,3-dihydro-		496-11-7	1 - < 3
Carbon Dioxide		124-38-9	1 - < 3
D-(+)-limonene		5989-27-5	1 - < 3
NAPHTHALENE		91-20-3	1 - < 3
Benzene, 1,3-diethyl-		141-93-5	< 1
Diethylbenzene		25340-17-4	< 1
Quartz [silica Crystalline]		14808-60-7	< 1
Crystalline Silica		15468-32-3	< 0.2
Silica - Crystalline, Cristobalite		14464-46-1	< 0.2
Other components below reportable levels			20 - < 30

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m ³
NAPHTHALENE (CAS 91-20-3)	PEL	5000 ppm 50 mg/m ³
Petroleum naphtha (CAS 64742-94-5)	PEL	10 ppm 400 mg/m ³ 100 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (CAS 15468-32-3)	TWA	0.15 mg/m3	Total dust.
		0.05 mg/m3	Respirable.
Quartz [silica Crystalline] (CAS 14808-60-7)	TWA	1.2 mppcf	Respirable.
		0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
Silica - Crystalline, Cristobalite (CAS 14464-46-1)	TWA	2.4 mppcf	Respirable.
		0.15 mg/m3	Total dust.
		0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	25 ppm	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
	TWA	200 mg/m3	Non-aerosol.
Quartz [silica Crystalline] (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Silica - Crystalline, Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	125 mg/m3	
		25 ppm	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm	
NAPHTHALENE (CAS 91-20-3)	STEL	9000 mg/m3	
		5000 ppm	
		75 mg/m3	
Quartz [silica Crystalline] (CAS 14808-60-7)	TWA	15 ppm	
		50 mg/m3	
		10 ppm	
Silica - Crystalline, Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
		3 fibers/cm3	Fiber.
		3 fibers/cm3	Dust.
		5 mg/m3	fibers, total dust
		5 mg/m3	Fiber, total

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,4-diethylbenzene (CAS 105-05-5)	TWA	5 ppm
Benzene, 1,3-diethyl- (CAS 141-93-5)	TWA	5 ppm
D-(+)-limonene (CAS 5989-27-5)	TWA	165.5 mg/m ³
Diethylbenzene (CAS 25340-17-4)	TWA	30 ppm 5 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

NAPHTHALENE (CAS 91-20-3)	Can be absorbed through the skin.
Petroleum naphtha (CAS 64742-94-5)	Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	wear safety glasses with side shields (or goggles)
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Dark grey liquid slurry
Physical state	Liquid.
Form	Aerosol.
Color	Dark grey
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	347 °F (175 °C) estimated
Flash point	190.0 °F (87.8 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	12.14 hPa estimated

Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Emulsifies
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	40 cP
Viscosity temperature	77 °F (25 °C)
Other information	
Density	7.68 lbs/gal estimated
Explosive properties	Not explosive.
Flame extension	None
Flammability (flash back)	No
Flammability class	Combustible IIIA estimated
Heat of combustion (NFPA 30B)	35.4 kJ/g
Oxidizing properties	Not oxidizing.
Percent volatile	1.97 % estimated
Specific gravity	0.91 estimated
VOC (Weight %)	< 10 % w/w

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
1,2,3-trimethylbenzene (CAS 526-73-8)		
Acute		
Oral		
LD50	Rat	8970 mg/kg

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
D-(+)-limonene (CAS 5989-27-5)		
Acute		
Dermal		
LD50	Rabbit	5 g/kg
Oral		
LD50	Mouse	5600 - 6600 mg/kg
NAPHTHALENE (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg
Oral		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg
Petroleum naphtha (CAS 64742-94-5)		
Acute		
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 25 ml/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Crystalline Silica (CAS 15468-32-3)	1 Carcinogenic to humans.
D-(+)-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.
NAPHTHALENE (CAS 91-20-3)	2B Possibly carcinogenic to humans.
Quartz [silica Crystalline] (CAS 14808-60-7)	1 Carcinogenic to humans.
Silica - Crystalline, Cristobalite (CAS 14464-46-1)	1 Carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Crystalline Silica (CAS 15468-32-3)	Known To Be Human Carcinogen.
NAPHTHALENE (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.
Quartz [silica Crystalline] (CAS 14808-60-7)	Known To Be Human Carcinogen.
Silica - Crystalline, Cristobalite (CAS 14464-46-1)	Known To Be Human Carcinogen.
	Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
1h-indene, 2,3-dihydro- (CAS 496-11-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 14 mg/l, 96 hours
Benzene, 1,3-diethyl- (CAS 141-93-5)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 4.05 - 4.25 mg/l, 96 hours
D-(+)-limonene (CAS 5989-27-5)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>) 69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 0.619 - 0.796 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (<i>Oncorhynchus gorbuscha</i>) 1.11 - 1.68 mg/l, 96 hours
Petroleum naphtha (CAS 64742-94-5)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,4-diethylbenzene	4.45
Benzene, 1,3-diethyl-	4.44
D-(+)-limonene	4.232
NAPHTHALENE	3.3
Tert-butylbenzene	4.11

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer Commodity
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	T75, TP5
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315

IATA

UN number	UN1950
UN proper shipping name	Aerosol, Flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG


UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

NAPHTHALENE (CAS 91-20-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - < 3
NAPHTHALENE	91-20-3	1 - < 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,3-trimethylbenzene (CAS 526-73-8)
1,2,4-Trimethylbenzene (CAS 95-63-6)
NAPHTHALENE (CAS 91-20-3)
Petroleum naphtha (CAS 64742-94-5)
Quartz [silica Crystalline] (CAS 14808-60-7)
Silica - Crystalline, Cristobalite (CAS 14464-46-1)
Tert-butylbenzene (CAS 98-06-6)

US. Massachusetts RTK - Substance List

1,2,3-trimethylbenzene (CAS 526-73-8)

1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,4-diethylbenzene (CAS 105-05-5)
 Benzene, 1,3-diethyl- (CAS 141-93-5)
 Carbon Dioxide (CAS 124-38-9)
 Crystalline Silica (CAS 15468-32-3)
 NAPHTHALENE (CAS 91-20-3)
 Quartz [silica Crystalline] (CAS 14808-60-7)
 Silica - Crystalline, Cristobalite (CAS 14464-46-1)
 Tert-butylbenzene (CAS 98-06-6)

US. New Jersey Worker and Community Right-to-Know Act

1,2,3-trimethylbenzene (CAS 526-73-8)
 1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,4-diethylbenzene (CAS 105-05-5)
 Benzene, 1,3-diethyl- (CAS 141-93-5)
 Carbon Dioxide (CAS 124-38-9)
 Crystalline Silica (CAS 15468-32-3)
 D-(+)-limonene (CAS 5989-27-5)
 Diethylbenzene (CAS 25340-17-4)
 NAPHTHALENE (CAS 91-20-3)
 Petroleum naphtha (CAS 64742-94-5)
 Quartz [silica Crystalline] (CAS 14808-60-7)
 Silica - Crystalline, Cristobalite (CAS 14464-46-1)
 Tert-butylbenzene (CAS 98-06-6)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,3-trimethylbenzene (CAS 526-73-8)
 1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,4-diethylbenzene (CAS 105-05-5)
 Benzene, 1,3-diethyl- (CAS 141-93-5)
 Carbon Dioxide (CAS 124-38-9)
 Crystalline Silica (CAS 15468-32-3)
 NAPHTHALENE (CAS 91-20-3)
 Quartz [silica Crystalline] (CAS 14808-60-7)
 Silica - Crystalline, Cristobalite (CAS 14464-46-1)
 Tert-butylbenzene (CAS 98-06-6)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
 NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica (CAS 15468-32-3)	Listed: October 1, 1988
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002
Quartz [silica Crystalline] (CAS 14808-60-7)	Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-28-2015
Revision date	05-18-2016
Version #	06
HMIS® ratings	Health: 2* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Physical & Chemical Properties: Multiple Properties
GHS: Classification