MSDS

Material Safety Data Sheet



1403 Herkimer Street Joliet, IL 60432-1059 (877) EKI-CHEM (815) 723-4000 www.eki-chem.com

24 HOUR EMERGENCY TELEPHONE NUMBER CALL CHEMTREC 1-800-424-9300

SupermountTM

SECTION 1 PRODUCT IDENTIFICATION

NAME: Supermount™ Coverslip Adhesive

EKI ORDER NUMBERS: 7405

SYNONYMS: Coverslip adhesive for microscopy, Mounting Media

CAS NO: Does not apply FORMULA: Does not apply REVISION DATE: 8 March 2005

****LABEL HAZARD STATEMENT AND PRECAUTIONS****

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION. Keep away from heat, sparks and flame. Avoid contact with skin, eyes and clothing. Avoid breathing vapor. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

SECTION 2 HAZARDOUS INGREDIENTS / EXPOSURE LIMITS

Terpene Resin Mixture / NA N/E N/E

Xylenes, 35% is subject to the reporting requirements of SARA 313 and 40CFR372

SECTION 3 PHYSICAL / CHEMICAL CHARACTERISTICS

SOLUBILITY IN WATER: Negligible BOILING POINT: (C): 141 VAPOR PRESSURE (mm Hg): 21 VAPOR DENSITY: 3.7 SPECIFIC GRAVITY: 0.87 MELTING POINT: (C): N/A

EVAPORATION RATE: 0.6

APPEARANCE AND ODOR: Clear, yellowish, sticky, viscous liquid. Sweet xylene odor.

SECTION 4 FIRE / EXPLOSION HAZARD DATA

FLASH POINT (C): N/E

AUTOIGNITION TEMPERATURE (C): N/E

FLAMMABLE LIMITS (%) UEL: N/E LEL: N/E EXTINGUISHING MEDIA: Water fog, foam dry chemical or CO2.

E K Industries, Inc. Revised: 8 March 2005

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive-pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water to prevent vapor pressure buildup and container weakening.

SECTION 5 REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Sources of ignition, heat.

MATERIALS TO AVOID: Strong oxidizers. HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2. HAZARDOUS POLYMERIZATION: Does not occur.

SECTION 6 HEALTH HAZARD DATA

ROUTES OF ENTRY AND EFFECTS OF OVEREXPOSURE

INHALATION: May cause nose and throat irritation.

SKIN CONTACT: May cause irritation. EYE CONTACT: May cause irritation. SKIN ABSORPTION: Kidney, liver damage.

INGESTION: Digestive tract irritation. Nervous system depression.

CHRONIC: Kidney, liver damage.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Asthma, skin sensitivity to xylenes,

impaired lung function.
CARCINOGENICITY: None.

****FIRST AID PROCEDURES****

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Immediately flush with plenty of water for at least 15 minutes.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Get immediate medical attention. Do NOT induce vomiting. If vomiting occurs, keep head below knees to avoid aspiration.

SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED: Eliminate sources of ignition. Absorb with inert material and containerize for disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with all applicable federal, state, and local environmental regulations.

STORAGE: Store tightly closed in approved "Flammable Liquids" storage area.

SECTION 8 CONTROL MEASURES

VENTILATION: Local preferred.

RESPIRATORY PROTECTION: NIOSH approved respirator if OSHA Exposure Limits

are exceeded.

EYE PROTECTION: Chemical splash safety goggles and/or full face shield. SKIN PROTECTION: Xylene-proof gloves, lab coat and impervious apron.

E K INDUSTRIES, INC. MAKES NO REPRESENTATION AS TO THE COMPREHENSIVENESS OR ACCURACY OF THIS INFORMATION. INDIVIDUALS RECEIVING THIS INFORMATION MUST EXERCISE THEIR INDEPENDENT JUDGMENT IN DETERMINING ITS APPROPRIATENESS FOR A PARTICULAR PURPOSE. ACCORDINGLY, E K INDUSTRIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES OF ANY KIND OR NATURE RESULTING FROM THE USE OF ANY SUCH INFORMATION. NO REPRESENTATIONS OR WARRANTIES OF ANY KIND OR NATURE, INCLUDING BUT NOT LIMITED TO: EXPRESS WARRANTIES, IMPLIED WARRANTIES OF MERCHANTABILITY, OR WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE, ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS.

E K Industries, Inc. Revised: 8 March 2005