



Material Safety Data Sheet

Issuing Date 05-Aug-2011

Revision Date

Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name GREEN RD ACETONE-BASED TRAFFIC 100 VOC
Product Code(s) 7105
UN-Number UN1263
Recommended Use Traffic paint

Supplier Address

Ennis Paint Inc.
5910 North Central Expressway
Suite 1050
Dallas TX 75206
T: 800.331.8118
800.331.8118 (For Technical Inquiries)

Chemical Emergency Phone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Highly flammable liquid and vapor
May be harmful if swallowed, inhaled, or absorbed through skin
Irritating to eyes and skin
Risk of serious damage to the lungs (by aspiration)
Causes central nervous system depression.
May adversely affect liver and kidney.
Cancer hazard

WARNING! This product contains a chemical known in the State of California to cause cancer and birth defects or other reproductive harm.

Appearance Green

Physical State Liquid.

Odor Solvent

Potential Health Effects

Principle Routes of Exposure Inhalation. Eye contact. Skin contact.

Acute Toxicity

Eyes

Moderately irritating to the eyes

Skin

Irritating to skin. May be harmful if absorbed through skin. Repeated exposure may cause skin dryness or cracking.

Inhalation

May be harmful if inhaled. Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled.

Ingestion

May be harmful if swallowed. Ingestion may cause irritation to mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. May cause additional effects as listed under "Inhalation".

Chronic Effects	Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). May cause adverse liver and kidney effects.
Aggravated Medical Conditions	Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects. Pre-existing eye disorders. Liver disorders. Skin disorders. Respiratory disorders. Neurological disorders. Kidney disorders.
Interactions with Other Chemicals	Use of alcoholic beverages may enhance toxic effects.
Environmental Hazard	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Acetone	67-64-1	15-40
Petroleum naphtha, light aromatic	64742-95-6	1-5
1,2,4 Trimethylbenzene	95-63-6	1-5
Phthalate compound	Proprietary	0.1-1
Quartz	14808-60-7	0.1-1
Ethyl benzene	100-41-4	0.1-1

4. FIRST AID MEASURES

General Advice	If swallowed, get medical help or contact a Poison Control Center right away. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Consult a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Notes to Physician	Aspiration hazard. Treat symptomatically.
Protection of First-aiders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Highly flammable liquid and vapor
Flash Point	-4°F / -20°C (Acetone)
Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable Extinguishing Media CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Explosion Data

Sensitivity to Mechanical Impact None
Sensitivity to Static Discharge Yes.

Specific Hazards Arising from the Chemical Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA	Health Hazard 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal Protection X

**Indicates a chronic health hazard.*

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. Do not allow material to contaminate ground water system.

Methods for Containment Dike far ahead of liquid spill for later disposal. A vapor suppressing foam may be used to reduce vapors.

Methods for Cleaning Up Cover liquid spill with sand, earth or other noncombustible absorbent material. Pick up and transfer to properly labeled containers. Use clean non-sparking tools to collect absorbed material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

7. HANDLING AND STORAGE

Handling Use only in area provided with appropriate exhaust ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing.

Storage Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Ethyl benzene 100-41-4	STEL: 125 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Phthalate compound	TWA: 5 mg/m ³	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³ (vacated) STEL: 10 mg/m ³	IDLH: 5000 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Measures

Showers. Eyewash stations. Explosion proof ventilation systems.

Personal Protective Equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

Tightly fitting safety goggles.

Protective gloves.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Green.	Odor	Solvent.
Odor Threshold	No information available	Physical State	Liquid
pH	No information available.	Autoignition Temperature	No information available.
Flash Point	-4°F / -20°C (Acetone)	Boiling Point/Boiling Range	>35°C / >95°F
Decomposition Temperature	No information available.	Explosion Limits	No information available.
Melting Point/Range	Not applicable	Evaporation Rate	No information available
Flammability Limits in Air	(For Acetone)	Vapor Density	No data available
Upper	12.8		
Lower	0.8		
Solubility	Insoluble		
Vapor Pressure	No data available		
VOC Content (%)	26.862		

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Strong acids. Strong oxidizing agents. Chlorinated compounds.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Carbon oxides.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information No acute toxicity information is available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 mg/kg (Rat)		
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Petroleum naphtha, light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h > 5.2 mg/L (Rat) 4 h
1,2,4 Trimethylbenzene	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Phthalate compound	= 6860 mg/kg (Rat)	= 24500 mg/kg (Rabbit)	> 23.67 mg/L (Rat) 1 h > 10.62 mg/L (Rat) 4 h

Chronic Toxicity

Chronic Toxicity

Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). May cause adverse liver and kidney effects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Phthalate compound	A3	Group 3	Reasonably Anticipated	X
Quartz	A2	Group 1	Known	X
Ethyl benzene	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

Target Organ Effects

Central nervous system (CNS). Kidney. Liver. Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Petroleum naphtha, light aromatic		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene		LC50 96 h: 7.19-8.28 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Phthalate compound	EC50 96 h: > 0.1 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 0.1 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: > 130 mg/L (Desmodesmus subspicatus)	LC50 96 h: 0.27 - 0.67 mg/L flow-through (Pimephales promelas) LC50 96 h: > 0.16 mg/L static (Pimephales promelas) LC50 96 h: > 0.200 mg/L flow-through (Lepomis macrochirus) LC50 96 h: > 0.200 mg/L static (Lepomis macrochirus) LC50 96 h: > 0.32 mg/L semi-static (Brachydanio rerio) LC50 96 h: > 0.32 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: > 0.32 mg/L semi-static (Oryzias latipes) LC50 96 h: > 0.32 mg/L semi-static (Poecilia reticulata) LC50 96 h: > 0.67 mg/L flow-through (Oryzias latipes) LC50 96 h: > 100 mg/L static (Oncorhynchus mykiss)	EC50 = 800 mg/L 15 min EC50 = 800 mg/L 30 min EC50 = 800 mg/L 5 min	LC50 48 h: = 9.4 mg/L (Daphnia magna) EC50 48 h: > 0.16 mg/L (Daphnia magna)
Ethyl benzene	EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0-18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: 7.55-11 mg/L flow-through (Pimephales promelas) LC50 96 h: 9.1-15.6 mg/L static (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)

Chemical Name	Log Pow
Acetone	-0.24
1,2,4 Trimethylbenzene	3.63
Phthalate compound	5.03
Ethyl benzene	3.118

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Do not re-use empty containers. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream: F039		U002
Phthalate compound -	U028	Included in waste stream: F039		U028

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable
Ethyl benzene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Subsidiary Class	
Packing Group	II
Description	UN1263,Paint,3,PG II
Emergency Response Guide Number	128

TDG

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263,PAINT,3,PG II

MEX

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263 Paint,3,II

ICAO

UN-Number	UN1263
Proper shipping name	Paint related material
Hazard Class	3
Packing Group	II
Description	UN1263,Paint related material,3,PG II

IATA

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
ERG Code	3L
Description	UN1263,Paint,3,PG II

IMDG/IMO

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-E
Description	UN1263, Paint,3,PG II, FP -20C

RID

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Description	UN1263 Paint,3,II

ADR

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Classification Code F1
Description UN1263 Paint,3,II

ADN

UN-No UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Classification Code F1
Special Provisions 163, 640C, 650
Description UN1263 Paint,3,II
Hazard Labels 3
Limited Quantity LQ6
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Phthalate compound		0.85	0.1
1,2,4 Trimethylbenzene	95-63-6	1.17	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Phthalate compound		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl benzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Phthalate compound	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Ethyl benzene	100-41-4	Carcinogen
Phthalate compound		Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Quartz	X	X	X	-	X
Diocetylphthalate	X	X	X	X	X
Acetone		X			X
Ethyl benzene		X			X
1,2,4 Trimethylbenzene	X	X	X	X	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Quartz		Mexico: TWA= 0.1 mg/m ³
Acetone		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³
Ethyl benzene		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m ³
1,2,4 Trimethylbenzene		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Phthalate compound	A3	Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid
D2A Very toxic materials
D2B Toxic materials



Canadian National Pollutant Release Inventory (NPRI)

Chemical Name	NPRI
1,2,4 Trimethylbenzene	X
Phthalate compound	X

Legend

X - Listed

16. OTHER INFORMATION

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 05-Aug-2011
Revision Date
Revision Note Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

End of Safety Data Sheet