



# Material Safety Data Sheet

Issuing Date 23-Sep-2011

Revision Date

Revision Number 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** SEMI-GLOSS WHITE SOLVENT PAINT

**Product Code(s)** 985141

**UN-Number** UN1263

**Recommended Use** Traffic paint

**Product Technology** S/B

### Supplier Address

Ennis Paint Inc.  
5910 North Central Expressway  
Suite 1050  
Dallas TX 75206  
T: 800.331.8118  
800.331.8118 (For Technical Inquiries)

**Chemical Emergency Phone Number** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**DANGER!**

### Emergency Overview

Highly flammable liquid and vapor  
Irritating to eyes and skin  
Risk of serious damage to the lungs (by aspiration)  
Causes central nervous system depression.  
May adversely affect liver and kidney.  
Cancer hazard

Contains a known or suspected reproductive toxin

**WARNING!** This product contains a chemical known in the State of California to cause cancer and birth defects or other reproductive harm.

**Appearance** White

**Physical State** Liquid.

**Odor** Aromatic solvent/toluene

### **Potential Health Effects**

**Principle Routes of Exposure** Inhalation. Skin contact. Eye contact.

### **Acute Toxicity**

**Eyes**

Moderately irritating to the eyes

**Skin**

Irritating to skin. Repeated exposure may cause skin dryness or cracking.

**Inhalation**

Inhalation in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled.

**Ingestion**

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. May cause additional affects as listed under "Inhalation".

<b>Chronic Effects</b>	Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. May cause adverse liver and kidney effects. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.
<b>Main Symptoms</b>	Vapors may cause drowsiness and dizziness. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
<b>Aggravated Medical Conditions</b>	Liver disorders, kidney disorders, central nervous system, cardiovascular, blood disorders and respiratory disorders. Skin disorders. Pre-existing eye disorders.
<b>Interactions with Other Chemicals</b>	Use of alcoholic beverages may enhance toxic effects.
<b>Environmental Hazard</b>	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Toluene	108-88-3	30-60
Titanium dioxide	13463-67-7	15-40
Feldspar	68476-25-5	7-13
Chloroalkanes	61788-76-9	3-7
Quartz	14808-60-7	1-5
Phthalate compound	Proprietary	1-5
Ethyl benzene	100-41-4	0.1-1
Benzene	71-43-2	<0.1

### 4. FIRST AID MEASURES

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. If swallowed, get medical help or contact a Poison Control Center right away.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. If irritation persists, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. Consult a physician.
<b>Inhalation</b>	Move victim to fresh air. If breathing has stopped, contact emergency medical services immediately. If not breathing, give artificial respiration.
<b>Ingestion</b>	Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
<b>Notes to Physician</b>	Aspiration hazard. Treat symptomatically.
<b>Protection of First-aiders</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Highly flammable liquid and vapor			
<b>Flash Point</b>	-14°F / -10°C			
<b>Suitable Extinguishing Media</b>	Dry chemical, CO <sub>2</sub> , water spray or regular foam. Use water spray or fog; do not use straight streams.			
<b>Unsuitable Extinguishing Media</b>	CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.			
<b>Explosion Data</b>				
<b>Sensitivity to Mechanical Impact</b>	None			
<b>Sensitivity to Static Discharge</b>	Yes.			
<b>Specific Hazards Arising from the Chemical</b>	Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.			
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
<b><u>NFPA</u></b>	<b>Health Hazard 2</b>	<b>Flammability 3</b>	<b>Instability 0</b>	<b>Physical and Chemical Hazards -</b>
<b><u>HMIS</u></b>	<b>Health Hazard 2*</b>	<b>Flammability 3</b>	<b>Physical Hazard 0</b>	<b>Personal Protection X</b>

\*Indicates a chronic health hazard.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use personal protective equipment. Avoid contact with skin, eyes and clothing.
<b>Environmental Precautions</b>	Prevent entry into waterways, sewers, basements or confined areas. Do not allow material to contaminate ground water system.
<b>Methods for Containment</b>	Dike far ahead of liquid spill for later disposal. A vapor suppressing foam may be used to reduce vapors.
<b>Methods for Cleaning Up</b>	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Ground and bond containers when transferring material. Pick up and transfer to properly labeled containers.
<b>Other Information</b>	Water spray may reduce vapor; but may not prevent ignition in closed spaces.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing.
<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep in properly labeled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Phthalate compound	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup> (vacated) STEL: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Engineering Measures

Showers. Eyewash stations. Explosion proof ventilation systems.

### Personal Protective Equipment

#### Eye/Face Protection Skin and Body Protection Respiratory Protection

Tightly fitting safety goggles.  
Wear protective gloves/clothing.  
If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

### Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal feeding stuffs.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	White.	<b>Odor</b>	Aromatic solvent/toluene.
<b>Odor Threshold</b>	No information available	<b>Physical State</b>	Liquid
<b>pH</b>	No information available.	<b>Autoignition Temperature</b>	No information available.
<b>Flash Point</b>	-14°F / -10°C	<b>Boiling Point/Boiling Range</b>	>35°C / >95°F
<b>Decomposition Temperature</b>	No information available.	<b>Explosion Limits</b>	No information available.
<b>Melting Point/Range</b>	No information available	<b>Evaporation Rate</b>	No information available
<b>Flammability Limits in Air</b>	(Toluene)	<b>Vapor Density</b>	No data available.
<b>Upper</b>	7.1%		
<b>Lower</b>	1.1%		
<b>Solubility</b>	No information available.		
<b>Vapor Pressure</b>	No data available.		
<b>VOC Content (%)</b>	31.4407		

**10. STABILITY AND REACTIVITY**

<b>Stability</b>	Stable under recommended storage conditions.
<b>Incompatible Products</b>	Strong acids. Strong oxidizing agents.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Hazardous Decomposition Products</b>	Carbon oxides. Hydrocarbons.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

**Product Information** No acute toxicity information is available for this product.

### **Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 mg/kg ( Rat )		
Toluene	>5580 mg/kg ( Rat )	12124 mg/kg ( Rat ) 8390 mg/kg ( Rabbit )	26700 ppm ( Rat ) 1 h
Phthalate compound	= 6860 mg/kg ( Rat )	= 24500 mg/kg ( Rabbit )	> 23.67 mg/L ( Rat ) 1 h > 10.62 mg/L ( Rat ) 4 h

### Chronic Toxicity

#### **Chronic Toxicity**

Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. May cause adverse liver and kidney effects. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.

#### **Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene		Group 3	-	-
Titanium dioxide		Group 2B		X
Chloroalkanes		Group 2B		X
Quartz	A2	Group 1	Known	X
Phthalate compound	A3	Group 3	Reasonably Anticipated	X
Ethyl benzene	A3	Group 2B		X
Benzene	A1	Group 1	Known	X

#### **ACGIH: (American Conference of Governmental Industrial Hygienists)**

- A1 - Known Human Carcinogen
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen

#### **IARC: (International Agency for Research on Cancer)**

- Group 1 - Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans
- Group 3: Not Classifiable as to its Carcinogenicity to Humans

#### **NTP: (National Toxicity Program)**

- Known - Known Carcinogen
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

#### **OSHA: (Occupational Safety & Health Administration)**

- X - Present

#### **Reproductive Toxicity**

Product is or contains a chemical which is a known or suspected reproductive hazard.

#### **Target Organ Effects**

Central nervous system (CNS). Cardiovascular system Respiratory system. Kidney. Liver.

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

### Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Toluene	EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 15.22-19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89-7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1-17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0-15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87-70.34 mg/L Poecilia reticulata 96 h static	EC50 = 19.7 mg/L 30 min	EC50 48 h: 5.46 - 9.83 mg/L Static (Daphnia magna) EC50 48 h: = 11.5 mg/L (Daphnia magna)
Phthalate compound	EC50 96 h: > 0.1 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 0.1 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: > 130 mg/L (Desmodesmus subspicatus)	LC50 96 h: 0.27 - 0.67 mg/L flow-through (Pimephales promelas) LC50 96 h: > 0.16 mg/L static (Pimephales promelas) LC50 96 h: > 0.200 mg/L flow-through (Lepomis macrochirus) LC50 96 h: > 0.200 mg/L static (Lepomis macrochirus) LC50 96 h: > 0.32 mg/L semi-static (Brachydanio rerio) LC50 96 h: > 0.32 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: > 0.32 mg/L semi-static (Oryzias latipes) LC50 96 h: > 0.32 mg/L semi-static (Poecilia reticulata) LC50 96 h: > 0.67 mg/L flow-through (Oryzias latipes) LC50 96 h: > 100 mg/L static (Oncorhynchus mykiss)	EC50 = 800 mg/L 15 min EC50 = 800 mg/L 30 min EC50 = 800 mg/L 5 min	LC50 48 h: = 9.4 mg/L (Daphnia magna) EC50 48 h: > 0.16 mg/L (Daphnia magna)
Ethyl benzene	EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0-18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: 7.55-11 mg/L flow-through (Pimephales promelas) LC50 96 h: 9.1-15.6 mg/L static (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Benzene	EC50 72 h: = 29 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 10.7-14.7 mg/L flow-through (Pimephales promelas) LC50 96 h: 22330-41160 µg/L static (Pimephales promelas) LC50 96 h: 70000-142000 µg/L static (Lepomis macrochirus) LC50 96 h: = 22.49 mg/L static (Lepomis macrochirus) LC50 96 h: = 28.6 mg/L static (Poecilia reticulata) LC50 96 h: = 5.3 mg/L flow- through (Oncorhynchus mykiss)		EC50 48 h: 8.76 - 15.6 mg/L Static (Daphnia magna) EC50 48 h: = 10 mg/L (Daphnia magna)

Chemical Name	Log Pow
Toluene	2.65
Phthalate compound	5.03
Ethyl benzene	3.118
Benzene	1.83

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Methods** Dispose of in accordance with local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated Packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Do not re-use empty containers.

**US EPA Waste Number**  
 D001  
 D008  
 D018  
 U019  
 U056  
 U154  
 U220

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Phthalate compound -	U028	Included in waste stream: F039		U028
Ethyl benzene - 100-41-4		Included in waste stream: F039		
Benzene - 71-43-2	waste number U019	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172	= 0.5 mg/L regulatory level	U019

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene - 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

**California Hazardous Waste Codes** 461

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Toluene	Toxic Ignitable
Feldspar	Toxic soluble
Ethyl benzene	Toxic Ignitable
Benzene	Toxic Ignitable

<b>14. TRANSPORT INFORMATION</b>
----------------------------------

**DOT**

<b>UN-Number</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Subsidiary Class</b>	None
<b>Packing Group</b>	II
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a severe marine pollutant according to DOT.
<b>Description</b>	UN1263,Paint,3,PG II
<b>Emergency Response Guide Number</b>	128

**TDG**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263,PAINT,3,PG II

**MEX**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263 Paint,3,II

**ICAO**

<b>UN-Number</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263,Paint,3,PG II

**IATA**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	3L
<b>Description</b>	UN1263,Paint,3,PG II

**IMDG/IMO**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>EmS No.</b>	F-E, S-E
<b>Description</b>	UN1263, Paint,3,PG II, FP -18C

**RID**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1

<b>Description</b>	UN1263 Paint,3,II
--------------------	-------------------

**ADR**

<b>UN-Number</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Description</b>	UN1263 Paint,3,II

**ADN**

<b>UN-No</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Special Provisions</b>	163, 640C, 650
<b>Description</b>	UN1263 Paint,3,II
<b>Hazard Labels</b>	3
<b>Limited Quantity</b>	LQ6
<b>Ventilation</b>	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL</b>	Complies

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethyl benzene	100-41-4	0.8256	0.1
Phthalate compound		1.18	0.1
Toluene	108-88-3	35.2886	1.0

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X
Phthalate compound		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Phthalate compound	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Ethyl benzene	100-41-4	Carcinogen
Toluene	108-88-3	Developmental
Benzene	71-43-2	Carcinogen Developmental Male Reproductive
Phthalate compound		Carcinogen Developmental Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Quartz	X	X	X	-	X
Ethyl benzene	X	X	X	X	X
Titanium dioxide	X	X	X	-	X
Diocetylphthalate	X	X	X	X	X
Toluene	X	X	X	X	X

**International Regulations**

Chemical Name	Carcinogen Status	Exposure Limits
Quartz		Mexico: TWA= 0.1 mg/m <sup>3</sup>
Titanium dioxide		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Toluene		Mexico: TWA= 50 ppm Mexico: TWA= 188 mg/m <sup>3</sup>
Phthalate compound	A3	Mexico: TWA 5 mg/m <sup>3</sup> Mexico: STEL 10 mg/m <sup>3</sup>

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

B2 Flammable liquid  
D2A Very toxic materials  
D2B Toxic materials



## Canadian National Pollutant Release Inventory (NPRI)

Chemical Name	NPRI
Toluene	X
Phthalate compound	X

**Legend**

X - Listed

**16. OTHER INFORMATION**

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501  
23-Sep-2011

**Issuing Date**  
**Revision Date**

**Revision Note** Initial Release.

**General Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

**End of Safety Data Sheet**