



Material Safety Data Sheet

Issuing Date 16-May-2011

Revision Date 23-Aug-2011

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Duraset 5 Fawn MMA (4:1)

Product Code(s) 999655F

UN-Number UN1263

Recommended Use Traffic paint

Product Technology MMA

Supplier Address

Ennis Paint Inc.

5910 North Central Expressway

Suite 1050

Dallas TX 75206

T: 800.331.8118

800.331.8118 (For Technical Inquiries)

Chemical Emergency Phone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Flammable liquid

Irritating to respiratory system and skin

May produce an allergic reaction

Cancer hazard

WARNING! This product contains a chemical known in the State of California to cause cancer and birth defects or other reproductive harm.

Appearance Fawn

Physical State Viscous liquid.

Odor Acrid fruity

Potential Health Effects

Acute Toxicity

Eyes

Skin

May cause irritation.

Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation

Irritating to respiratory system.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chronic Effects

Repeated contact may cause allergic reactions in very susceptible persons. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Aggravated Medical Conditions

Skin disorders. Respiratory disorders.

Environmental Hazard

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Methyl Methacrylate	80-62-6	15-40
Butyl acrylate	141-32-2	10-30
Titanium dioxide	13463-67-7	1-5
Ci 77491	1309-37-1	1-5
Quartz	14808-60-7	0.1-1
Methyl pyrrolidone	872-50-4	0.1-1
Chromium	7440-47-3	<0.1

4. FIRST AID MEASURES

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, call a physician.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. Consult a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Administer oxygen if breathing is difficult. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Seek immediate medical attention/advice.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician immediately.
Notes to Physician	Treat symptomatically. May cause sensitization of susceptible persons.
Protection of First-aiders	Remove all sources of ignition. Use personal protective equipment.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Flammable liquid.			
Flash Point	55.4°F / 13°C			
Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or alcohol-resistant foam.			
Explosion Data				
Sensitivity to Mechanical Impact	None			
Sensitivity to Static Discharge	Yes.			
Specific Hazards Arising from the Chemical	Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).			
Protective Equipment and Precautions for Firefighters	Move containers from fire area if you can do it without risk.			
NFPA	Health Hazard 2	Flammability 3	Instability 2	Physical and Chemical Hazards *
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 2	Personal Protection X

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use personal protective equipment. Avoid contact with skin, eyes and clothing.
Environmental Precautions	Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods for Containment	Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.
Methods for Cleaning Up	Dam up. Use personal protective equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically and collect in suitable container for disposal.
Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.

7. HANDLING AND STORAGE

Handling	Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists.
Storage	Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Ci 77491 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ fume (vacated) TWA: 10 mg/m ³ fume	IDLH: 2500 mg/m ³ Fe dust and fume TWA: 5 mg/m ³ Fe dust and fume
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Butyl acrylate 141-32-2	TWA: 2 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 55 mg/m ³	TWA: 10 ppm TWA: 55 mg/m ³
Methyl Methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 410 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Measures Showers. Eyewash stations. Explosion proof ventilation systems.

Personal Protective Equipment

Eye/Face Protection	Safety glasses with side-shields.
Skin and Body Protection	Wear protective gloves/clothing.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures When using, do not eat, drink or smoke. Remove and wash contaminated clothing before reuse. Wash thoroughly after handling. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Fawn.	Odor	Acrid fruity .
Odor Threshold	No information available	Physical State	Viscous liquid
pH	No information available.		
Flash Point	55.4°F / 13°C	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Boiling Range	No information available
Melting Point/Range	No information available		
Flammability Limits in Air	No information available.	Explosion Limits	No information available.
Solubility	No information available.	Evaporation Rate	No information available
Vapor Pressure	No data available	Vapor Density	No data available

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Alkaline. Amines. Oxidizing or reducing agents. Sulfur compounds.
Conditions to Avoid	Excessive heat.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Polymerization may occur when exposed to excessive heating and incompatibles.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information Irritating to respiratory system and skin.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl pyrrolidone	= 3598 mg/kg (Rat)	= 2000 mg/kg (Rabbit) = 2500 mg/kg (Rat)	= 3.1 mg/L (Rat) 4 h
Quartz	500 mg/kg (Rat)		
Ci 77491	> 10000 mg/kg (Rat)		
Titanium dioxide	> 10000 mg/kg (Rat)		> 6820 mg/m ³
Butyl acrylate	= 900 mg/kg (Rat)	= 1800 mg/kg (Rabbit) = 2 mL/kg (Rabbit)	= 10.3 mg/L (Rat) 4 h = 2730 ppm (Rat) 4 h
Methyl Methacrylate	= 7872 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 400 ppm (Rat) 1 h = 4632 ppm (Rat) 4 h

Chronic Toxicity

Chronic Toxicity

Repeated contact may cause allergic reactions in very susceptible persons. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Methyl Methacrylate		Group 3		
Butyl acrylate		Group 3		
Titanium dioxide		Group 2B		X
Ci 77491		Group 3		
Quartz	A2	Group 1	Known	X
Chromium		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Target Organ Effects

Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl Methacrylate	EC50 96 h: = 170 mg/L (<i>Pseudokirchneriella subcapitata</i>)	LC50 96 h: 125.5-190.7 mg/L static (Pimephales promelas) LC50 96 h: 153.9-341.8 mg/L static (Lepomis macrochirus) LC50 96 h: 170-206 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 243-275 mg/L flow-through (Pimephales promelas) LC50 96 h: 326.4-426.9 mg/L static (Poecilia reticulata) LC50 96 h: > 79 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: > 79 mg/L static (Oncorhynchus mykiss)		EC50 48 h: = 69 mg/L (<i>Daphnia magna</i>)
Butyl acrylate	EC50 96 h: = 5.5 mg/L (<i>Pseudokirchneriella subcapitata</i>)	LC50 72 h: = 5 mg/L (<i>Carassius auratus</i>) LC50 96 h: = 5.2 mg/L flow-through (Oncorhynchus mykiss)	EC50 = 31.0 mg/L 30 min EC50 = 35.0 mg/L 15 min EC50 = 37.0 mg/L 5 min	EC50 24 h: = 42 mg/L (<i>Daphnia magna</i>) EC50 48 h: = 8.2 mg/L (<i>Daphnia magna</i>)
Methyl pyrrolidone	EC50 72 h: > 500 mg/L (<i>Desmodesmus subspicatus</i>)	LC50 96 h: = 1072 mg/L static (Pimephales promelas) LC50 96 h: = 1400 mg/L static (Poecilia reticulata) LC50 96 h: = 4000 mg/L static (Leuciscus idus) LC50 96 h: = 832 mg/L static (Lepomis macrochirus)		EC50 48 h: = 4897 mg/L (<i>Daphnia magna</i>)

Chemical Name	Log Pow
Methyl Methacrylate	0.7
Butyl acrylate	2.38
Methyl pyrrolidone	-0.46

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl Methacrylate - 80-62-6	U162	Included in waste stream: F039		U162
Chromium - 7440-47-3		Included in waste streams: F032, F034, F035, F037, F038, F039	5.0 mg/L regulatory level	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl Methacrylate	Toxic Ignitable
Chromium	Toxic Corrosive Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Subsidiary Class	None
Packing Group	II
Description	UN1263,Paint,3,PG II
Emergency Response Guide Number	128

TDG

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263,PAINT,3,PG II

MEX

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263 Paint,3,II

ICAO

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263,Paint,3,PG II

IATA

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
ERG Code	3L
Description	UN1263,Paint,3,PG II

IMDG/IMO

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-E
Description	UN1263, Paint,3,PG II, FP 13C

RID

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Description	UN1263 Paint,3,II

ADR

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Description	UN1263 Paint,3,II

ADN

UN-No	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263 Paint,3,II
Hazard Labels	3
Limited Quantity	LQ6
Ventilation	VE01

15. REGULATORY INFORMATIONInternational Inventories

TSCA
DSL

All components are listed on the TSCA Inventory.
All components are listed either on the DSL or NDSL.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl pyrrolidone	872-50-4	0.1-1	1.0
Butyl acrylate	141-32-2	10-30	1.0
Methyl Methacrylate	80-62-6	15-40	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	Yes

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Methyl Methacrylate	1000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Chromium			RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl Methacrylate	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Methyl pyrrolidone	872-50-4	Developmental
Nickel	7440-02-0	Carcinogen
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Methyl pyrrolidone	X	X	X		
Chromium		X			X
Quartz	X	X	X	-	X
Ci 77491	X	X	X		X
Titanium dioxide	X	X	X	-	X
Butyl acrylate	X	X	X		X
Methyl Methacrylate	X	X	X	X	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Chromium		Mexico: TWA 0.5 mg/m ³
Quartz		Mexico: TWA= 0.1 mg/m ³
Ci 77491		Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³
Titanium dioxide		Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³
Butyl acrylate		Mexico: TWA 10 ppm Mexico: TWA 55 mg/m ³
Methyl Methacrylate		Mexico: TWA 100 ppm Mexico: TWA 410 mg/m ³ Mexico: STEL 125 ppm Mexico: STEL 510 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid
D2A Very toxic materials
D2B Toxic materials



Canadian National Pollutant Release Inventory (NPRI)

Chemical Name	NPRI
Chromium	X
Butyl acrylate	X

16. OTHER INFORMATION

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 16-May-2011

Revision Date 23-Aug-2011

Revision Note (M)SDS sections updated. 14.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

End of Safety Data Sheet