

SAFETY DATA SHEET



Date Issued : 6/3/2009
MSDS No : 6410
Date-Revised : 12/11/2014
Revision No : 2

DT-5 LACQUER THINNER

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DT-5 LACQUER THINNER

PRODUCT CODE: 6410,6411

MANUFACTURER

Tarr Acquisition, LLC
 4115 W. Turney Ave.
 Phoenix, AZ 85019
Product Stewardship: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Flammable Liquids, Category 1B
 Acute Toxicity (Oral)

GHS LABEL



Health
hazard



Flame



Skull and
crossbones

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H304: May be fatal if swallowed and enters airways.
 H226: Flammable liquid and vapour.
 H301: Toxic if swallowed.

PRECAUTIONARY STATEMENT(S)

Prevention:

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
 P311: Call a POISON CENTER or doctor/physician.
 P270: Do not eat, drink or smoke when using this product.
 P262: Do not get in eyes, on skin, or on clothing.
 P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 P102: Keep out of reach of children.

DT-5 LACQUER THINNER**EMERGENCY OVERVIEW**

IMMEDIATE CONCERNS: DANGER! Poison. Flammable. Contains methanol. Cannot be made non-poisonous. Liquid and vapor harmful. May be fatal or cause blindness if swallowed. Avoid prolonged breathing of vapors. Avoid contact with eyes and skin. Use only in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: POISONOUS. May be fatal or cause blindness if swallowed. Ingestion may have a narcotic effect including signs of CNS depression such as dizziness, headache, drowsiness, loss of coordination, and fatigue.

INHALATION: Excessive exposure to this product may cause headache, CNS depression, drowsiness, dizziness, loss of appetite, irritation of the respiratory tract, drunkenness, unconsciousness, or death.

MEDICAL CONDITIONS AGGRAVATED: Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

COMMENTS HEALTH: Can cause optic nerve damage (blindness).

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Methanol	47 - 50	67-56-1
Toluene	35 - 39	108-88-3
Benzene	< 0.1	71-43-2
Acetone	5 - 9	67-64-1
n-Heptane	5 - 7	142-82-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention.

SKIN: Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

INGESTION: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea.

5. FIRE FIGHTING MEASURES

DT-5 LACQUER THINNER

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

DT-5 LACQUER THINNER**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Methanol	TWA	200	260	200	262
	STEL			250	328
Toluene	TWA	200		50 ^[2]	188 ^[2]
	STEL	300 ^[1]	^[1]		
Benzene	TWA	1 % ^[3]	^[3]	0.5 %	
	STEL	5		2.5	
Acetone	TWA	1000	2400	500	
	STEL			750	
n-Heptane	TWA	500 %	2000	400 %	
	STEL			500	

OSHA TABLE COMMENTS:

1. C = Ceiling
2. S = Skin
3. Carcinogen

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

DT-5 LACQUER THINNER**PHYSICAL STATE:** Liquid**ODOR:** Pungent odor.**COLOR:** Clear, colorless liquid.**pH:** NA = Not Applicable**PERCENT VOLATILE:** 100**FLASHPOINT AND METHOD:** < (20°F) to (52°F)**FLAMMABLE LIMITS:** 0.01 to 0.36**AUTOIGNITION TEMPERATURE:** (867°F) to (896°F)**VAPOR PRESSURE:** Not Determined. However estimated boiling points for major constituents would typically be >212 deg F (Mackam 2CSF) to 394 deg F (Solvent Naphtha) and possibly higher because of the high boiling point of the NP9.**VAPOR DENSITY:** Heavier than air.**BOILING POINT:** (133°F) to (232°F)**FREEZING POINT:** Not Determined. However estimated boiling points for major constituents would typically be >212 deg F (Mackam 2CSF) to 394 deg F (Solvent Naphtha) and possibly higher because of the high boiling point of the NP9.**SOLUBILITY IN WATER:** Negligible**EVAPORATION RATE:** Slower than ether.**DENSITY:** 6.790**SPECIFIC GRAVITY:** 0.815 to 0.816**(VOC):** 5.946 LBS./gal.**10. STABILITY AND REACTIVITY****STABLE:** Yes**POLYMERIZATION:** Avoid heat, flame, and other sources of ignition.**CONDITIONS TO AVOID:** Avoid strong alkalies and oxidizing agents.**HAZARDOUS DECOMPOSITION PRODUCTS:** May form carbon dioxide, carbon monoxide, various hydrocarbons.**11. TOXICOLOGICAL INFORMATION****ACUTE**

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Benzene	636 mg/kg (Rat)	> 14000 mg/kg (Rabbit)	□ 4000 (NINHL rat)
Acetone	5800 mg/kg (Rat)		

DERMAL LD₅₀: > 14000 mg/kg (rabbit)

DT-5 LACQUER THINNER

Notes: LD50 is for Benzene. This product may contain benzene (CAS 71-43-2) at a concentration less than 300 ppm.

ORAL LD₅₀: 636 mg/kg (rat)

Notes: LD50 is for Toluene. LD50 for Benzene is 5,000 mg/kg (rat). This product may contain benzene (CAS 71-43-2) at a concentration less than 300 ppm.

INHALATION LC₅₀: 4000 (NINHL rat)

Notes: LC50 is for Benzene. This product may contain benzene (CAS 71-43-2) at a concentration less than 300 ppm.

EYE EFFECTS: Poison. May be fatal or cause blindness, if swallowed. Cannot be made nonpoisonous.

SENSITIZATION: While there is no evidence that industrially acceptable levels of toluene vapors (e.g., the TLV) have produced cardiac effects in humans, animal studies have shown that inhalation of high levels of toluene produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms. This latter effect was shown to be enhanced by hypoxia or the injection of adrenalinlike agents. Prolonged and repeated exposures to high concentrations of toluene have resulted in hearing loss in laboratory rats. While the effect of solvents on the human auditory system is uncertain, solvent abusers exposed to high doses of toluene show signs of hearing loss, and occupational exposure to toluene may interact with noise in causing hearing loss in the work environment. The effects of solvents on human hearing are uncertain. Solvent abusers and noise interaction with toluene in the work environment may cause signs of hearing loss.

MUTAGENICITY: Toluene is not known to be mutagenic or carcinogenic. However, the available human and experimental data are limited and insufficient to assess carcinogenic potential. Toluene is not listed as a carcinogen by NTP, IARC, or OSHA. Intentional abuse of toluene vapors has been linked to damage of brain, liver, kidney and to death. Many case studies involving abuse during pregnancy clearly indicate that toluene is a developmental toxicant. Developmental toxic effects comparable to those observed in humans have been seen in lab animals but the effects were generally associated with maternal toxicity.

COMMENTS: Poison. May be fatal or cause blindness, if swallowed. Cannot be made nonpoisonous.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

DT-5 LACQUER THINNER**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** Flammable Liquids, Toxic, N.O.S. (Toluene, Methanol)**PRIMARY HAZARD CLASS/DIVISION:** 3**UN/NA NUMBER:** UN 1993**PACKING GROUP:** II**NAERG:** 128**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 5,000 LBS. for Methanol, 1,000 LBS. for Toluene which are a percentage of this product.**LABEL:** Flammable liquid**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**Flammable
LiquidSkull and
crossbones**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes**313 REPORTABLE INGREDIENTS:** Methyl Alcohol (CAS 67-56-1), Toluene (CAS 108-88-3), Benzene (CAS 71-43-2)**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA RQ:** Component RQ lbs


Methyl Alcohol = 5000 lbs

Toluene = 1000 lbs

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following chemicals known to the State of California to cause cancer and reproductive toxicity: Benzene, Toluene**GENERAL COMMENTS:** The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.**16. OTHER INFORMATION****REASON FOR ISSUE:** Updated SDS information and changed to new format.

DT-5 LACQUER THINNER**PREPARED BY:** Compliance Dept.**REVISION SUMMARY:** This MSDS replaces the 1/5/2010 MSDS. Revised: **Section 1:** REASON FOR ISSUE. **Section 2:** . **Section 16:** NFPA CODES (HEALTH, REACTIVITY, NFPA STORAGE CLASSIFICATION).**HMIS RATING**

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		H

NFPA CODES**NFPA STORAGE CLASSIFICATION:** These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.**HMIS RATINGS NOTES:** The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered. Personal protection rating to be supplied by user depending on use conditions.**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.