

MATERIAL SAFETY DATA SHEET



Date Issued: 11/12/2010
MSDS No: 36

A-190

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: A-190

GENERAL USE: Authorized uses are listed in 27 CFR 20.112.

PRODUCT CODE: 36, 37, 37NR, 38, 955

ALTERNATE TRADE NAME(S): TARSOL D2-190

MANUFACTURER

Tarr Acquisition, LLC
4115 W. Turney Ave.
Phoenix, AZ 85019

Service Number: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Poison. Flammable. Contains methanol. Cannot be made non-poisonous. Liquid and vapor harmful. May be fatal or cause blindness if swallowed. Avoid prolonged breathing of vapors. Avoid contact with eyes and skin. Use only in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

SKIN: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: POISONOUS. May be fatal or cause blindness if swallowed. Ingestion may have a narcotic effect including signs of CNS depression such as dizziness, headache, drowsiness, loss of coordination, and fatigue.

INHALATION: May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. Excessive exposure to this product may cause headache, CNS depression, drowsiness, dizziness, loss of appetite, irritation of the respiratory tract, drunkenness, unconsciousness, or death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea. Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis.

MEDICAL CONDITIONS AGGRAVATED: Preexisting diseases in or history of ailments involving

skin, central nervous system, liver and kidney.

TARGET ORGAN STATEMENT: This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain.

COMMENTS HEALTH: Laboratory studies have shown that harmful by inhalation and if swallowed. Possible risks of irreversible effects.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS
Ethanol	71 - 81	64-17-5	200-578-6
Methanol	12 - 22	67-56-1	200-659-6
Methyl isobutyl ketone	0.5 - 3	108-10-1	
Water	1 - 6	7732-18-5	231-791-2

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Flush skin with water. If irritation occurs, get medical attention.

INGESTION: Call poison control center or get medical help immediately. If patient is conscious and alert, give 8 ounces of water or juice and induce vomiting, keeping patient's head below hips to prevent aspiration of liquid into lungs. Never induce vomiting on an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: < (60°F) TAG CC

FLAMMABLE LIMITS: 0.014 to 0.36

AUTOIGNITION TEMPERATURE: Not Determined

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: Extremely flammable liquid. Vapor accumulation could flash and/or explode if in contact with open flame.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: WARNING. Flammable and Poisonous Liquid. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory

protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)						
Chemical Name	EXPOSURE LIMITS					
	OSHA PEL		ACGIH TLV		SupplierOEL	
ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	
Ethanol	TWA	1000	1900	1000	1884	NL
	STEL					NL
Methanol	TWA	200	260	200	262	
	STEL			250	328	
Methyl isobutyl ketone	TWA	100	410	20	-	
	STEL			75		

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible.

Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Freezing Point (°C)	Auto Ignition (°C)	Solubility in Water	Specific Gravity
Methanol	52					
Methyl isobutyl ketone	60	115.8	-85	460	Moderate in water.	0.804

PHYSICAL STATE: Liquid

ODOR: Mild odor.

COLOR: Clear, colorless liquid.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

VAPOR PRESSURE: 39 mm Hg at 20°C

VAPOR DENSITY: Heavier than air.

BOILING POINT: (148°F) to (242°F)

FREEZING POINT: NDA = no data available.

MELTING POINT: No data available.

FLASHPOINT AND METHOD: < (60°F) TAG CC

SOLUBILITY IN WATER: Soluble

EVAPORATION RATE: Slower than Butyl Acetate.

DENSITY: 6.69 - 6.79

10. STABILITY AND REACTIVITY

STABLE: Yes

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

INCOMPATIBLE MATERIALS: This product is incompatible with strong acids or bases, oxidizers, alkali metals, and halogens.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Chemical Name	IARC Status
Ethanol	1

REPRODUCTIVE EFFECTS: This product contains ethanol. Alcoholic beverage consumption has been associated with birth defects in humans. The relevance of this finding to ethanol exposure in industrial environments is uncertain.

TARGET ORGANS: This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain. Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TERATOGENIC EFFECTS: No evidence of teratogenicity was noted following inhalation exposure of pregnant rats by airborne concentrations of up to 16,000 ppm of ethyl alcohol for 7 hours on days 1 through 19 of gestation.

GENERAL COMMENTS: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

COMMENTS: Poison. May be fatal or cause blindness, if swallowed. Cannot be made nonpoisonous.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Ethyl alcohol solutions

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1170

PACKING GROUP: II

NAERG: 127

LABEL: Flammable liquid

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable Liquid



Skull and crossbones

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes

CHRONIC: Yes

313 REPORTABLE INGREDIENTS: Methyl Isobutyl Ketone (CAS 108-10-1)

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Methanol	12 - 22	67-56-1
Methyl isobutyl ketone	0.5 - 3	108-10-1

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, none of the chemicals in this product are listed as an extremely hazardous substance under Section 302 of SARA Title III nor does this product contain any other such substances.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Methanol	12 - 22	5,000
Methyl isobutyl ketone	0.5 - 3	5,000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Methanol	67-56-1
Methyl isobutyl ketone	108-10-1
Water	7732-18-5

TSCA REGULATORY: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

REASON FOR ISSUE: Updated MSDS information and changed to new format.

PREPARED BY: Compliance Dept.

REVISION SUMMARY: New MSDS

HMIS RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	H

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered.

ADDITIONAL MSDS INFORMATION: Last revision 12/26/2003.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.