# **MATERIAL SAFETY DATA SHEET**

## CB 124A

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER:	Tarr, Inc.	
	4115 W. Turney Avenue	Portland, Oregon
		Phoenix, Arizona
	Phoenix, AZ 85019	Auburn, Washington
<b>INFORMATION PHONE:</b>	(602) 233-2000	Vancouver, Washington
EMERGENCY PHONE:	CHEMTREC 800-424-9300 (US) Day or night International Call Collect CHEMTREC 202-483-7616	<b>Print Date:</b> 10/28/2004
<b>PRODUCT NAME:</b>	CB 124A	
<b>PRODUCT NUMBER:</b>	CB124A	
UPC NUMBER:		
PREPARED BY:	Patricia Rodabaugh	
DATE PREPARED:	6/15/2000	
LAST REVISION:	7/31/1996	
SYNONYMS:	Solvent blend	
COMPOSITION/INFO	DMATION ON INCOEDIENTS	



Chemical Name	CAS # W	eight %	OSHA PEL	ACGIH TLV	NOTE
Solvent naphtha, light aliphatic	64742-89-8	65-75	300 ppm	300 ppm	
n-Butanol	71-36-3	10-20	50 ppm	50 ppm	
n-Propyl acetate	109-60-4	10-20	200 ppm	200 ppm	

## **3. HAZARDOUS IDENTIFICATION**

EMERGENCY OVERVIEW: DANGER! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

## POTENTIAL HEALTH EFFECTS

EYE CONTACT:	Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating.
INHALATION:	Vapors may be irritating to the nose, throat, and respiratory tract. High vapor concentrations may cause central nervous system (CNS) depression.
INGESTION:	Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspir. pneumontis.
SKIN CONTACT:	Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

#### SIGNS AND SYMPTOMS OF EXPOSURE:

Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing an cyanosis.

## 4. FIRST AID MEASURES

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation persists, get medical attention.

**INHALATION:** Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

# **INGESTION:** Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

#### AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impared function from preexisiting disorders may be aggravated by exposure to this product.

#### SUPPLEMENTAL HEALTH INFORMATION:

Near fatal exposures may result in congestive effects to a wide variety of organs.

## **5. FIRE FIGHTING MEASURES**

#### FLAMMABLE PROPERTIES

FLASH POINT: 55 F	FLASH POINT	METHO	D USED:	Tag Closed Cup
AUTOIGNITION: N/A	LEL:	0.01	UEL:	0.112

#### **EXTINGUISHING MEDIA:**

Use water fog, "alcohol" foam, dry chemical, or CO2.

#### SPECIAL FIRE FIGHTING PROCEDURES:

WARNING. Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

#### **COMBUSTION PRODUCTS:**

Carbon monoxide and unidentified organic compounds may be formed during combustion.

## 6. ACCIDENTAL RELEASE MEASURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

## 7. HANLDING AND STORAGE

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

#### **OTHER PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

#### **RESPIRATORY PROTECTION:**

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respir. of an air-purifying respir. for organic vapors.

#### **VENTILATION:**

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

#### **PROTECTIVE GLOVES:**

Test data indicate the best protection is provided by neoprene, nitrile, and natural rubber gloves.

#### **EYE PROTECTION:**

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

#### WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

#### **ENGINEERING CONTROLS:**

Facilities storing or utilizing this material should be equipped with and eyewash facility and a safety shower.

#### **EXPOSURE GUIDELINES:**

May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventillation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**SOLUBILITY IN WATER:** Complete solubility with most hydrocarbon solvents, partial solubility with water.

APPEARANCE AND ODOR: Clear, colorless liquid with pungent odor.

<b>BOILING POINT:</b>	215-247	PERCENT VOLATILE:	100
VAPOR PRESSURE:	4.1 - 25	PH:	N/A
<b>EVAPORATION RATE:</b>	Slower than ether	<b>MOLECULAR WEIGHT:</b>	
POUNDS PER GALLON:	6.49	VAPOR DENSITY:	Heavier than air
SPECIFIC GRAVITY:	0.77	<b>OTHER PROPERTIES:</b>	
<b>MELTING POINT:</b>	NDA		

FREEZING POINT:

## **10. STABILITY AND REACTIVITY**

**STABILITY:** Stable

CONDITIONS TO AVOID: Stable under normal conditions.

#### **INCOMPATIBILITY:**

Strong oxidizers.

#### HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

#### HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition.

## **11. TOXICOLOGY INFORMATION**

Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervouus system damage.

## **12. ECOLOGICAL INFORMATION**

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

## **13. DISPOSAL CONSIDERATIONS**

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

## 14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name:	Flammable liquids, n.o.s. (naphtha, butanol)	PACKING GROUP: GUIDE NUMBER:	II 128
HAZARD CLASS: UN NUMBER:	3 UN 1993	DOT CLASS:	Flammable liquid

## **15. REGULATORY INFORMATION**

This product is a mixture and each component is listed in the TSCA Inventory of Chemical Substances.

## **16. OTHER INFORMATON**

HMIS INFORMATION:	HEALTH: 2	FLAMMABILITY: 3	<b>REACTIVITY:</b> 0	PROTECTIVE: G
SARA Title III Information:				
SARA 302:				
SARA 311/312:				
SARA 313:	Under Section 313	this product should be reported		

N/A = Not Applicable NDA = No Data Available

#### Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr, Incorporated makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Tarr, Inc. assumes no responsibility for injuries from the use of the product described herein.