

MATERIAL SAFETY DATA SHEET



Date Issued: 01/19/2012
MSDS No: 6232
Date-Revised: 02/11/2012
Revision No: 1

TAX PAID ETHANOL 30 PROOF

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TAX PAID ETHANOL 30 PROOF

PRODUCT CODE: 6232

ALTERNATE TRADE NAME(S): 15% ETHANOL

MANUFACTURER

Tarr Acquisition, LLC

4115 W. Turney Ave.

Phoenix, AZ 85019

Service Number: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300

CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Combustible liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is mildly irritating to the eyes. High vapor concentrations may also be irritating.

SKIN: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (headache, drowsiness, dizziness, loss of coordination and fatigue).

INHALATION: May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea.

MEDICAL CONDITIONS AGGRAVATED: Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

3. COMPOSITION / INFORMATION ON INGREDIENTS

TAX PAID ETHANOL 30 PROOF

Chemical Name	Wt. %	CAS	EINECS
Ethanol	12 - 16	64-17-5	200-578-6
Water	84 - 88	7732-18-5	231-791-2

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

INGESTION: Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (53°F) Lowest flash of chemical constituents within product.

FLAMMABLE LIMITS: 0.033 to 0.19

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Combustible Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: WARNING. Combustible. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

TAX PAID ETHANOL 30 PROOF**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
Ethanol	TWA	1000	1900	1000	1884	NL	NL
	STEL					NL	NL

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Alcohol odor.

COLOR: Clear, colorless liquid.

pH: NA = Not Applicable

PERCENT VOLATILE: 15

VAPOR PRESSURE: mm Hg at (68°F)

VAPOR DENSITY: Heavier than air.

BOILING POINT: (173°F) to (192°F)

FREEZING POINT: NDA = no data available.

MELTING POINT: (20°F)

FLASHPOINT AND METHOD: (53°F) Lowest flash of chemical constituents within product.

TAX PAID ETHANOL 30 PROOF**SOLUBILITY IN WATER:** Complete.**EVAPORATION RATE:** Slower than ether.**DENSITY:** 8.064**Notes:** LBS./gallon**SPECIFIC GRAVITY:** 0.940 to 0.99**10. STABILITY AND REACTIVITY****STABLE:** Yes**POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.**INCOMPATIBLE MATERIALS:** Strong oxidizers.**11. TOXICOLOGICAL INFORMATION****CARCINOGENICITY**

Chemical Name	IARC Status
Ethanol	1

TARGET ORGANS: This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain.**12. ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION:** Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.**EMPTY CONTAINER:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.**14. TRANSPORT INFORMATION**

TAX PAID ETHANOL 30 PROOF**DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** Ethanol Solutions**PRIMARY HAZARD CLASS/DIVISION:** Combustible liquid**UN/NA NUMBER:** UN 1170**PACKING GROUP:** III**NAERG:** 127**OTHER SHIPPING INFORMATION:** USDOT combustible exception: 173.150(f)(1).**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes**313 REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.**302/304 EMERGENCY PLANNING****EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Water	7732-18-5

TSCA STATUS: Listed.**GENERAL COMMENTS:** The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.**16. OTHER INFORMATION****PREPARED BY:** COMPLIANCE DEPT.**REVISION SUMMARY:** This MSDS replaces the 01/20/2012 MSDS.**HMIS RATING**

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	☒

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered.

TAX PAID ETHANOL 30 PROOF

Personal protection rating to be supplied by user depending on use conditions.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.