

MATERIAL SAFETY DATA SHEET

ADHESIVE CLEANER

Tarr

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Tarr, Incorporated
P.O. Box 12570
Portland, OR 97212

INFORMATION PHONE: (503) 288-5294

EMERGENCY PHONE: CHEMTREC 800-242-9300 (US) Day or night
International Call Collect CHEMTREC 202-483-7616

PRODUCT NAME: ADHESIVE CLEANER

PRODUCT NUMBER: AC

UPC NUMBER:

PREPARED BY Patricia Rodabaugh

DATE PREPARED: 12/16/2002

LAST REVISION: 8/27/1999

SYNONYMS: Aromatic hydrocarbons

Portland, Oregon
Phoenix, Arizona
Auburn, Washington
Vancouver, Washington

Print Date: 12/16/2002

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	Weight %	OSHA PEL	ACGIH TLV
Solvent naphtha, light aliphatic	64742-89-8	75-85	300 ppm	300 ppm
Xylenes	1330-20-7	15-25	100 ppm	100 ppm
Toluene	108-88-3	<0.4	100 ppm	50 ppm (skin)
Ethyl benzene	100-41-4	4-5	100 ppm	50 ppm (skin)

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECT

EYE CONTACT: Material may cause eye irritation. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. High vapor concentrations may cause central nervous system (CNS) depression.

INGESTION: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspir. pneumonitis.

SKIN CONTACT: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SIGNS AND SYMPTOMS OF EXPOSURE:

Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). In severe cases death may result.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be

administered by qualified personnel. Get medical attention immediately.

INGESTION: DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

SKIN CONTACT: Wash affected area with soap and water. If irritation occurs, get medical attention.

AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impaired function from preexisting disorders may be aggravated by exposure to this product. Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

SUPPLEMENTAL HEALTH INFORMATION:

*Note to physician: If more than 2.0 ml per kg has been ingested and vomiting has not occurred, emesis should be induced with supervision. Keep victim's head below hips to prevent aspiration.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 50 deg. F

FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NDA

LEL: 0.01 **UEL:** 0.07

EXTINGUISHING MEDIA:

Use water fog, "alcohol" foam, dry chemical, or CO₂.

SPECIAL FIRE FIGHTING PROCEDURES:

WARNING. Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

COMBUSTION PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respir. or an air-purifying respir. for organic vapors.

VENTILATION:

Controlling airborne concentration below the ACGIH TLV exposure guideline is recommended. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PROTECTIVE GLOVES:

Test data indicate the best protection is provided by neoprene, and natural rubber gloves.

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

ENGINEERING CONTROLS:

Facilities storing or utilizing this material should be equipped with and eyewash facility and a safety shower.

EXPOSURE GUIDELINES:

May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUBILITY IN WATER: Complete solubility with most hydrocarbon solvents, partial solubility with water.

APPEARANCE AND ODOR: Clear, water-white liquid with characteristic odor.

BOILING POINT:	201 - 286F	PERCENT VOLATILE:	100
VAPOR PRESSURE:	6.0 - 6.6	PH:	N/A
EVAPORATION RATE:	Slower than ether	MOLECULAR WEIGHT:	NDA
POUNDS PER GALLON:	6.11	VAPOR DENSITY:	Lighter than air
SPECIFIC GRAVITY:	0.739 - 0.789	OTHER PROPERTIES:	
MELTING POINT:	NDA		
FREEZING POINT:	NDA		

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Stable under normal conditions.

INCOMPATIBILITY:

Strong acids or bases, oxidizers, alkali metals and halogens.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition.

11. TOXICOLOGY INFORMATION

This product may contain benzene (CAS No. 71-43-2) at a concentration less than 10 ppm.

12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

3. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORTATION INFORMATION

DOT CLASS:	Flammable liquid	PACKING GROUP:	II
HAZARD CLASS:	3	GUIDE NUMBER:	128
UN NUMBER:	UN 1993	PROPER SHIPPING NAME:	Flammable liquids, n.o.s. (Naphtha, Xylene)

15. REGULATORY INFORMATION

All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

16. OTHER INFORMATION

HMIS INFORMATION: **HEALTH:** 2 **FLAMMABILITY:** 3 **REACTIVITY:** 0 **PROTECTIVE:** H

SARA Title III Information:

SARA 302: To the best of our knowledge, none of the chemicals in this product are listed as an Extremely Hazardous Substance under Section 302 of SARA Title III nor does this product contain any other such substances.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313: Xylene (CAS 1330-20-7), toluene (108-88-3), and ethyl benzene (100-41-4)

This product contains the following chemicals known to the State of California to cause cancer & reproductive toxicity: Benzene, Toluene

Xylene is not listed as a carcinogen by NTP, IARC, or OSHA.

A chronic feeding study in rats with ethyl benzene caused cancer (increase in total malignant tumors). Developmental toxicity studies in rats with ethyl benzene showed evidence of skeletal and other malformations at maternally toxic doses; similar effects were not seen in rabbits. Ethyl benzene was not mutagenic in: Ames test, yeast, drosophila, sister chromatic exchange with cultured human lymphocytes cells and in vitro cytogenetics assay with CHO cells.

Toluene is not known to be mutagenic or carcinogenic. However, the available human and experimental data are limited and insufficient to assess carcinogenic potential. Toluene is not listed as a carcinogen by NTP, IARC, or OSHA. Intentional abuse of toluene vapors has been linked to damage of brain, liver, kidney and to death. Many case studies involving abuse during pregnancy clearly indicate that toluene is a developmental toxicant. Developmental toxic effects comparable to those observed in humans have been seen in lab animals but the effects were generally associated with maternal toxicity. While there is no evidence that industrially acceptable levels of toluene vapors (e.g., the TLV) have produced cardiac effects in humans, animal studies have shown that inhalation of high levels of toluene produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms. This latter effect was shown to be enhanced by hypoxia or the injection of adrenalinlike agents.

N/A = Not Applicable

NDA = No Data Available

Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr, Incorporated makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Tarr, Inc. assumes no responsibility for injuries from the use of the product described herein.