

SAFETY DATA SHEET



Date Issued : 5/15/2014
MSDS No : 1484

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

MANUFACTURER

Tarr Acquisition, LLC
4115 W. Turney Ave.
Phoenix, AZ 85019

Product Stewardship: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Flammable Liquids, Category 1B

GHS LABEL



Flame

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H224: Extremely flammable liquid and vapour.

PRECAUTIONARY STATEMENT(S)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Extremely flammable liquid and vapor.

POTENTIAL HEALTH EFFECTS

EYES: Can cause mild eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

SKIN: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

INGESTION: Swallowing small amounts of this material during normal handling operations is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

INHALATION: Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. symptoms usually occur at air concentrations higher than the recommended exposure limits.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing disorders of the following organ(s) or organ system(s) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), central nervous system, nervous system, male reproductive system.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Hexane	68 - 72	110-54-3
IPA	28 - 32	67-63-0

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Immediately wash skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Target Organ Effects: Prolonged and repeated exposure to n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of the arms and legs) and result in muscular weakness and loss of sensation. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, nasal damage, nervous system damage, testis damage, lung damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: visual impairment, central nervous system effects.

NOTES TO PHYSICIAN: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in person exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. See Aggravated Medical Conditions.

5. FIRE FIGHTING MEASURES

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

EXTINGUISHING MEDIA: Use regular foam, dry chemical, or carbon dioxide (CO₂).

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

FIRE FIGHTING PROCEDURES: Clear fire area of unprotected personnel. Fire fighters should wear self contained breathing apparatus. Water spray may be ineffective in fighting the fire but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot burning liquid. Wear a self contained breathing apparatus with full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemicals resistant personal protective equipment. Refer to the personal protective equipment section of this SDS.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Extremely Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Keep away from heat, sparks, and flame. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignition without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operation conditions. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS**EXPOSURE GUIDELINES****OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)**

Chemical Name		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Hexane	TWA	500 ^[1]	1800 ^[1]	50	180	NL	NL
	STEL					NL	NL
IPA	TWA	400	980	200	490	NL ^[1]	NL ^[1]
	STEL			400	960	NL	NL

OSHA TABLE COMMENTS:

1. NL = Not Listed

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Hydrocarbon.

COLOR: Clear, colorless liquid.

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: (-10°F) Flash Point is an estimate based on Hexane component.

FLAMMABLE LIMITS: 1.0% to 7.5%

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

VAPOR PRESSURE: ~ 102 mm Hg at 20°C

Notes: Calculated based on components.

VAPOR DENSITY: Heavier than air.

BOILING POINT: (149°F) to (180°F)

FREEZING POINT: (0°F)

MELTING POINT: No data available.

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE: Slower than ether.

DENSITY: 5.95

SPECIFIC GRAVITY: 0.714 to 0.715 at (60°F)

(VOC): ~ 5.950 LBS./gal.

10. STABILITY AND REACTIVITY

STABILITY: Avoid heat, flame, and other sources of ignition.

POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Notes: Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by IARC, NTP, or OSHA.

TARGET ORGANS: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

GENERAL COMMENTS: Developmental Information: This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Flammable Liquids, N.O.S. (Hexane, Isopropanol)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1993

PACKING GROUP: II

NAERG: 128

REPORTABLE QUANTITY (RQ) UNDER CERCLA: 5,000 lbs.

LABEL: Flammable liquid

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable

Liquid

R11: Highly flammable.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: n-hexane (CAS 110-54-3)

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA RQ: 5,000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: Listed.

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California

SUNRISE NON-CHLORINATED BRAKE CLEANER PLUS

Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the State of California to cause cancer.: Benzene.

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the State of California to cause reproductive harm.: Benzene.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable
Liquid

R7: May cause fire.


16. OTHER INFORMATION

PREPARED BY: COMPLIANCE

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	H

NFPA CODES



NFPA STORAGE CLASSIFICATION: These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.