

MATERIAL SAFETY DATA SHEET



Date Issued: 07/06/2009

MSDS No: 40391

SDA 23A 190 proof

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SDA 23A 190 proof

PRODUCT CODE: 40391

MANUFACTURER

Tarr Acquisition, LLC

4115 W. Turney Ave.

Phoenix AZ 85019

Service Number: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300

CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECTS

EYES: May cause moderate irritation, including burning sensation, tearing, redness or swelling.

SKIN: Liquid is mildly irritating to the skin. May cause a burning sensation, redness and/or swelling. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Liquid is moderately toxic and may be harmful if swallowed; may product CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

INHALATION: Prolonged overexposure to either vapor or mist may cause coughing, shortness of breath, dizziness and drunkenness. High vapor concentrations may cause drowsiness and irritation or produce central nervous system (CNS) depression.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), pain in the abdomen, blood abnormalities (breakage of red blood cells), kidney damage and death. Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea.

CHRONIC EFFECTS: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Not listed as a carcinogen by the NTP, IARC, or OSHA.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing disorders or diseases of the eye. This material may affect mucous tissue and/or aggravate mucous membrane dysfunction.

ROUTES OF ENTRY: Inhalation, skin absorption, skin contact, eye contact.

TARGET ORGAN STATEMENT: This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain.

COMMENTS HEALTH: Can cause optic nerve damage (blindness).

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Ethanol	85 - 95	64-17-5
Acetone	5 - 10	67-64-1
Water	3 - 8	7732-18-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

INGESTION: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (1°F) Lowest flash of chemical constituents within product.

FLAMMABLE LIMITS: 0.026 to 0.19

AUTOIGNITION TEMPERATURE: Not Determined

EXTINGUISHING MEDIA: Use "alcohol resistant" foam, dry chemical, or CO₂. Water may be ineffective, but water applied as a spray can absorb some of the fire's heat and should be used to keep fire-exposed containers cool.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, releases flammable vapors. When mixed

with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapor source. Fine sprays/mists may be combustible at temperatures below normal flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

FIRE FIGHTING EQUIPMENT: None identified.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep material out of storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

HANDLING: None identified.

STORAGE: None identified.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Ethanol	TWA	1000	1900	1000	1884	NL	NL
	STEL					NL	NL
Acetone	TWA	1000	2400	500			
	STEL			750			

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible.

Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If overexposure has been determined or documented, a NIOSH/MSHA jointly approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier.) Engineering or administrative controls should be implemented to reduce exposure.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Alcohol odor.

APPEARANCE: Colorless, mobile liquid.

COLOR: Clear, colorless liquid.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

VAPOR PRESSURE: 44-180 mmHg

VAPOR DENSITY: Heavier than air.

BOILING POINT: (133°F) to (173°F)

FREEZING POINT: NDA = no data available.

MELTING POINT: No data available.

FLASHPOINT AND METHOD: (1°F) Lowest flash of chemical constituents within product.

SOLUBILITY IN WATER: Appreciable (10 percent or more)

EVAPORATION RATE: Slower than ether.

DENSITY: 6.67

SPECIFIC GRAVITY: 0.770 to 0.81

(VOC): 6.374 lbs./gal.

Notes: None identified.

10. STABILITY AND REACTIVITY

STABLE: Yes

STABILITY: None identified.

POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon monoxide and carbon dioxide.

INCOMPATIBLE MATERIALS: This product is incompatible with strong acids or bases, oxidizers, alkali metals, and halogens.

11. TOXICOLOGICAL INFORMATION

ACUTE

INHALATION LC₅₀: None identified.

CHRONIC: None identified.

CARCINOGENICITY

Notes: None identified.

REPRODUCTIVE EFFECTS: None identified.

TARGET ORGANS: This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain.

TERATOGENIC EFFECTS: None identified.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Ethyl alcohol solutions

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1170

PACKING GROUP: II

NAERG: 127

LABEL: Flammable liquid

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

Flammable Liquid

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes
CHRONIC: Yes

313 REPORTABLE INGREDIENTS: To the best of our knowledge, this product is not listed as a toxic chemical.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

PREPARED BY: Compliance Dept.

REVISION SUMMARY: New MSDS

HMIS RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	H

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.