

# SAFETY DATA SHEET

New SDS.



Date Issued : 7/10/2013

MSDS No : 8026

## Solvent Blend

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Solvent Blend**PRODUCT CODE:** 8026**MANUFACTURER**

Tarr, LLC

P.O. Box 12570

Portland, OR 97212

**Service Number:** 503-288-5294**24 HR. EMERGENCY TELEPHONE NUMBERS****CHEMTREC (US Transportation) :**(800) 424 - 9300**CANUTEC (Canadian Transportation) :**(613) 996 - 6666

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Environmental**

Flammable Liquids, Category 2

**GHS LABEL**

Flame

DANGER

H225: Highly flammable liquid and vapour.

**EMERGENCY OVERVIEW**

**IMMEDIATE CONCERNS:** WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May cause central nervous system depression. May be irritating to eyes and skin.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Moderately irritating to the eyes.

**SKIN:** Mildly irritating to the skin.

**INGESTION:** Irritating to the gastrointestinal tract, causing abdominal pain and vomiting, sometimes bloody. Ingestion may cause CNS depression, low blood pressure, rapid heart beat and liver damage.

**INHALATION:** May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

## Solvent Blend

**ACUTE TOXICITY:** Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

**MEDICAL CONDITIONS AGGRAVATED:** Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS	EINECS
Isopropyl Alcohol	63 - 73	67-63-0	200-661-0
Acetone	10 - 20	67-64-1	200-662-2
Methanol	10 - 20	67-56-1	200-659-6
Toluene	0 - 0.5	108-88-3	203-625-9
Water	0 - 1	7732-18-5	231-791-2

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

**SKIN:** Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

**INGESTION:** Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Class IB flammable liquid.

**EXTINGUISHING MEDIA:** Use water fog, "alcohol" foam, dry chemical, or CO<sub>2</sub>.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

**FIRE FIGHTING PROCEDURES:** WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

### 6. ACCIDENTAL RELEASE MEASURES

#### ENVIRONMENTAL PRECAUTIONS

## Solvent Blend

**WATER SPILL:** Keep material out of storm sewers and ditches which lead to waterways.

**GENERAL PROCEDURES:** WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**COMMENTS:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Isopropyl Alcohol	TWA	400	980	200	490	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	STEL			400	960	NL	NL
Acetone	TWA	1000	2400	500			
	STEL			750			
Methanol	TWA	200	260	200	262		
	STEL			250	328		
Toluene	TWA	200		50 <sup>[3]</sup>	188 <sup>[3]</sup>		
	STEL	300 <sup>[2]</sup>	<sup>[2]</sup>				
<b>OSHA TABLE COMMENTS:</b>							
1. NL = Not Listed							
2. C = Ceiling							
3. S = Skin							

**ENGINEERING CONTROLS:** Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

## Solvent Blend

**SKIN:** Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

**PROTECTIVE CLOTHING:** Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

**WORK HYGIENIC PRACTICES:** Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Solubility in Water	Specific Gravity
Acetone	-17.2	Miscible	0.797
Methanol	52		
Toluene	4.5 TAG CC	0.07% (74 deg. F)	0.87

**PHYSICAL STATE:** Liquid

**ODOR:** Mild odor.

**APPEARANCE:** Clear.

**COLOR:** Water-white.

**pH:** Essentially neutral.

**PERCENT VOLATILE:** 100

**FLASHPOINT AND METHOD:** (-4°F) to (53°F) Closed Cup

**Notes:** Acetone has the lowest flash point of any of the constituents at -4 deg F, Methanol next at 51 deg F, IPA next at 53 deg F and Toluene at 43 deg F. The largest percentage of product is IPA but the lower flash components such as acetone have the largest impact on the flash point. While the flash point will be between -4 deg F and 53 deg F, it will be much closer to the lower temperature than the higher.

**FLAMMABLE LIMITS:** Not determined.

**AUTOIGNITION TEMPERATURE:** Not Determined

**VAPOR DENSITY:** Heavier than air.

**BOILING POINT:** (148°F) to (212°F)

**FREEZING POINT:** NDA = no data available.

**SOLUBILITY IN WATER:** Highly soluble in water.

**EVAPORATION RATE:** Not Determined

## Solvent Blend

**DENSITY:** 6.59 at (60°F)

**SPECIFIC GRAVITY:** 0.7904 @ 60 deg F

**(VOC):** 5.260 LBS./gal.

### 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** No

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

**INCOMPATIBLE MATERIALS:** Strong oxidizers.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)
Acetone	5800 mg/kg (Rat)

#### CARCINOGENICITY

Chemical Name	IARC Status
Toluene	3

**GENERAL COMMENTS:** The methanol component is poisonous. May be fatal or cause blindness if enough swallowed. Cannot be made non-poisonous.

### 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

**EMPTY CONTAINER:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

## Solvent Blend

**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Flammable Liquids, n.o.s. (Isopropanol, Methanol)

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** UN 1993

**PACKING GROUP:** II

**NAERG:** 127

**LABEL:** Flammable liquid

### 15. REGULATORY INFORMATION

#### UNITED STATES

#### DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable Liquid

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**313 REPORTABLE INGREDIENTS:** Toluene (CAS 108-88-3)

#### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Vol. %	CAS
Isopropyl Alcohol	63 - 73	67-63-0
Methanol	10 - 20	67-56-1

#### 302/304 EMERGENCY PLANNING

**EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

#### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**Solvent Blend**

Chemical Name	Vol. %	CERCLA RQ
Acetone	10 - 20	5,000 LBS.
Methanol	10 - 20	5,000
Toluene	0 - 0.5	1,000

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Isopropyl Alcohol	67-63-0
Acetone	67-64-1
Methanol	67-56-1
Toluene	108-88-3
Water	7732-18-5

**TSCA STATUS:** Listed.

**CALIFORNIA PROPOSITION 65**

Chemical Name	Wt. %	Listed
Toluene	0	• Female Reproductive

**GENERAL COMMENTS:** The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.


**16. OTHER INFORMATION**

**REASON FOR ISSUE:** New product.

**PREPARED BY:** Compliance

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<input type="checkbox"/>	<b>G</b>

**NFPA CODES**

**NFPA STORAGE CLASSIFICATION:** These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.