

SAFETY DATA SHEET



Date Issued : 2/6/2013
MSDS No : 1965

PAINTERS SUPPLY LT

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PAINTERS SUPPLY LT

MANUFACTURER

Tarr Acquisition, LLC
4115 W. Turney Ave.
Phoenix, AZ 85019
Service Number: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health

Flammable Liquids

GHS LABEL



Flame

DANGER

H226: Flammable liquid and vapour.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

POTENTIAL HEALTH EFFECTS

EYES: Risk of serious damage to eyes.

SKIN: Irritating to skin. Repeated exposure may cause skin dryness or cracking.

INGESTION: Toxic: Dnager of very serious irreversible effects if swallowed.

INHALATION: Harmful if inhaled.

3. COMPOSITION / INFORMATION ON INGREDIENTS

PAINTERS SUPPLY LT

Chemical Name	Vol. %	CAS	EINECS
VM&P	25 - 35	64742-89-8	265-192-2
Methanol	25 - 35	67-56-1	200-659-6
Acetone	20 - 30	67-64-1	200-662-2
Glycol Ether EB	0 - 5	111-76-2	2039050
Toluene	15 - 25	108-88-3	203-625-9

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Get medical attention.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing. Call a physician if irritation develops. Wash clothing before reuse.

INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (2°F) TAG CC

GENERAL HAZARD: Flammable liquid and vapor.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

LARGE SPILL: Dike around large spills to prevent spreading.

COMMENTS: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Use in well ventilated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PAINTERS SUPPLY LT**EXPOSURE GUIDELINES****OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)**

Chemical Name		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
VM&P	TWA	[1]	[1]			100 [2]	400 [2]
Methanol	TWA	200	260	200	262		
	STEL			250	328		
Acetone	TWA	1000	2400	500			
	STEL			750			
Glycol Ether EB	TWA	50 [3]	240 [3]	20 [4]	97 [4]	NL	NL
	STEL					NL	NL
Toluene	TWA	200		50 [4]	188 [4]		
	STEL	300 [5]	[5]				

OSHA TABLE COMMENTS:

1. Our supplier has adopted, as Interim Standards, the OSHA PELs that were established in 1989 and later rescinded.
2. In the absence of occupational exposure standards for this product, it is recommended that these values are adopted.
3. NL = Not Listed
4. S = Skin
5. C = Ceiling

ENGINEERING CONTROLS: Provide local exhaust ventilation to control vapor/mists.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical goggles/face shield.

SKIN: Impervious gloves such as viton or nitrile should be worn at all times when handling this material. (Consult your safety equipment supplier.) In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec.8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134, when airborne exposure guidelines and/or comfort levels may be exceeded, use an approved air-purifying respirator.

PROTECTIVE CLOTHING: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

PAINTERS SUPPLY LT

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
VM&P	19			Solubility negligible in water.	0.743
Methanol	52				
Acetone				Miscible	0.797
Glycol Ether EB	66	170.5 760 mmHg	-65	Soluble	0.902
Toluene	4.5 TAG CC			0.07% (74 deg. F)	0.87

PHYSICAL STATE: Liquid

ODOR: Ketone odor.

COLOR: Water-white.

PERCENT VOLATILE: 100

VAPOR PRESSURE: 97.7 mm Hg at 20°C

VAPOR DENSITY: 2

BOILING POINT: (133°F) to (342°F)

FLASHPOINT AND METHOD: (2°F) TAG CC

SOLUBILITY IN WATER: Appreciable

DENSITY: 6.652

SPECIFIC GRAVITY: 0.79 to 0.8

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

HAZARDOUS DECOMPOSITION PRODUCTS: May form carbon dioxide, carbon monoxide, various hydrocarbons.

INCOMPATIBLE MATERIALS: Isolate from strong oxidizers such as permanganates, chromates and peroxides.

11. TOXICOLOGICAL INFORMATION

ACUTE

PAINTERS SUPPLY LT

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
VM&P	> 2000 mg/kg (Rat)	> 2000 mg/kg (rat)	> 5000 ppm / 1 hour (rat)
Acetone	5800 mg/kg (Rat)		
Glycol Ether EB	> 500 to 2000 mg/kg (guinea pig)	> 2000	to 0 No deaths at highest tested does./1 hours, guinea pig.

CARCINOGENICITY

Chemical Name	IARC Status
Glycol Ether EB	3
Toluene	3

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of waste material according to local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint Related Material

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: II

NAERG: 128

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable Liquid

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

PAINTERS SUPPLY LT**313 REPORTABLE INGREDIENTS:** Methanol, Toluene, Glycol Ether EB (2-Butoxyethanol)**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Vol. %	CAS
Methanol	25 - 35	67-56-1
Toluene	15 - 25	108-88-3

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Vol. %	CERCLA RQ
Methanol	25 - 35	5,000
Acetone	20 - 30	5,000 LBS.
Toluene	15 - 25	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)


Chemical Name	CAS
VM&P	64742-89-8
Methanol	67-56-1
Acetone	67-64-1
Glycol Ether EB	111-76-2
Toluene	108-88-3

CALIFORNIA PROPOSITION 65

Chemical Name	Vol. %	Listed
Toluene	15 - 25	• Female Reproductive

16. OTHER INFORMATION**REASON FOR ISSUE:** New product.**PREPARED BY:** COMPLIANCE**HMIS RATING**

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES

NFPA STORAGE CLASSIFICATION: These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

PAINTERS SUPPLY LT

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.