

# MATERIAL SAFETY DATA SHEET



Date Issued: 07/14/2006

MSDS No: 4115

Date-Revised: 08/06/2008

Revision No: 1

## UNELKO 200

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** UNELKO 200

**GENERAL USE:** Authorized uses are listed in 27 CFR 20.112.

**PRODUCT CODE:** 4115

#### MANUFACTURER

Tarr Acquisition, LLC  
4115 W. Turney Ave.  
Phoenix, AZ 85019

**Service Number:** 602-233-2000

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation)** : (800) 424 - 9300  
**CANUTEC (Canadian Transportation)** : (613) 996 - 6666

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** **WARNING!** Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May cause central nervous system depression. May be irritating to eyes and skin.

#### POTENTIAL HEALTH EFFECTS

**EYES:** Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

**SKIN:** Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**INGESTION:** Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (headache, drowsiness, dizziness, loss of coordination and fatigue).

**INHALATION:** May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**ACUTE TOXICITY:** Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

**MEDICAL CONDITIONS AGGRAVATED:** Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impaired function from preexisting disorders may be aggravated by exposure to this product.

**TARGET ORGAN STATEMENT:** This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these

findings to ethanol exposure in industrial environments is uncertain.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS
Ethanol	83 - 90	64-17-5	200-578-6
2-Propanol	8 - 14	67-63-0	200-661-0
Methyl isobutyl ketone	0.6 - 1.1	108-10-1	

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

**SKIN:** Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

**INGESTION:** DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** (55°F) to (60°F) TAG CC

**FLAMMABLE LIMITS:** 0.014 to 0.19

**AUTOIGNITION TEMPERATURE:** Not Determined

**EXTINGUISHING MEDIA:** Use water fog, "alcohol" foam, dry chemical, or CO<sub>2</sub>.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

**FIRE FIGHTING PROCEDURES:** WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

### 6. ACCIDENTAL RELEASE MEASURES

**GENERAL PROCEDURES:** WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Keep away from heat, sparks, and flame. Surfaces that are hot may ignite

even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**STORAGE:** Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

**COMMENTS:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)						
		EXPOSURE LIMITS				
		OSHA PEL		ACGIH TLV		SupplierOEL
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm
Ethanol	TWA	1000	1900	1000	1884	NL
	STEL					NL
2-Propanol	TWA	400	980	200	490	NL <sup>[1]</sup>
	STEL			400	960	NL
Methyl isobutyl ketone	TWA	100	410	50		
	STEL			75		

**OSHA TABLE COMMENTS:**

1. NL = Not Listed

**ENGINEERING CONTROLS:** Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Use chemical safety goggles and/or full face shield where splashing is possible.

Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

**SKIN:** Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respirator or an air-purifying respirator for organic vapors.

**PROTECTIVE CLOTHING:** Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

**WORK HYGIENIC PRACTICES:** Use good personal hygiene when handling this product. Wash hands

after use, before eating, drinking, smoking, or using the toilet.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**COMMENTS:** May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Freezing Point (°C)	Auto Ignition (°C)	Solubility in Water	Specific Gravity
Methyl isobutyl ketone	60	115.8	-85	460	Moderate in water.	0.804

**PHYSICAL STATE:** Liquid

**ODOR:** Alcohol odor.

**COLOR:** Clear, colorless liquid.

**pH:** NA = Not Applicable

**VAPOR PRESSURE:** 14.5 - 96

**VAPOR DENSITY:** Heavier than air.

**BOILING POINT:** (173°F) to (241°F)

**FREEZING POINT:** NDA = no data available.

**FLASHPOINT AND METHOD:** (55°F) to (60°F) TAG CC

**SOLUBILITY IN WATER:** Soluble

**EVAPORATION RATE:** Less than 1 (n-Butyl Acetate = 1)

**DENSITY:** 6.60

**SPECIFIC GRAVITY:** 0.780 to 0.81

**(VOC):** 6.595 lbs./gal.

## 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide and unidentified organic compounds may be formed during combustion.

**INCOMPATIBLE MATERIALS:** This product is incompatible with strong acids or bases, oxidizers, alkali metals, and halogens.

**COMMENTS:** Prevent vapor accumulation.

## 11. TOXICOLOGICAL INFORMATION

**CARCINOGENICITY**

Chemical Name	IARC Status
Ethanol	1

**REPRODUCTIVE EFFECTS:** This product contains ethanol. Alcoholic beverage consumption has been associated with birth defects in humans. The relevance of this finding to ethanol exposure in industrial environments is uncertain.

**TARGET ORGANS:** This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain. Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**GENERAL COMMENTS:** Laboratory studies have shown that harmful by inhalation and if swallowed. Possible risks of irreversible effects.

**12. ECOLOGICAL INFORMATION**

**GENERAL COMMENTS:** Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

**EMPTY CONTAINER:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Ethanol Solutions

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** UN 1170

**PACKING GROUP:** II

**NAERG:** 127

**LABEL:** Flammable liquid

**15. REGULATORY INFORMATION**

**UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable Liquid

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes  
**CHRONIC:** Yes

**313 REPORTABLE INGREDIENTS:** Methyl Isobutyl Ketone (CAS 108-10-1)

**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
2-Propanol	8 - 14	67-63-0
Methyl isobutyl ketone	0.6 - 1.1	108-10-1

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** To the best of our knowledge, none of the chemicals in this product are listed as an extremely hazardous substance under Section 302 of SARA Title III nor does this product contain any other such substances.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

Chemical Name	Wt. %	CERCLA RQ
Methyl isobutyl ketone	0.6 - 1.1	5,000 lbs.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
2-Propanol	67-63-0
Methyl isobutyl ketone	108-10-1

**TSCA REGULATORY:** All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

**16. OTHER INFORMATION**

**PREPARED BY:** Compliance Dept.

**REVISION SUMMARY:** Revision #: 1. This MSDS replaces the August 06, 2008 MSDS. Any changes in information are as follows: In Section 1: General Use Statement

**HMIS RATING**

<b>HEALTH:</b>	<b>2</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	<b>H</b>

**HMIS RATINGS NOTES:** The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered.

**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.