

SAFETY DATA SHEET



Date Issued : 11/12/2014
MSDS No : 3109

SCREEN WASH 184

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SCREEN WASH 184

MANUFACTURER

Tarr, LLC
P.O. Box 12570
Portland, OR 97212
Product Stewardship: 503-288-5294

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666


2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Physical:

Flammable Liquids, Category 3

GHS LABEL



Flame Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May cause asphyxiation, or brain, lung or other organ injury if inhaled, swallowed or absorbed by the skin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

SKIN: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of

SCREEN WASH 184

the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Ingestion may cause headache, dizziness, fatigue, and central nervous system depression.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing eye and skin disorders may be aggravated by exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Acetone	55 - 60	67-64-1
Solvent EEP	1 - 4	763-69-9
Xylenes (o-,m-,p- isomers)	35 - 40	1330-20-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

INGESTION: Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

NOTES TO PHYSICIAN: If victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage should be considered following intubation with a cuffed endotracheal tube.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IB flammable liquid.

GENERAL HAZARD: Flammable Liquid and Vapor! Contact with strong oxidizers may cause fire.

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

SCREEN WASH 184

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep material out of storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
Chemical Name	EXPOSURE LIMITS				
	OSHA PEL	ACGIH TLV	ppm	mg/m ³	
Acetone	TWA	1000	2400	500	
	STEL			750	
Solvent EEP	TWA	[1]	[1]	[2]	[2]
Xylenes (o-,m-,p- isomers)	TWA	100	435	100	434
	STEL			150	651

OSHA TABLE COMMENTS:

1. NA=NOT APPLICABLE
2. NA = Not Applicable

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench

SCREEN WASH 184

facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Pungent odor.

APPEARANCE: Clear

COLOR: Water-white.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: (21°F) (Calculated)

AUTOIGNITION TEMPERATURE: No data available.

VAPOR PRESSURE: 1.5 mm Hg @ deg C (77 deg F)

VAPOR DENSITY: Lighter than air.

BOILING POINT: (165°F)

SOLUBILITY IN WATER: Negligible in water.

EVAPORATION RATE: Slower than ether.

DENSITY: 6.908 at (60°F)

SPECIFIC GRAVITY: 0.829 to 0.830 15.5°C/60°F

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under ordinary conditions of use and storage.

POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Prevent vapor accumulation.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

SCREEN WASH 184**INCOMPATIBLE MATERIALS:** Strong oxidizers.**11. TOXICOLOGICAL INFORMATION****ACUTE**

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Acetone	5800 mg/kg (Rat)		
Xylenes (o-,m-,p- isomers)	4300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	6700 ppm / 4 hours (rat)

NOTES: Material may cause eye irritation. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

EYE EFFECTS: Irritating to eyes.

GENERAL COMMENTS: None identified.

COMMENTS: This product may contain benzene (CAS 71-43-2) at a concentration of less than 10 ppm.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Readily biodegradable.

ECOTOXICOLOGICAL INFORMATION: Keep out of waterways.

BIOACCUMULATION/ACCUMULATION: Not expected to bioaccumulate significantly.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: Flammable Liquids, N.O.S. (Acetone, Xylene)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1993

PACKING GROUP: II

SCREEN WASH 184**NAERG:** 128**LABEL:** Flammable liquid**MARINE POLLUTANT #1:** No**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable

Liquid

S23: Do not breathe gas/fumes/vapour/spray.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: Xylenes (1330-20-7)

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA RQ: Acetone 5000 lbs

Xylene 1000 lbs

CALIFORNIA PROPOSITION 65: To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

CANADA**WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Flammable

Liquid

S15: Keep away from heat.

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.


SCREEN WASH 184**16. OTHER INFORMATION**

REASON FOR ISSUE: Updated SDS information and changed to new format.

PREPARED BY: Compliance

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	G

NFPA CODES

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.