

B14



MATERIAL SAFETY DATA SHEET

590 S. Paddock Pontiac MI 48341

Ph: 248-333-1333 Fax: 248-333-1426

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Eastway 68
SYNONYMS: Petroleum Way Oil
PRODUCT CODES: 31780001

MANUFACTURER: Eastern Oil Company
ADDRESS: 590 South Paddock
Pontiac, MI 48341

EMERGENCY PHONE: Eastern Oil (248) 333-1333

FAX PHONE: (248) 333-1426

CHEMICAL FAMILY: Petroleum Hydrocarbon
CHEMICAL FORMULA: Mixture

SECTION 1 NOTES: Product is a blend of highly refined petroleum oils fortified with additives to enhance extreme pressure, lubricity, and film strength.

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	% WT	OSHA TWA	ACGIH TLV	SARA 313
Mineral Oil	Various	>97	5 mg/m3 (Mist)	5 mg/m3 (Mist)	No

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: No acute effects expected from incidental skin contact during handling. Aspiration hazard if swallowed. Regulated OSHA air contaminant (29 CFR 1910.1000, Subpart Z). Liquid is slippery and will burn. Avoid release of this product to the environment.

ROUTES OF ENTRY: Eyes, Skin, Inhalation, Ingestion

POTENTIAL HEALTH EFFECTS:

EYES: May cause mild irritation.

SKIN: Long term or repeated exposures will defat the skin resulting in irritation and possible dermatitis.

INGESTION: May result in vomiting. Danger of aspiration to the lungs with potential for chemical pneumonitis.

INHALATION: Prolonged, excessive inhalation may cause irritation to the lungs and air passages.

ACUTE HEALTH HAZARDS: Eye and respiratory irritation.

CHRONIC HEALTH HAZARDS: Possible dermatitis and respiratory tract inflammation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dry skin.

CARCINOGENICITY

OSHA: NO ACGIH: NO NTP: NO IARC: NO

SECTION 3 NOTES: NONE

MATERIAL SAFETY DATA SHEET

590 S. Paddock Pontiac MI 48341

Ph: 248-333-1333 Fax: 248-333-1426

SECTION 4: FIRST AID MEASURES

EYES: Flush with copious amounts of water for several minutes. If irritation persists, continue with water application. If after 15 minutes, irritation continues, seek medical attention.

SKIN: Promptly wash skin with mild soap and water.

INGESTION: Do not induce vomiting. Seek qualified medical attention. Small amounts, which may enter the mouth incidental to handling, may be rinsed out with water.

INHALATION: Remove to fresh air. In severe cases of overexposure, such as with a fire, administer oxygen and seek qualified medical attention.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Treat symptoms as required. Product contains petroleum oils.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT:

F: >300 deg. Fahrenheit Min.

C:

METHOD USED: Cleveland Open Cup

AUTOIGNITION TEMPERATURE:

F: Not Determined

C:

NFPA HAZARD CLASSIFICATION

HEALTH: 1

FLAMMABILITY: 1

REACTIVITY: 0

OTHER: None

HMIS HAZARD CLASSIFICATION

HEALTH: 1

FLAMMABILITY: 1

REACTIVITY: 0

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical, Water Fog

SPECIAL FIRE FIGHTING PROCEDURES: Water may spread the fire as oil can float on it. Water spray may be used to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Water may spread the fire. Heated containers may rupture.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon, Sulfur, Phosphorous, and Nitrogen. Smoke, odorous and toxic fumes may form during incomplete combustion. High heat may also generate low levels of ammonia and hydrogen sulfide.

SECTION 5 NOTES: Use of water for fire fighting must be done with caution as water may actually spread the fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Prevent spread of material, especially to rivers or waterways by diking with dirt or absorbent. For large spills, pump released material into recovery containers and then spread absorbent over the spill area to collect residuals. For small spills, wipe up or use absorbent to clean the spill area.

SECTION 6 NOTES: Prevent spill from reaching any type of running or standing water, such as streams, sewers, well water and ponds.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a sheltered area, away from temperature extremes in labeled containers. Keep away from heat, sparks, or flame. Avoid contact with eyes, skin, clothing, and shoes.

OTHER PRECAUTIONS: When handling, have appropriate safety equipment for the working conditions including eyewash. Do not pressurize, cut, weld, braze, solder, drill, or grind containers containing product residues.

SECTION 7 NOTES: None



MATERIAL SAFETY DATA SHEET

590 S. Paddock Pontiac MI 48341

Ph: 248-333-1333 Fax: 248-333-1426

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Good ventilation desirable.

VENTILATION: Sufficient to control mists below the operator exposure threshold limit of 5 mg/m³.

RESPIRATORY PROTECTION: Required if employee exposure exceeds threshold.

EYE PROTECTION: Where contact is likely, wear safety glasses.

SKIN PROTECTION: Gloves recommended when handling. Neoprene, nitrile, or PVC offers good protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: As required, wear aprons, sleeves or other protective gear to prevent long-term skin contact.

WORK HYGIENIC PRACTICES: Keep clean. Wash exposed skin areas with mild soap and water.

EXPOSURE GUIDELINES: Avoid excessive inhalation of vapors or mists. Product is regulated by OSHA as an air contaminant. A TLV of 5 mg/m³ has been established.

SECTION 8 NOTES: None

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Amber oil

ODOR: Mild petroleum

PHYSICAL STATE: Liquid

pH AS SUPPLIED: Not Applicable
pH (Other):

BOILING POINT: Greater than 475 deg. Fahrenheit

VAPOR PRESSURE (mmHg): Less than 0.1 mm of Hg.
@ C: 20 deg.

SPECIFIC GRAVITY (H₂O = 1): 0.88 Typical
@ C: 20 deg.

EVAPORATION RATE: Nil

SOLUBILITY IN WATER: Nil

VOLATILE ORGANIC COMPOUNDS (VOC): Not Determined

SECTION 9 NOTES:

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID (STABILITY): Any type of contamination.

INCOMPATIBILITY (MATERIAL TO AVOID): Avoid mixing with strong oxidizers (such as powdered floor cleaners, caustic soda, or liquid perchlorates) and reducers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Oxides of Carbon, Sulfur, Phosphorous and Nitrogen may form during combustion. Also, low levels of hydrogen sulfide may be generated at elevated temperatures.



MATERIAL SAFETY DATA SHEET

590 S. Paddock Pontiac MI 48341

Ph: 248-333-1333 Fax: 248-333-1426

HAZARDOUS POLYMERIZATION: None

SECTION 10 NOTES: None

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Not Determined

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not Determined

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Contact waste hauler for recycling. Follow all Local, State and Federal regulations.

RCRA HAZARD CLASS: None

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME:

HAZARD CLASS:

ID NUMBER:

PACKING GROUP:

LABEL STATEMENT:

SECTION 14 NOTES: Not DOT Regulated

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): Components Listed

Sara 313 REPORTABLE INGREDIENTS: None

SECTION 15 NOTES:

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: None noted.

PREPARATION INFORMATION: Prepared at a QS 9000 certified facility.

DISCLAIMER: The information presented was obtained from sources believed to be reliable. However, it is provided without any warranty, expressed or implied, regarding its correctness. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the use, handling, storage, or disposal of the product.