



## MATERIAL SAFETY DATA SHEET

REVISION DATE: 01/10/2013  
DATE PRINTED: 01/10/2013

REVISION NUMBER: 2

### 1. CHEMICAL PRODUCT

PRODUCT NAME: **E-CLEANER Low Foam All Purpose Cleaner**  
PRODUCT CODE: 119265

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 1/1 Fire: 0/0  
Reactivity: 0/0 Special/Protective Equipment: None/B

DISTRIBUTED BY: ECORE International  
715 Fountain Avenue  
Lancaster, PA 17601

Emergency Phone:  
INFOTRAC: 1-800-535-5053  
OUTSIDE US: 1-352-323-3500

### 2. HAZARDS IDENTIFICATION

#### EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Low toxicity in small quantities. Nausea. Diarrhea Abdominal pain.  
SKIN CONTACT: May cause mild skin irritation.  
INHALATION: Inhalation of spray mist may be irritating.  
EYE CONTACT: May cause mild eye irritation.  
CHRONIC EFFECTS: None known.  
EFFECTS/CARCINOGENICITY: None listed under OSHA, IARC, or NTP.  
ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
Detergent blend MIXTURE	1 - 5	Not applicable	Not applicable

### 4. FIRST AID MEASURES

INGESTION: If swallowed, do NOT induce vomiting. Give victim two glasses of water, Call a physician immediately. Never give anything by mouth to an unconscious person.  
SKIN: Wash with soap and water. Remove contaminated clothing and laundry before reuse. Get medical attention if irritation persists.  
INHALATION: If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.  
EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.  
NOTES TO PHYSICIAN: None.

### 5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: (F): None to boiling (C): None to boiling  
METHOD: TCC  
FLAMMABLE LIMITS IN AIR

## E-CLEANER Low Foam All Purpose Cleaner

LOWER (%):  
UPPER (%):

No data  
No data

SENSITIVITY TO MECHANICAL IMPACT(Y/N):  
SENSITIVITY TO STATIC DISCHARGE:  
SUITABLE EXTINGUISHING MEDIA:  
FIRE FIGHTING PROCEDURES:

NO  
Sensitivity to static discharge is not expected.  
As for surrounding fire.  
Non-combustible material.

### 6. ACCIDENTAL RELEASE MEASURES

#### SPILL PROCEDURES:

SMALL SPILLS:

Flush with water.

LARGE SPILLS:

Dike to contain, reclaim all possible. Flush remainder with water. Be aware of potential for surfaces to become slippery.

PERSONAL PRECAUTIONS:

Wear adequate personal protective equipment, see Section 8, Exposure Controls/Personal Protection.

ENVIRONMENTAL PRECAUTIONS:

Not applicable

METHODS FOR CLEANING UP:

Not applicable

### 7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN  
IN HANDLING AND STORAGE:

Keep out of reach of children.  
Avoid prolonged contact. Avoid creating mists or aerosols.

OTHER PRECAUTIONS:

No other spill procedures necessary.

SPECIFIC USE(S):

Not applicable.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



EXPOSURE CONTROLS:

None known.

RESPIRATORY PROTECTION:

None required.

PROTECTIVE GLOVES:

Rubber gloves.

EYE PROTECTION:

Safety Glasses.

OTHER PERSONAL PROTECTION

None required.

EQUIPMENT:

VENTILATION:

None required.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

Light green, Liquid. No fragrance added.

BOILING POINT (F):

212° F

(C) 100° C

VAPOR PRESSURE:

15.7 mm Hg @ 22.2° C

VAPOR DENSITY (AIR=1):

0.625

SOLUBILITY IN WATER:

Soluble

SPECIFIC GRAVITY:

0.99 - 1.01

VOC Content (%):

1.3% (EPA Method 24)

EVAPORATION RATE:

(BuAc = 1) 1.26

PH:

6.8 (8.09 at 1:32 dilution)

### 10. STABILITY AND REACTIVITY

STABILITY DATA:

STABLE

POLYMERIZATION:

Will Not Occur.

## E-CLEANER Low Foam All Purpose Cleaner

### 10. STABILITY AND REACTIVITY

**HAZARDOUS DECOMPOSITION:** Oxides of Nitrogen. Oxides of Carbon.  
**INCOMPATIBILITY (MATERIALS TO AVOID):** None known.  
**CONDITIONS/HAZARDS TO AVOID:** None known.

### 11. TOXICOLOGICAL INFORMATION

**ACUTE TOXICITY:** Not Established  
**EFFECTS OF CHRONIC EXPOSURE:** Not established.  
**OTHER TOXIC EFFECTS:** Not established.

### 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** Not regarded as dangerous for the environment.  
**CHEMICAL FATE INFORMATION:** The product is not expected to be hazardous to the environment.  
**MOBILITY:** Not applicable.  
**PERSISTENCE/DEGRADABILITY:** Not applicable  
**BIOACCUMULATIVE POTENTIAL:** Not applicable  
**OTHER ADVERSE EFFECTS:** Not applicable

### 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS:** Dispose in accordance with Federal, State and Local regulations.

### 14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

### 15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
Detergent blend MIXTURE	1 - 5	Not Listed	Not Listed	Not Listed	Not Listed

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
Detergent blend MIXTURE	1 - 5	Not Listed	Not Listed	Not Listed

None of the components of this material are included in the Massachusetts Substance List nor are present at or above reportable levels.

None of the components of this material are included in the New Jersey Substance List nor are present at or above reportable levels.

None of the components of this material are included in the Pennsylvania Substance List nor are present at or above reportable levels.

### 16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

\*\*\* END OF MSDS \*\*\*

# SAFETY DATA SHEET

Lysol® I.C. Brand III Disinfectant Spray



HEALTH • HYGIENE • HOME

## 1. Product and company identification

**Product name** : Lysol® I.C. Brand III Disinfectant Spray

**Distributed by** : Reckitt Benckiser LLC.  
Morris Corporate Center IV  
399 Interpace Parkway (P.O. Box 225)  
Parsippany, New Jersey 07054-0225  
+1 973 404 2600

**Emergency telephone number (Medical)** : 1-800-338-6167

**Emergency telephone number (Transport)** : 1-800-424-9300 (U.S. & Canada) CHEMTREC  
Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

**Website:** : <http://www.rbnainfo.com>

**Product use** : Multipurpose Cleaner  
Professional use

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

**SDS #** : D0313648 v4.0

**Formulation #:** : 1589-023 (0271639 v1.0)

**EPA ID No.** : 777-99-675

**UPC Code / Sizes** : 36241-95029-08 (19 oz. Aerosol Can)

## 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 2

### GHS label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Flammable aerosol.  
Pressurized container: may burst if heated.

### Precautionary statements

**Code #** : FF0271639 (D0313648) **SDS #** : D0313648 v4.0 **Date of issue** : 12/05/2015.

1/13

D0313648 v4.0

## 2. Hazards identification

<b>General</b>	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
<b>Prevention</b>	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
<b>Response</b>	: Not applicable.
<b>Storage</b>	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
<b>Disposal</b>	: Not applicable.
<b>Supplemental label elements</b>	: None known.
<b>Hazards not otherwise classified</b>	: None known.

## 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Ethyl alcohol	30 - 60	64-17-5
butane	1 - 5	106-97-8
propane	< 2.5	74-98-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4. First aid measures

### Description of necessary first aid measures

<b>Eye contact</b>	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
<b>Inhalation</b>	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
<b>Skin contact</b>	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
<b>Ingestion</b>	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

D0313648 v4.0

## 4. First aid measures

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : May cause eye irritation upon direct contact with eyes.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.



D0313648 v4.0

## 8. Exposure controls/personal protection

### Control

#### Occupational exposure limits

Ingredient name	Exposure limits
Ethyl alcohol	<b>ACGIH TLV (United States, 6/2013).</b> STEL: 1000 ppm 15 minutes. <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1000 ppm 8 hours. TWA: 1900 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2013).</b> TWA: 1000 ppm 10 hours. TWA: 1900 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 1000 ppm 8 hours. TWA: 1900 mg/m <sup>3</sup> 8 hours.
butane	<b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 800 ppm 8 hours. TWA: 1900 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2013).</b> TWA: 800 ppm 10 hours. TWA: 1900 mg/m <sup>3</sup> 10 hours. <b>ACGIH TLV (United States, 6/2013).</b> STEL: 1000 ppm 15 minutes.
propane	<b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1000 ppm 8 hours. TWA: 1800 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2013).</b> TWA: 1000 ppm 10 hours. TWA: 1800 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 1000 ppm 8 hours. TWA: 1800 mg/m <sup>3</sup> 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.



D0313648 v4.0

## 8. Exposure controls/personal protection

### Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Aerosol.]
- Color** : Clear.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : 10.8 to 11.8 [Conc. (% w/w): 100%]
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: 25.6°C (78.1°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 0.8667 to 0.8967 g/cm<sup>3</sup> [20 to 25°C]
- Solubility** : Easily soluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

### Aerosol product

- Type of aerosol** : Spray

D0313648 v4.0

## 9. Physical and chemical properties

Heat of combustion : 21.4 kJ/g  
 Ignition distance : <45.72 cm

## 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.  
**Chemical stability** : The product is stable.  
**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.  
**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).  
**Incompatible materials** : Do not mix with household chemicals.  
**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m <sup>3</sup> 7 g/kg	4 hours -
*Lysol I.C. Brand III Disinfectant Spray	LC50 Inhalation Vapor	Rat	>2.12 mg/l	4 hours Maximum attainable concentration

**Conclusion/Summary** : Not classified Harmful. \*Information is based on toxicity test result of the concentrate of a similar product.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl alcohol	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
*Lysol I.C. Brand III Disinfectant Spray	Eyes - Cornea opacity	Rabbit	< 1	72 hours	4 days
	Skin - Primary dermal irritation index (PDII)	Rabbit	0.3	4 hours	72 hours

#### Conclusion/Summary

**Skin** : Slightly irritating to the skin. \*Information is based on toxicity test result of the concentrate of a similar product.

**Eyes** : Moderately irritating to eyes. \*Information is based on toxicity test result of the concentrate of a similar product.

#### Sensitization

### Mutagenicity

### **Carcinogenicity**

## Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-

Not available.

Not available.

Not available.

Not available.

Not available.

### Potential acute health effects

<b>Eye contact</b>	: May cause eye irritation upon direct contact with eyes.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Skin contact</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: No known significant effects or critical hazards.

<b>Eye contact</b>	: Adverse symptoms may include the following: irritation redness
<b>Inhalation</b>	: Adverse symptoms may include the following: respiratory tract irritation coughing
<b>Skin contact</b>	: No specific data.
<b>Ingestion</b>	: No specific data.

### Short term exposure

**Potential delayed effects** : Not available.

D0313648 v4.0

## 11. Toxicological information

### Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

### Persistence and degradability

Not available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Ethyl alcohol	-0.35	-	low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.






Other adverse effects : No known significant effects or critical hazards.

D0313648 v4.0

### 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

### 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
TDG Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
Mexico Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IMDG Class	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-		See DG List

PG\* : Packing group

### 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) PAIR: 2-methylpropan-2-ol; 2-(4-tert-butylbenzyl)propionaldehyde  
TSCA 8(a) CDR Exempt/Partial exemption: Not determined  
United States inventory (TSCA 8b): Not determined.  
Clean Water Act (CWA) 311: ammonia  
Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112 : Not listed  
(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 : Not listed  
Class I Substances

Clean Air Act Section 602 : Not listed  
Class II Substances

D0313648 v4.0

**15. Regulatory information**

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

**SARA 302/304****Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312**

Classification : Fire hazard

**Composition/information on ingredients**

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Ethyl alcohol	30 - 60	Yes.	No.	No.	Yes.	No.

**State regulations**

Massachusetts : The following components are listed: ETHYL ALCOHOL; BUTANE; PROPANE

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE; PROPANE

Pennsylvania : The following components are listed: DENATURED ALCOHOL; BUTANE; PROPANE

**Label elements**

Signal word: : CAUTION

Hazard statements : Causes moderate eye irritation

Precautionary measures : Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Wash with soap and water.

Keep out of the reach of children.

CONTENTS UNDER PRESSURE. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 °F. Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Hazard statements :



Flammable



D0313648 v4.0

## 16. Other information

Hazardous Material :  
Information System (U.S.A.)

Health	1
Flammability	3
Physical hazards	0
Personal protection	B

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection :  
Association (U.S.A.)



NFPA (30B) aerosol Flammability Level 2

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

Date of issue : 12/05/2015.

Date of previous issue : 25/01/2011.

Version : 4

**D0313648 v4.0**

## 16. Other information

**Prepared by** : Reckitt Benckiser LLC.  
Product Safety Department  
1 Philips Parkway  
Montvale, New Jersey 07646-1810 USA.  
FAX: 201-476-7770

**Revision comments** : Revision as per US GHS.

☑ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.