



MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT

INM Elektrik Slide

MSDS DATE: 04/09/04

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ELECTRIK SLIDE

PRODUCT CODES: INMESO

MANUFACTURER: International Nail Manufacturers (inm)
Division of Nail Cartel, Inc.

ADDRESS: 1221 N. Lakeview Ave.
Anaheim, CA 92807

EMERGENCY PHONE: INFOTRAK: 1-800-535-5053
USA 1-800-424-9300 International: 1-352-323-3500

OTHER CALLS: 1-800-541-9838

FAX PHONE: 1-714-779-9971

PREPARED BY: Steven Tate, Production Manager
1-714-779-9892

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT:</u>	<u>CAS NO.</u>	<u>WT:</u>	<u>Hazardous in Blend</u>
White Mineral Oil	8042-47-5	100	No

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

ROUTES OF ENTRY: SKIN- YES

POTENTIAL HEALTH EFFECTS

EYES: This product is minimally irritating to the eyes upon direct contact. Based on testing of similar products and/or components.

SKIN: This product is not expected to cause any skin irritation upon direct single or repeated and prolonged contact; however, similar chemical composition products applied to the skin of laboratory animals resulted in minimal to slight dermal irritation.

INGESTION: This product is relatively non-toxic by ingestion unless aspiration occurs. Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. This product has laxative properties and may result in abdominal cramps and diarrhea.

INHALATION: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. See Section 8 for oil mist exposure limits.

SECTION 4: FIRST AID MEASURES

EYES CONTACT: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and seek immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately.

INGESTION: May act as a laxative. Do not induce vomiting do to aspiration hazard. If vomiting should occur, lower head below knees to avoid aspiration. Seek immediate medical attention.



MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT

INM Elektrik Slide

MSDS DATE: 04/09/04

INHALATION: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: No data available.
(% BY VOLUME) LOWER: No data available.

FLASH POINT:
F: 320 F
C: 160 C
METHOD USED: ASTM D-92 (COC)

AUTOIGNITION TEMPERATURE: No data available.
F: No data available.
C: No data available.

NFPA HAZARD CLASSIFICATION
HEALTH: 0 FLAMMABILITY: 1 STABILITY: 0
OTHER:

HMIS HAZARD CLASSIFICATION
HEALTH: FLAMMABILITY: REACTIVITY:
PROTECTION:

EXTINGUISHING MEDIA: Use dry chemical, foam, or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:

PERSONNEL SAFEGUARDS: Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Remove all sources of ignition.

REGULATORY NOTIFICATIONS: Notify appropriate authorities of spill.

CONTAINMENT AND CLEAN UP: Contain spill immediately. Do not allow spill to enter sewers or watercourses. Absorb with appropriate inert material such as sand, clay, etc. Large spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Wash clothing prior to reuse. May be slippery when spilled.

OTHER PRECAUTIONS: Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106—Flammable and Combustible Liquids.



MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT
SECTION 7 NOTES:

INM Elektrik Slide

MSDS DATE: 04/09/04

Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION : If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits.

RESPIRATORY PROTECTION: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified.

EYE PROTECTION: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

SKIN PROTECTION: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.).

EXPOSURE GUIDELINES: This product does not contain any components with OSHA or ACGIH exposure limits. If oil is generated, exposure limits apply.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Transparent, water-white liquid.

ODOR: Odorless.

pH AS SUPPLIED: No data available.

BOILING POINT:
F: 500-800
C: 260-427.7

MELTING POINT: Not applicable.

VAPOR PRESSURE (mmHg): < 0.1 mm Hg
F: 68 F

VAPOR DENSITY (AIR = 1): > 1

SPECIFIC GRAVITY (H₂O = 1): 0.83 @ 60/60 F (approximate)

EVAPORATION RATE (EE = 1): < 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (con't)

SOLUBILITY IN WATER: Soluble in hydrocarbons, negligible in water.

PERCENT VOLATILE:
BY WT/ BY VOL @ Nil

VOLATILE ORGANIC COMPOUNDS (VOC): No data available.

MOLECULAR WEIGHT: Varies

VISCOSITY:
@ 100 F/ 40 C
F: No data available
C: No data available



MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT **INM Elektrik Slide**

MSDS DATE: 04/09/04

OCTANOL/ WATER COEFFICIENT: LOG KOW = No data available.

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): High heat and open flame.

INCOMPATIBILITY (MATERIAL TO AVOID): May react with strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:
CARCINOGENICITY: The International Agency for Research on Cancer (IARC) has concluded that highly refined mineral oils are Group 3 substances, "Not Classifiable as to their carcinogenicity to humans," based on inadequate human and inadequate animal evidence. IARC has also concluded that there is no evidence for the carcinogenicity to experimental animals of white oils when administered by routes other than by intraperitoneal injection.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

REGULATORY INFORMATION: All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Caution! If regulated solvents are used to clean up spilled material, the resulting waste mixture may be regulated. Department of Transportation (DOT) regulations may apply for transporting this material when spilled.

WASTE DISPOSAL METHOD: Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)
HIGHWAY/ RAIL (BULK): Not Regulated
HIGHWAY/ RAIL (NON-BULK): Not Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

INTERNATIONAL INFORMATION:
Vessel (IMDG): Not Regulated
Air (ICAO): Not Regulated

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS
TSCA (TOXIC SUBSTANCE CONTROL ACT): Listed.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):



MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT

INM Elektrik Slide

MSDS DATE: 04/09/04

This product is not known to contain any SARA, Title III, Section 313 Reportable Chemicals at or greater than 1.0% (0.1% carcinogens).

311/312 HAZARD CATEGORIES: Not Regulated.

313 REPORTABLE INGREDIENTS: This product is not known to contain any SARA, Title III, Section 313 Reportable Chemicals at or greater than 1.0% (0.1% for carcinogens).

INTERNATIONAL REGULATIONS: Not a Controlled Product under Canadian WHMIS.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: None available.

DISCLAIMER: The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.