

MATERIAL SAFETY DATA SHEET

Product Trade Name: FA-15

Revision Date: 12-Dec-2014

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: FA-15
Synonyms: None
Chemical Family: Alcohol Surfactant Blend
Application: Wetting Agent

Manufacturer/Supplier: Halliburton Energy Services, Inc.
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Methanol	67-56-1	60 - 100%	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	5 - 10%	Not applicable	Not applicable
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	5 - 10%	Not applicable	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. May cause blindness. May be absorbed through the skin. Repeated overexposure may cause liver and kidney effects. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician The administration of ethanol after ingestion of this compound acts to counter the adverse effects of this material on the liver.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F): 62
Flash Point/Range (C): 16.7
Flash Point Method: PMCC
Autoignition Temperature (F): Not Determined
Autoignition Temperature (C): Not Determined
Flammability Limits in Air - Lower (%): Not Determined
Flammability Limits in Air - Upper (%): Not Determined

Fire Extinguishing Media Carbon Dioxide, Dry Chemicals, Foam.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases. Runoff to sewer may cause fire or explosion hazard.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 3, Reactivity 0
HMS Ratings: Health 2, Flammability 3, Physical Hazard 0, PPE: X

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another. Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Avoid breathing mist.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 12 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection	If engineering controls and work practices cannot keep exposure below occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified professional. Positive pressure self-contained breathing apparatus if methanol is released.
Hand Protection	Impervious rubber gloves.
Skin Protection	Rubber apron.
Eye Protection	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Colorless to amber or brown
Odor:	Alcohol
pH:	5.87 - 7.17
Specific Gravity @ 20 C (Water=1):	0.8661 - 0.8921
Density @ 20 C (lbs./gallon):	7.22 - 7.44
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	0
Freezing Point/Range (C):	-17.8
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers. Strong alkalis.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide. Oxides of sulfur. Oxides of nitrogen. Hydrogen cyanide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation. Ingestion.

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

May cause severe eye irritation.

Skin Contact

May cause skin irritation. May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause skin defatting with prolonged exposure.

Ingestion

May be fatal or cause blindness if swallowed. May cause headache, dizziness, nausea, vomiting, gastrointestinal irritation and central nervous system depression.

Chronic Effects/Carcinogenicity

Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart, central nervous system and spleen damage.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methanol	67-56-1	> 1187 - 2769 mg/kg (Rat) 3000 mg/kg (Monkey) 300 mg/kg (Human)	15800 mg/kg (Rabbit) 393 mg/kg (Primate)	87.5 mg/L (Rat) 6h vapour 128.2 mg/L (Rat) 4h vapour 83.2 mg/L (Rat) 4 h 64000 ppm (Rat) 4 h 10 mg/L (Human)
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	1836 mg/kg (similar substance)	No data available	No data available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	1836 mg/kg (similar substance)	No data available	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: Not determined

Acute Crustaceans Toxicity: Not determined

Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Methanol	67-56-1	EC50(96h): ca. 22000 mg/L (Pseudokirchnerella subcapitata, Growth rate)	LC50: 28200 mg/l (Pimephales promelas) LC50(96h): 12700 – 15400 mg/L (Lepomis macrochirus) 200 hr NOEC for % Embryo-cardiovascular for stage 2 = 15800 mg/L	IC50(3h): > 1000 mg/L (activated sludge)	EC50(96h): 18260 mg/L (Daphnia magna) NOEC(21d): 122 mg/L (Daphnia magna, Reproduction)
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	No information available	No information available	No information available	No information available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	No information available	No information available	No information available	No information available

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Methanol	67-56-1	Readily biodegradable (95-97% @ 20d)
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	No information available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	No information available

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Methanol	67-56-1	-0.77 BCF 1.0 – 4.5 (Cyprinus carpio) BCF < 10 (Leuciscus idus melanotus)
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	No information available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No information available.

Substances	PBT and vPvB assessment
Methanol	Not PBT/vPvB

12.6. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: UN1993
UN Proper Shipping Name: Flammable Liquid, N.O.S. (Contains Methanol)
Transport Hazard Class(es): 3
Packing Group: II
NAERG: NAERG 128

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG u10

UN Number: UN1993
UN Proper Shipping Name: Flammable Liquid, N.O.S. (Contains Methanol)
Transport Hazard Class(es): 3
Packing Group: II

IMDG/IMO

UN Number: UN1993
UN Proper Shipping Name: Flammable Liquid, N.O.S. (Contains Methanol)
Transport Hazard Class(es): 3
Packing Group: II

EMS: EmS F-E, S-E

IATA/ICAO

UN Number: UN1993
UN Proper Shipping Name: Flammable Liquid, N.O.S. (Contains Methanol)
Transport Hazard Class(es): 3
Packing Group: II

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Fire Hazard

EPA SARA (313) Chemicals This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Methanol//67-56-1

EPA CERCLA/Superfund Reportable Spill Quantity EPA Reportable Spill Quantity is 1088 Gallons based on Methanol (CAS: 67-56-1).

EPA RCRA Hazardous Waste Classification If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:
Ignitability D001

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class B2 Flammable Liquids
D1B Toxic Materials
D2A Very Toxic Materials
D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****