

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



1. Identification

1.1. Product identifier

Product Identity Feature Builder Firming
Alternate Names Sundry Chemical, Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Sundry Chemical
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name The Dodge Company, Inc
9 Progress Road
Billerica, MA 01821

Emergency

CHEMTREC (USA) (800) 424-9300
Customer Service: The Dodge Company, Inc (800) 443-6343, (978) 600-2099

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Acute Tox. 3;H301	Toxic if swallowed.
Acute Tox. 3;H311	Toxic in contact with skin.
Acute Tox. 3;H331	Toxic if inhaled.
Skin Corr. 1B;H314	Causes severe skin burns and eye damage.
Eye Dam. 1;H318	Causes serious eye damage.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Muta. 2;H341	Suspected of causing genetic defects.
Carc. 1B;H350	May cause cancer.
STOT SE 1;H370	Causes damage to organs. Specific Target Organs: (Not Available)

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P307+311 IF exposed: Call a POISON CENTER or doctor / physician.

P308+313 IF exposed or concerned: Get medical advice / attention.

P321 Specific treatment (see information on this label).

P330 IF SWALLOWED: Rinse mouth.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methanol CAS Number: 0000067-56-1	75 - 100	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370 (> 10%) STOT SE 2;H371 (3% ~ 10%)	[1][2][3]
Formaldehyde CAS Number: 0000050-00-0	5 - 10	Carc. 1B;H350 Muta. 2;H341 Acute Tox. 3;H301 Acute Tox. 3;H311 Acute Tox. 3;H331 Skin Corr. 1B;H314 Skin Sens. 1;H317 >0.2 %	[1][2]
Cellulose Nitrate	1 - 5	Flam. Sol. 1;H228	[1]

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



CAS Number: 0009004-70-0

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

If chemical is swallowed, Call Physician Or Poison Control Center For Most Current Information. Ingestion is life threatening.

Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow.

Victims Of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take copy of label and SDS with victim to health professional.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Acute: Severe irritation of the tissue that had contact with the product (skin, eyes, mucous membranes). Drowsiness, fatigue, confusion may be experienced after inhalation or ingestion of the material.

Chronic: Methanol is eliminated slowly from the body. Therefore repeated exposures may build up to toxic levels in body tissues. Animal studies shows long term exposures to Methanol damages the CNS, kidneys or liver, skin disorders, and birth defects.

Symptoms of Over Exposure by Route of Exposure: Methanol may be harmful if swallowed, inhaled, or injected into skin. Methanol can cause skin and eye irritation or damage. Methanol can be very irritating to mucous membranes and the respiratory tract.

Inhalation: Inhalation of Methanol vapors may lead to irritation of the nose and throat. Symptoms of overexposure may include dizziness, coughing, headache, dyspnea,

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



lachrymation, nausea and vomiting. Exposure to high concentrations of this material vapor may cause unconsciousness or death.

Primary Routes of Entry: Inhalation, skin contact, eyes, ingestion.

Target Organs: CNS, eyes, circulatory and respiratory systems.

Contact With Skin or Eyes: Methanol is an eye and skin irritant. Splashes in the eye may cause eye irritation, redness, tearing, and temporary corneal damage or blindness.

Skin Absorption: Methanol is absorbed through the skin and may result in effects similar to inhalation exposure.

Ingestion: Ingestion of one to four ounces of Methanol can cause irreversible damage to the nervous system, blindness, or death. It cannot be made non-poisonous. Aspiration of the material into the lungs can cause chemical pneumonitis.

Injection: Injection of Methanol can lead to redness and irritation of the surrounding tissue. Reproductive or genetic defect hazard. See section 2 for further details.

Inhalation

Toxic if inhaled. Causes damage to organs.

Eyes

Causes serious eye damage.

Skin

Toxic in contact with skin. May cause an allergic skin reaction. Causes severe skin burns and eye damage.

Ingestion

Toxic if swallowed.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, foam or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep container tightly closed.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

Safety Data Sheet
Feature Builder Firming

SDS Revision Date:

11/16/2016



5.3. Advice for fire-fighters

Wear self-contained breathing apparatus to protect from decomposition products.

ERG Guide No. 127

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep container closed when not in use. Avoid contact with eyes, skin, or clothing.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

Spread an inert absorbent on the spill and place in a suitable, properly labeled container for recovery or disposal.

Flush area with large quantities of water.

7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: This substance is not compatible with strong oxidizing agents, acetyl bromide, alkylaluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and raney nickel catalyst.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000050-00-0	Formaldehyde	OSHA	TWA 0.75 ppm STEL 2 ppm
		ACGIH	STEL: 0.3 ppm Ceiling: 1 ppm S, A2, 1
		NIOSH	Ca TWA 0.016 ppm C 0.1 ppm [15-minute]
		Supplier	No Established Limit
0000067-56-1	Methanol	OSHA	TWA 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm Skin
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3) [skin]
		Supplier	No Established Limit
0009004-70-0	Cellulose Nitrate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

8.2. Exposure controls

Respiratory

Not necessary where area is properly ventilated.

Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance

Clear, pale-pink-orange, slightly fluorescent Liquid

Odor

Slightly perfumed, with pungent odor.

Odor threshold

Not determined

pH

NA

Melting point / freezing point

NA

Initial boiling point and boiling range

66-68C 151-155F

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



Flash Point	10-10C 50-54F
Evaporation rate (Ether = 1)	> 1 (n-Butyl acetate = 1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 6% Upper Explosive Limit: 36.5%
Vapor pressure (Pa)	98%
Vapor Density	Greater than 1
Specific Gravity	0.900
Solubility in Water	97%
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	97%

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Extreme heat may cause product to decompose, producing acrid smoke and irritating fumes.

10.5. Incompatible materials

This substance is not compatible with strong oxidizing agents, acetyl bromide, alkylaluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and raney nickel catalyst.

10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Methanol - (67-56-1)	143.00, Human - Category: 3	No data available	No data available	No data available	64,000.00, Rat - Category: NA
Formaldehyde - (50-00-0)	260.00, Guinea Pig - Category: 3	270.00, Rabbit - Category: 3	No data available	No data available	No data available
Cellulose Nitrate - (9004-70-0)	5,000.00, Mouse - Category: 5	No data available	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000050-00-0	Formaldehyde	OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: Yes
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009004-70-0	Cellulose Nitrate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	3	Toxic if swallowed.
Acute toxicity (dermal)	3	Toxic in contact with skin.
Acute toxicity (inhalation)	3	Toxic if inhaled.
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Serious eye damage/irritation	1	Causes serious eye damage.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	2	Suspected of causing genetic defects.
Carcinogenicity	1B	May cause cancer.

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



Reproductive toxicity	---	Not Applicable
STOT-single exposure	1	Causes damage to organs.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa
Formaldehyde - (50-00-0)	1.41, Oncorhynchus mykiss	5.80, Daphnia pulex	0.00 (96 hr),
Cellulose Nitrate - (9004-70-0)	Not Available	Not Available	579.00 (96 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN2059	UN2059	UN2059
14.2. UN proper shipping name	UN2059, Nitrocellulose, solution, flammable with not more than 12.6 percent nitrogen, by mass, and not more than 55 percent nitrocellulose, 3, III	Nitrocellulose, solution, flammable with not more than 12.6 percent nitrogen, by mass, and not more than 55 percent nitrocellulose	Nitrocellulose, solution, flammable with not more than 12.6 percent nitrogen, by mass, and not more than 55 percent nitrocellulose
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	III	III	III
14.5. Environmental hazards			
IMDG	Marine Pollutant: No;		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D1B E
US EPA Tier II Hazards	<p style="text-align: right;">Fire: Yes</p> <p style="text-align: right;">Sudden Release of Pressure: No</p> <p style="text-align: right;">Reactive: No</p> <p style="text-align: right;">Immediate (Acute): Yes</p> <p style="text-align: right;">Delayed (Chronic): Yes</p>
EPCRA 302 Extremely Hazardous:	Formaldehyde
EPCRA 313 Toxic Chemicals:	Formaldehyde

Safety Data Sheet

Feature Builder Firming

SDS Revision Date:

11/16/2016



Methanol

Proposition 65 - Carcinogens (>0.0%):

Formaldehyde

Proposition 65 - Developmental Toxins (>0.0%):

Methanol

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Cellulose Nitrate

Formaldehyde

Methanol

Pennsylvania RTK Substances (>1%):

Cellulose Nitrate

Formaldehyde

Methanol

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H228 Flammable solid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

Safety Data Sheet
Feature Builder Firming

SDS Revision Date:

11/16/2016



H371 May cause damage to organs.

This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document