

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FERROPRO MUCK-OFF GRAFFITI REMOVER

Recommended use of the chemical and restrictions on use: Graffiti remover.

Supplier: Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street,
Padstow, NSW 2211
Australia

Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825
Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.
This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

Risk Phrase(s):

R36/37/38 Irritating to eyes, respiratory system and skin.
R61 May cause harm to the unborn child.

Poisons Schedule (SUSMP): S6 Poison.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
N-methyl-2-pyrrolidone	872-50-4	>60%	R36/37/38, Repr. Cat.2 R61
Surfactants	-	10-<30%	-
Ethyl 3-ethoxy propionate	763-69-9	10-<30%	R10

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Product Name: FERROPRO MUCK-OFF GRAFFITI REMOVER
Substance No: 000704626801

Issued: 25/07/2013
Version: 4

Safety Data Sheet

**Ingestion:**

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the substance or mixture:

Combustible liquid. On burning will emit toxic fumes, including those of oxides of carbon and oxides of nitrogen .

Special protective equipment and precautions for fire-fighters:

Keep containers cool with water spray. If safe to do so, remove containers from path of fire. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water.

7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour.

Conditions for safe storage, including any incompatibilities:

Store in a well ventilated area away from foodstuffs, oxidising agents and sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

1-Methyl-2-pyrrolidone: 8hr TWA = 103 mg/m³ (25 ppm), 15 min STEL = 309 mg/m³ (75 ppm), Sk

Safety Data Sheet



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Use in well ventilated areas. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Blue



MANUFACTURE, PACKAGING AND TRANSPORT: Blue - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and face shield or chemical goggles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. **FOR CONSUMER USE:** Use with adequate ventilation. Avoid contact with eyes and skin. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Clear / Hazy
Solubility:	Dispersible in water.
Specific Gravity:	0.985 @ 20°C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	0.1 kPa
Flash Point (°C):	90 (approx.)
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
% Volatile by Volume:	Not available
Solubility in water (g/L):	Dispersible
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	150 (approx.)
Decomposition Point (°C):	Not available

Product Name: FERROPRO MUCK-OFF GRAFFITI REMOVER
Substance No: 000704626801

Issued: 25/07/2013
Version: 4

9. PHYSICAL AND CHEMICAL PROPERTIES

pH:	Not applicable
Viscosity:	34 Pa.s
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	Hazardous polymerisation will not occur.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration pneumonia (inflammation of the lung).
Eye contact:	An eye irritant.
Skin contact:	Contact with skin will result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. Component/s of this material can be absorbed through the skin with resultant toxic effects.
Inhalation:	Material is irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea.

Acute toxicity: No LD50 data available for the product. For the constituent N-methyl-2- pyrrolidone (1):
Oral LD50 (rat): 3605 mg/kg
Dermal LD50 (rabbit): 5000 mg/kg
Inhalation LC50 (rat): >5.1 mg/L/4 hrs

Skin corrosion/irritation:	Irritant (rabbit).
Serious eye damage/irritation:	Irritant (rabbit).
Chronic effects:	No information available for the product. For 1-methyl-2-pyrrolidone : May cause harm to the unborn child.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
-------------	--------------------------------

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

Risk Phrase(s):

R36/37/38 Irritating to eyes, respiratory system and skin.
R61 May cause harm to the unborn child.

Poisons Schedule (SUSMP): S6 Poison.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

(1) Safety Data Sheet - Australia Pty Ltd; 05/ 2011.

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 0800 735 539 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

5 Yearly Revised Primary SDS
Change in Hazardous Substance Classification

Safety Data Sheet



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.