

Kwik Klean A/C Flush Solvent

Version 1.3 Revision Date: 02/23/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Kwik Klean A/C Flush

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

Manufacturer or supplier's details

Company : FJC

Address 101 Commercial Drive, Mooresville NC 28115

SECTION 2. HAZARDS

IDENTIFICATION

:

:

GHS Classification Category 4

Flammable liquids :

Category 3 (Central nervous system)

Specific target organ toxicity

- single exposure

: Category 1

Aspiration hazard

GHS Label element

Hazard pictograms



 $\langle ! \rangle$

Danger

Signal word H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways. H336

Hazard statements May cause drowsiness or dizziness.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

Precautionary statements and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

SDS Number: 100000010809 1 / 9 Low Odor Base Solvent

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER

or doctor/ physician if you feel unwell.

P331 Do NOT induce vomiting.

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Weight %
64742-47-8	Distillates (petroleum), hydrotreated light	90 - 100

Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

advice.

If symptoms persist, call a physician.

In case of skin contact If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

SDS Number: 100000010809 2 / 9 Low Odor Base Solvent

If swallowed : Keep respiratory tract clear.

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Foam

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon oxides toxic

fumes

Unidentified organic and inorganic

compounds. Hydrogen sulfide sulfur oxides

Sulphuric acid

Carbon oxides

A complex mixture of airborne solid and liquid particulates and

gases (smoke). toxic fumes

Unidentified organic and inorganic

compounds. Hydrogen sulfide sulfur oxides Irritating fumes or substances may form.

Sulphuric acid

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-: Use personal protective equipment. tive equipment and emer- Ensure adequate ventilation. gency procedures

SDS Number: 100000010809 3 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep in a well-ventilated place. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8	Distillates (petroleum), hydrotreated light	TWA	200 mg/m3 (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL

SDS Number: 100000010809 4 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

 STEV (Mist)
 10 mg/m3
 CA QC OEL

 TWA
 525 mg/m3
 CA ON OEL

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, Colorless

Odour : mild, Hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Freezing Point (Melting

point/range)

: -49 °C (-56 °F)

Boiling Point (Boiling : 200 - 300 °C (392 - 572 °F)

point/boiling range)

Flash point : 80 - 95.6 °C (176 - 204.1 °F)

Method: Tag closed cup

Evaporation rate : 0.082

(Butyl Acetate = 1)

SDS Number: 100000010809 5 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

Flammability (solid, gas) : No data available

Upper explosion limit : 4.9 - 5.5 %(V)

Lower explosion limit : 0.5 - 0.6 %(V)

Vapour pressure : 0.23 - 0.45 mmHg @ 20 - 25 °C (68 - 77 °F)

Relative vapour density : > 7 @ 20 - 25 °C (68 - 77 °F)

(Air = 1.0)

Relative density : 0.80 - 0.825 @ 15.6 °C (60.1 °F)

Reference substance: (water = 1)

Density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient:

noctanol/water

: No data available

Auto-ignition temperature : > 220 °C

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : < 10 mm2/s @ 40 °C (104 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Vapours may form explosive mixture with air.

Conditions to avoid : Keep away from heat, flame, sparks and other ignition sources.

Incompatible materials : Strong oxidizing agents

SDS Number: 100000010809 6 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

SECTION 11. TOXICOLOGICAL INFORMATION

STOT - single exposure

Components:

64742-47-8:

Target Organs: Nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Aspiration toxicity

Components:

64742-47-8:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : No

: No data available

mation

SECTION 13. DISPOSAL CONSIDERATIONS

SDS Number: 100000010809 7 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

Disposal methods

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

TDG (Transportation of Dangerous Goods): Not regulated as a dangerous good

IATA (International Air Transport Association): Not regulated as a dangerous good

IMDG-Code: Not regulated as a dangerous good

Special Notes: : The flash point for this material is greater than 100 F (38 C).

Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous

substance.

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B3: Combustible Liquid

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

SDS Number: 100000010809 8 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Revision Date : 02/23/2018

Material number:

16118608, 16098886, 16020483, 785216, 775084, 639471, 602800, 576900, 573661, 52686, 70236, 102431, 102999, 52690, 20591, 20590

Key or leg	end to abbreviations and acronyms	used in the	safety data sheet	
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%	
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration	
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit	
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances	
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic	
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act	
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit	
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.	
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value	
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average	

SDS Number: 100000010809 9 / 10 Low Odor Base Solvent

Kwik Klean A/C Flush Solvent

Version 1.2 Revision Date: 02/23/2018

ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Concentration 50%	

SDS Number: 100000010809 10 / 10 Low Odor Base Solvent