



Safety Data Sheet

FMC®-205

SDS No. 526

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: FMC®-205**General Use:** polysulfide elastomer**Manufacturer:** Smooth-On, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazards Identification

Classification of the substance or mixture

Skin Irritation – Category 3

Eye Irritation – Category 2A

Carcinogenicity – Category 2

Acute Environment – Category 1

Pictograms:**Signal Word:** Warning**Health Hazards:** H316

Causes mild skin irritation

H319

Causes serious eye irritation

H351

Suspected of causing cancer

Environmental Hazards:

H400

Very toxic to aquatic life

General

P101

If medical advice is needed, have product container or label at hand.

Precautions:

P102

Keep out of reach of children.

P103

Read label before use.

Prevention

P201

Obtain special instructions before use.

Precautions:

P202

Do not handle until all safety precautions have been read and understood.

P264

Wash with soap and water thoroughly after handling.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Response

P305 + P351 +

Precautions:

P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313

IF exposed or concerned: Get medical advice/attention.

P332 + P313

If skin irritation occurs: Get medical advice/attention.

Storage Precautions:	P337 + P313	If eye irritation persists: Get medical advice/attention.
	P391	Collect spillage.
	P405	Store locked up.
Disposal Precautions:	P501	Dispose of contents/container to federal, state and local regulations

Hazards not otherwise classified (HNOC) or not covered by GHS - none

Section 3 - Composition / Information on Ingredients

CAS No.	Hazardous Component	Concentration
68611-50-7	Propane, 1,2,3-trichloro-polymer with 1,1'-[methylenebis(oxy)]bis[2-chlorethane] and sodium sulfide, reduced	33% - 55%
1333-86-4	Carbon black	17% - 28%
1241-94-7	Phosphoric acid, 2-ethylhexyl diphenyl ester	17% - 28%
84-74-2	Dibutyl phthalate	5% - 12%

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flammable Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None known.

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Further information: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak procedures:

Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Environmental precautions:

Very toxic to aquatic life.

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures. Wash hands after use.

Storage Requirements: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Respiratory protection is not normally required when using this product with adequate ventilation. Should a respirator be needed, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with organic vapor cartridges.

Hand Protection: Wear chemically protective gloves to prevent prolonged or repeated skin contact.

Eye Protection: Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment: Provide eye bath and safety shower.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

Appearance : Black viscous liquid
Odor/Threshold: Mercaptan odor
pH: N.A. (non-aqueous)
Melting Point/Freezing Point: N.A.
Low/High Boiling Point: N.A.
Flash Point: >300 °F
Evaporation Rate: Not available
Flammability: f.p. at or above 200 °F
UEL/LEL: Not available

Vapor Pressure: None (Polymeric Resin)
Vapor Density (Air=1): >1
Specific Gravity (H₂O=1, at 4 °C): 1.35
Water Solubility: Insoluble
Partition coefficient: Not available
Auto-ignition temperature: Not available
Decomposition temperature: Not available
Viscosity: < 14,000 centipoise
% Volatile: No VOC

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong bases, and acids.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce carbon oxides and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

Skin Corrosion/Irritation: causes mild skin irritation
Serious Eye Damage/Irritation: causes serious eye irritation
Respiratory/Skin Sensitization: no data
Germ Cell Mutagenicity: no data
Carcinogenicity: suspected of causing cancer.
Reproductive Toxicity: may damage fertility or the unborn child.
Specific Target Organ Toxicity – Single Exposure: no data
Specific Target Organ Toxicity – Repeated Exposure: no data
Aspiration Hazard: no data
Acute Toxicity: no data
Chronic Exposure: no data
Potential Health Effects – Miscellaneous: no data

Section 12 - Ecological Information

Toxicity: no data
Persistence and Degradability: no data
Bioaccumulative Potential: no data
Mobility in Soil: no data
Other Adverse Effects: no data

Section 13 - Disposal Considerations

Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

DOT	IATA	IMDG
Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (di-n-butylphthalate)	Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (di-n-butylphthalate)	Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (di-n-butylphthalate)
HC: 9	HC: 9	HC: 9
Label: Marine Pollutant (55 gal drum quantities only)	Label: Marine Pollutant	Label: Marine Pollutant


Section 15 - Regulatory Information

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

California Proposition 65: This product contains chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

16 - Other Information

HMIS	
H	1
F	0
R	0



NFPA

Revision: 16

Date Prepared: April 13, 2015

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.