

Safety Data Sheet



Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **FOSROC NITOCOTE PUR PRIMER PART A**

Recommended use: Part A of an epoxy priming system for use in conjunction with chemical resistant polyurethane elastomer, for use in the mining industry. Applied by brush, phenolic resin core roller, trowel or airless sprayer.

Supplier: Parchem Construction Suppliers Pty Ltd
ABN: 80 069 961 968
Street Address: 7 Lucca Road
Wyong NSW 2259
Australia
Telephone: (02) 4350 5000

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Warning

Hazard Classification

Skin Corrosion/Irritation – Category 2
Serious Eye Damage/Irritation – Category 2A
Sensitisation – Skin – Category 1A
Carcinogenicity – Category 2

Hazard Statement(s)

H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H351 Suspected of causing cancer

Prevention Precautionary Statement(s)

P102 Keep out of reach of children
P103 Read label before use
P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P261 Avoid breathing fume, gas, mist, vapours or spray
P264 Wash hands, face and all exposed skin thoroughly after handling
P272 Contaminated work clothing should not be allowed out of the workplace
P273 Avoid release to the environment
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

Product name: FOSROC NITOCOTE PUR PRIMER PART A

SDS No: PARGHSEN000012

Issued: 30 January 2015

Version: 2.0

Page: 1 of 8

Safety Data Sheet



Response Precautionary Statement(s)

P101	If medical advice is needed, have product container or label at hand
P302+352	IF ON SKIN: Wash with soap and water
P362	Take off contaminated clothing and wash before reuse
P333+313	If skin irritation or a rash occurs: Get medical advice/attention
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P337+313	If eye irritation persists get medical advice/attention
P391	Collect spillage

Storage Precautionary Statement(s)

P405	Store locked up
------	-----------------

Disposal Precautionary Statement(s)

P501	Dispose of contents/container in accordance with local, regional, national and international regulations
------	--

Poisons Schedule (Aust): S5

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 9 Miscellaneous Dangerous Goods

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Bisphenol A-Epichlorhydrin reaction product	25068-38-6	30 - 60%
Carbon black	133-86-4	1 - 10%
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin contact: If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

Product name: FOSROC NITOCOTE PUR PRIMER PART A

SDS No: PARGHSEN000012

Issued: 30 January 2015

Version: 2.0

Page: 2 of 8

Safety Data Sheet



PPE for First Aiders: Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code: •3Z

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible liquid.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 36

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 9 Miscellaneous Dangerous Good as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

However for:

	TWA		STEL		CARCINOGEN CATEGORY	NOTICES
	ppm	mg/m3	ppm	mg/m3		
Carbon black	-	3	-	-	-	-

As published by the Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal protection equipment: C: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Safety Data Sheet



9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Black liquid with an aromatic odour.

Solubility:	Slightly soluble in water.
Specific Gravity (20 °C):	1.35
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	18 mmHg
Flash Point (°C):	>93
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	N Av
Melting Point/Range (°C):	<0
Boiling Point/Range (°C):	240
Decomposition Point (°C):	N Av
pH:	N Av
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

Safety Data Sheet



Acute toxicity

Inhalation: This material has been classified as non-hazardous.

Skin contact: This material has been classified as non-hazardous.

Ingestion: This material has been classified as non-hazardous.

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes).

Skin: this material has been classified as a Category 2 Hazard (irritant to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as a Category 1A Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as a Category 2 Hazard.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information is available to complete an assessment.

Long-term aquatic hazard: This material has been classified as a Category Chronic 2 Hazard.

Acute toxicity estimate (based on ingredients): 1 - 10 mg/L

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

Safety Data Sheet



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 3082
Dangerous Goods Class: 9 Miscellaneous
Packing Group: III
Hazchem Code: •3Z
Emergency Response Guide No: 47

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(CONTAINS BISPHENOL A-EPICHLORHYDRIN REACTION PRODUCT)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), oxidising agents (Class 5.1) or organic peroxides (Class 5.2), however exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

UN No: 3082
Dangerous Goods Class: 9 Miscellaneous
Packing Group: III

Proper Shipping Name: PAINT

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 3082
Dangerous Goods Class: 9 Miscellaneous
Packing Group: III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(CONTAINS BISPHENOL A-EPICHLORHYDRIN REACTION PRODUCT)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP)* established under the *Therapeutic Goods Act (Commonwealth)*.
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Supersedes: January 2010

Reason(s) For Issue: 5 Yearly Revision
Format change
Change in Hazardous Substance Classification

Technical Support: Australia - 1300 737 787, New Zealand – 0800 657 156

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd and Concrete Plus cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.