FPF Liquid Muscle FP-SL167

MSDS Preparation Date (dd/mm/yyyy): 03/01/2013

Page 1 of 6

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : FPPF Liquid Muscle

Product Code(s) : FP-SL167
Product Use : Fuel additive
Chemical Family : Mixture.

Supplier's name and address: Manufacturer's name and address:

FPPF Chemical Company, Inc. Refer to Supplier

117 West Tupper Street Buffalo, NY, USA

14201

Information Telephone # : 1-800-735-3773

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

SECTION 2 - HAZARDS IDENTIFICATION

Classification : OSHA: Hazardous classification: Combustible liquid; Acute Health Hazard; Chronic

Health Hazard.

WHMIS classification: Class B3 (Combustible Liquids); Class D2B (Materials Causing

Other Toxic Effects, Toxic Material).

Emergency Overview: Amber liquid. Odor of ether and petroleum distillates.

Warning! Combustible liquid and vapor. May be harmful if inhaled. Inhalation may cause respiratory irritation and central nervous system depression. Causes eye irritation. May cause skin irritation. May be harmful or fatal if swallowed. May cause gastrointestinal discomfort.

Aspiration can result in life-threatening lung injury.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation: Harmful by inhalation. Inhalation may cause respiratory irritation and central nervous system

depression. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and

other central nervous system effects.

Skin : May cause skin irritation.

Eyes : May cause moderate to severe irritation.

Ingestion : Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Aspiration into the

lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be

fatal.

Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS#	Wt.%
Mineral spirits	64742-88-7	N/Av

SECTION 4 - FIRST AID MEASURES

Inhalation

: Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.

FP-SL167 **FPPF Liquid Muscle**

MSDS Preparation Date (dd/mm/yyyy): 03/01/2013

Skin contact : Remove/Take off immediately all contaminated clothing. Wash off immediately with

plenty of water for at least 15 minutes. Get medical attention. Wash contaminated

Page 2 of 6

clothing before re-use.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If irritation or

symptoms develop, seek medical attention.

Ingestion Seek immediate medical attention/advice. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep

victim's head lowered (forward) to reduce the risk of aspiration.

Notes For Physician : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

Combustible liquid and vapor. This material may be ignited by heat, sparks and direct flame. Material will float on water and can be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200)

: Class II Combustible Liquid.

: None known. **Oxidizing properties**

Explosion data: Sensitivity to mechanical impact / static discharge

: May be sensitive to static discharge. Not expected to be sensitive to mechanical

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

Carbon oxides; Aldehydes; Hydrocarbons; irritating fumes and smoke.

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

> Health: 2 Flammability: Instability: 0 Special Hazards: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

: All persons dealing with clean-up should wear the appropriate protective equipment Personal precautions

> including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. **Environmental precautions**

For large spills, dike the area to prevent spreading.

Spill response/cleanup : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools

and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as

required.

Prohibited materials Do not use combustible absorbents, such as sawdust.

Special spill response procedures

In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

US CERCLA Reportable quantity (RQ): None.

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures : Use in a well ventilated area. Wear suitable protective equipment during handling. Do

not ingest. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Use proper bonding and grounding techniques when transferring liquid. Avoid contact with incompatible materials. Wash

thoroughly after handling.

Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of Storage requirements direct sunlight. Storage area should be clearly identified, clear of obstruction and

accessible only to trained and authorized personnel. Inspect periodically for damage or

leaks. No smoking in the area.

Incompatible materials Strong oxidizing agents

: Always keep in containers made of the same materials as the supply container. Special packaging materials

Page 3 of 6

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits OSHA PEL ACGIH TLV **TWA STEL PEL** STEL Ingredients Mineral spirits N/Av N/Av 500 ppm (as N/Av petroleum distillates, naphtha)

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below

recommended exposure limits.

Respiratory protection : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Confirmation

of which type of respirator is most suitable for the intended application should be

obtained from respiratory protection suppliers.

Skin protection: Impervious gloves must be worn when using this product. Advice should be sought

from glove suppliers.

Eye / face protection : Chemical splash goggles are recommended. A full face shield may also be

necessary

Other protective equipment : Wear resistant clothing and boots. Other equipment may be required depending on

workplace standards. An eyewash station and safety shower should be made available

in the immediate working area.

General hygiene considerations

Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing

home.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid Appearance : Amber liquid.

Odour : Odor of ether and Odour threshold : N/Av

petroleum distillates.

pH : N/Av

Boiling point : N/Av Specific gravity : 0.794

Melting/Freezing point : N/Av Coefficient of water/oil distribution

: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : N/Av

: N/Av

Vapour density (Air = 1) : >1 Evaporation rate (n-Butyl acetate = 1)

: <1

Volatile organic Compounds (VOC's)

Volatiles (% by weight) : N/Av

: N/Av

Flash point : 43.9°C / 111°F

Flash point Method : Tag closed cup Auto-ignition temperature : N/Av

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

N/Av : N/Av

Flame Projection Length : N/Ap Flashback observed : N/Ap

Section 10: Stability And Reactivity

Stability and reactivity : Stable under the recommended storage and handling conditions prescribed.

Hazardous polymerization : Will not occur.

Conditions to avoid : Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate

ventilation, especially in confined areas.

Materials To Avoid And Incompatibility

See Section 7 (Handling and Storage) section for further details.

Hazardous decomposition products

None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

FPF Liquid Muscle FP-SL167

Page 4 of 6

MSDS Preparation Date (dd/mm/yyyy): 03/01/2013

Target organs : Eyes, skin, respiratory system, digestive system, central nervous system.

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin & Eyes: YES Ingestion: YES

Toxicological data : There is no available data for the product itself, only for the ingredients. See

below for individual ingredient acute toxicity data.

	LCso(4hr)	LD ₅₀	
<u>Ingredients</u>	inh, rat	(Oral, rat)	(Rabbit, dermal)
Mineral spirits	N/Av	N/Av	N/Av

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects: Not expected to be cause reproductive effects.

Teratogenicity: Not expected to be a teratogen.

Mutagenicity: Not expected to be mutagenic in humans.

Epidemiology: Not available.

Sensitization to material : Not expected to be a skin or respiratory sensitizer.

Synergistic materials : Not available.

IrritancyMay cause eye, skin and respiratory tract irritation.other important hazardsNone known or reported by the manufacturer.

Conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself.

Mobility : No data is available on the product itself.

Persistence : No data is available on the product itself.

Bioaccumulation potential: No data is available on the product itself.

Other Adverse Environmental effects

The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle waste according to recommendations in Section 7. Empty containers retain

residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.

Methods of Disposal : Dispose of in accordance with federal, provincial and local hazardous waste laws.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the

criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and

federal environmental agencies.

SECTION 14: TRANPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label			
49CFR/DOT	NA1993	Combustible liquid, n.o.s. (Aliphatic naphtha)	Combustible.	III	COMBUSTIBLE			
49CFR/DOT Additional information	Not regulated for road or rail shipment if packaged in non-bulk containers (450 Litres or less each). The 'label' appearing here is the placard to be used for bulk shipments.							
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aliphatic naphtha)	3	III	3			
TDG Additional information	This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met.							

Page 5 of 6

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). See Section 2.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

International Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). See Section 2.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating : *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: *2 Flammability: 2 Reactivity: 0

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

FPPF Liquid Muscle FP-SL167

MSDS Preparation Date (dd/mm/yyyy): 03/01/2013

Page 6 of 6

: 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009

2. International Agency for Research on Cancer Monographs, searched 2009 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases

(Chempendium, HSDB and RTECs). 4. Material Safety Data Sheet from manufacturer.

5. US EPA Title III List of Lists

6. California Proposition 65 List

Prepared for:

References

FPPF Chemical Company, Inc. 117 West Tupper Street Buffalo, NY, USA 14201 Telephone: 1-800-735-3773

Please direct all enquiries to FPPF Chemical Company

Prepared by:

ICC The Compliance Center Inc. http://www.thecompliancecenter.com



DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

Preparation Date (dd/mm/yyyy)

: 03/01/2013

END OF DOCUMENT