

Section I - Product and Company Identification

Product Name: Fast Finish Top Coat

Chemical Name: LACQUER

Family: TOP COAT

Manufacturer: EZ Flow Nail Systems

13720 Rosecrans Ave. Santa Fe Springs CA. 90670

Product Use: NAIL TOP COAT

Emergency Phone Numbers: (800) 535 - 5053

Information Contacts: (562) 229-0337

Section II - Hazardous Ingredients

Chemical Identity	CAS Numbers	INCI Name	Exposure	Limits	Carcinogen	%
			OSHA TWA/STEL	ACGIH TWA/STEL		
Isobutyl Acetate	110-19-0	Isobutyl Acetate	150 ppm	150 ppm	Not Listed	>50
Ethyl Acetate	141 - 78 - 6	Ethyl Acetate	400 ppm	400 ppm	Not Listed	<40
Hydroxy propyl cellulose	9004-64-2	Hydroxy propyl cellulose	N/E	N/E	Not Listed	<20
Methyl Ethyl Ketone	78 - 93 - 3	Methyl Ethyl Ketone	200 ppm	200 ppm	Not Listed	<5
Xylene	1330-20-7	Xylene	100 ppm	100 ppm	3/no/no	<1
Benzophenone	119-61-9	Benzophenone	N/E	N/E	Not Listed	<1

N/E - None Established

N/R - Not Reviewed

N/DA - No Data Available

N/A - Not Applicable

Section III - Hazards Identification

EMERGENCY OVERVIEW

- May cause eye irritation.
- Flammable liquid and vapor
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	Inhalation, skin contact, eye contact
Eye	Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling.
Skin	Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, cracking, and skin burns.
Ingestion	Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.
Inhalation	Vapor and mist are irritating to mucous membranes. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.
Sub-Chronic Effects	May cause headaches, nausea, vomiting and narcotic effect if over-exposed.

NOTE: Refer to Section 11, Toxicological Information for Details

Section IV - First Aid Measures

First Aid for Eye	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently for 15 min. with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.
First Aid for Skin	Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.
First Aid for Inhalation	Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Section V - Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
TAG Closed: 68 ° F	400 ppm	750 ° F - 900 ° F

Method:

Extinguishing Media: Foam, dry chemical, cold water spray.

Fire Fighting Instructions: Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Water spray may be used to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

Section VI - Accidental Release Measures

Spill or Release Procedures: Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Section VII - Handling and Storage

Handling: Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash skin thoroughly after handling.

Storage: Store in a well ventilated area. Store @ 70 + 15 ° F, allow some air space above liquid level. Keep containers closed while not in use.

Explosion Hazard: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Section VIII - Exposure Controls / Personal Protective Equipment

Engineering Controls: Use process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General: For open systems where contact is likely, wear long sleeves, chemical resistant gloves and chemical goggles. Provide eye wash stations and showers.

Eye/ Face Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.

Skin Protection: Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: Use organic vapor mask and local exhaust systems.

Section IX - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile
Clear,viscous liquid	fruity ester odor	NA	(H2O=1):0.98	300-400 cps	W/W % : 99+

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
170 ° F	N/DA	N/DA	N/DA	(Air=1):1	NA	NA	Insoluble

Section X - Stability and Reactivity

Stability:

Stable

Hazardous Decomposition Products:

Heated material produces NO₂ , CO₂ , CO

Conditions to Avoid:

Heat, flame, ignition sources.

Incompatibility (Materials to Avoid):

Avoid oxidizing agents, acids & bases (heat)

Hazardous Polymerization:

May occur

Section XI - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
Oral LD50 (rat) : 3.2-6.4g/kg	Dermal LD50 (rabbit): >20mL/kg	Inhalation LC50 (rat) : 3500 - 8000 ppm/4 hours	Rabbit : slight	Rabbit : slight

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

Section XII - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

Section XIII - Disposable Concentrations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Section XIV - Transport Information

DOT/UN Shipping Name: UN 1993, Flammable Liquid NOS (Ethyl Acetate, Isobutyl Acetate), Class 3, PG II

Section XV - Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutant (HAP) , as defined by the U. S. Clean Air Act: Methyl Ethyl Ketone CAS #78-93-3, Xylene CAS #1330-20-7 , Benzophenone CAS #119-61-9. There are no ODS substances in this product.
------------------------	---

Material Safety Data Sheet

GLASS KOTE

Page 4 of 4

Clean Water Act: HS/Priority Pollutant	This product contains the following chemicals listed under the U. S Clean Water Act Hazardous Substance List: Xylene CAS #1330-20-7, Isobutyl acetate CAS #110-19-0. The following chemicals are listed as primary pollutants: None
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazard are: Immediate (acute) health hazard Fire hazard
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA (40 CFR 261). Ethyl Acetate CAS #141 - 78 - 6 RCRA Code: U112, Methyl Ethyl Ketone CAS #78 - 93 - 3 RCRA Code: U159, Xylene CAS #1330-20-7 RCRA Code: U239.
SARA Title III: Section 302	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List). Ethyl Acetate , CAS #141-78-6, RQ (Lbs) : 5000 Isobutyl Acetate , CAS #110-19-0, RQ (Lbs) : 5000 Methyl Ethyl Ketone , CAS #78-93-3, RQ (Lbs) : 5000 Xylene, CAS #1330-20-7, RQ (Lbs) : 100
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are : Immediate (acute) health hazard Fire hazard
SARA Title III: Section 313:	This product contains chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 . Methyl Ethyl Ketone , CAS #78-93-3 Xylene CAS #1330-20-7
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

State Regulations

CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3
MA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3
NJ Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3
PA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3
FL Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3
MN Right-to-Know Law:	Benzophenone CAS #119-61-9, Ethyl Acetate CAS #141-78-6, Xylene CAS #1330-20-7, Isobutyl Acetate CAS #110-19-0, Methyl Ethyl Ketone CAS 78-93-3

International Regulations

CDSL: Canadian Inventory
(on Canadian Transitional List)

Ethyl Acetate CAS #141-78-6 on DSL. WHMIS = B2, D2B
Isobutyl Acetate CAS #110-19-0 on DSL. WHMIS = n/da
Methyl Ethyl Ketone CAS #78-93-3 on DSL. WHMIS = B2, D2A

EINECS: European Inventory:

Hydroxypropyl cellulose CAS #9004-64-2 on DSL. WHMIS = n/da

Benzophenone CAS #119-61-9 on DSL. WHMIS = n/da

Xylene CAS #1330-20-7 on DSL. WHMIS = n/da

Isobutyl Acetate (203-745-1)

- Hazard Symbol (F), R Values (R11), S Values (S9, S16, S23, S29, S33)

Ethyl Acetate (205-500-4)

- Hazard Symbol (XI F), R Values (R11, R36, R66, R67), S Values (S16, S26, S33)

MEK (201-159-0)

- Hazard Symbol (XI F), R Values (R11, R36, R66, R67), S Values (S9, S16)

Hydroxypropyl cellulose (unlisted)

- Hazard Symbol (n/da), R Values (n/da), S Values (S24/25, S28A, S37, S45)

Xylene (215-535-7)

- Hazard Symbol (XN), R Values (R10, R20/21, R38), S Values (S25)

Benzophenone (204-337-6)

- Hazard Symbol (n/da), R Values (n/da), S Values (n/da).

Section XVI - Other Information

Hazard Rating System

NFPA: Health= 1/Flammability = 3/Reactivity = 1

HMIS: Health= 1/Flammability = 3/Reactivity = 1

Product Number -

Approval Date: 3/28/2001

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800)535-5053.