

MATERIAL SAFETY DATA SHEET

Product Trade Name: FillCem 1200 Cement Blend

Revision Date: 30-Jan-2015

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: FillCem 1200 Cement Blend

Synonyms: None

Chemical Family: Cement

Application: Cement

Manufacturer/Supplier Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Fly ash	68131-74-8	5 - 10%	TWA: 1 mg/m ³	Not applicable
Portland cement	65997-15-1	30 - 60%	TWA: 1 mg/m ³	15 mg/m ³
Silica, amorphous	7631-86-9	30 - 60%	2 mg/m ³	80 mg/m ³ - %SiO ₂
Crystalline silica, quartz	14808-60-7	5 - 10%	TWA: 0.025 mg/m ³	10 mg/m ³ - %SiO ₂ + 2
Crystalline silica, cristobalite	14464-46-1	0.1 - 1%	TWA: 0.025 mg/m ³	1/2 x 10 mg/m ³ - %SiO ₂ + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

3. HAZARDS IDENTIFICATION

Hazard Overview

CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, AS/NZS 1715, or equivalent respirator when using this product. Review the Safety Data Sheet (SDS) for this product, which has been provided to your employer.

4. FIRST AID MEASURES

Inhalation	If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.
Skin	Get medical attention if irritation persists.
Eyes	In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.
Ingestion	Under normal conditions, first aid procedures are not required.
Notes to Physician	Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	Not Determined
Flash Point/Range (C):	Not Determined
Flash Point Method:	Not Determined
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media None - does not burn.

Special Exposure Hazards Not applicable.

Special Protective Equipment for Fire-Fighters Not applicable.

NFPA Ratings: Health 1, Flammability 0, Reactivity 0
HMIS Ratings: Health 1*, Flammability 0, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary Measures None known.

Procedure for Cleaning / Absorption

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. HANDLING AND STORAGE

Handling Precautions

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Material is slippery when wet.

Storage Information

Store in a cool, dry location. Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Product has a shelf life of 24 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

Respiratory Protection

Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715, or equivalent respirator when using this product.

Hand Protection

Normal work gloves.

Skin Protection

Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

Eye Protection

Wear safety glasses or goggles to protect against exposure.

Other Precautions

Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Color:	Gray
Odor:	Odorless
pH:	12.4
Specific Gravity @ 20 C (Water=1):	Not Determined
Density @ 20 C (lbs./gallon):	Not Determined
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	0
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	0.5
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined

Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from any contact with water.
Incompatibility (Materials to Avoid)	Hydrofluoric acid.
Hazardous Decomposition Products	Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
------------------------------------	----------------------------------

Symptoms related to exposure

Acute Toxicity	
Inhalation	Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A). Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).
Eye Contact	May cause severe eye irritation.
Skin Contact	Can dry skin. May cause an allergic skin reaction. May cause alkali burns with confined contact.
Ingestion	None known

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Fly ash	68131-74-8	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat) (similar substance)	> 5.38 mg/L (Rat) 4h
Portland cement	65997-15-1	> 2000 mg/kg (Rat)	> 2000 mg/kg	> 1 mg/L (Rat) 4h
Silica, amorphous	7631-86-9	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 3.1 mg/L (Rat, 4h, maximum attainable concentration)
Crystalline silica, quartz	14808-60-7	> 5000 mg/kg (Rat)	No data available	No data available
Crystalline silica, cristobalite	14464-46-1	> 5000 mg/kg (Rat)	No data available	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Fly ash	68131-74-8	EC50: 1400 - 2000 mg/L (Scenedesmus subspicatus) EbC50(72h): 81.1 mg/L (biomass, Desmodesmus subspicatus) ErC50(72h): > 100 mg/L (growth rate, Desmodesmus subspicatus)	LC50: 700 - 2000 mg/L (Leuciscus idus) LC50(96h): > 100 mg/L (Poecilia reticulata)	EC50(3h): > 1000 mg/L (activated sludge)	TLM96: > 1000 ppm (Crangon crangon) EC50: 140 - 2000 mg/L (Daphnia magna) LC50(48h) > 100 mg/L (Daphnia magna)
Portland cement	65997-15-1	No information available	No information available	No information available	No information available
Silica, amorphous	7631-86-9	EC50: 440 mg/L (Pseudokirchneriella subcapitata)	LC50: 5000 mg/L (Brachydanio rerio); LC50: 45.4 mg/L (Oncorhynchus mykiss)	EC50(15min): 8700 mg/L (Microtox)	EC50: 7600 mg/L (Ceriodaphnia dubia) EC50: 40.38 mg/L (Ceriodaphnia dubia)

Crystalline silica, quartz	14808-60-7	No information available	LL0(96h): 10000 mg/L(Danio rerio) (similar substance)	No information available	LL50(24h): > 10000 mg/L (Daphnia magna) (similar substance)
Crystalline silica, cristobalite	14464-46-1	No information available	LL0(96h): 10000 mg/L(Danio rerio) (similar substance)	No information available	LL50(24h): > 10000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Fly ash	68131-74-8	The methods for determining biodegradability are not applicable to inorganic substances.
Portland cement	65997-15-1	The methods for determining biodegradability are not applicable to inorganic substances.
Silica, amorphous	7631-86-9	The methods for determining biodegradability are not applicable to inorganic substances.
Crystalline silica, quartz	14808-60-7	The methods for determining biodegradability are not applicable to inorganic substances.
Crystalline silica, cristobalite	14464-46-1	The methods for determining biodegradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Fly ash	68131-74-8	No information available
Portland cement	65997-15-1	No information available
Silica, amorphous	7631-86-9	No information available
Crystalline silica, quartz	14808-60-7	No information available
Crystalline silica, cristobalite	14464-46-1	No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No information available.

Substances	PBT and vPvB assessment
Fly ash	Not PBT/vPvB
Portland cement	No data available
Crystalline silica, quartz	Not PBT/vPvB
Crystalline silica, cristobalite	No data available

12.6. Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Disposal Method Bury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG ul0

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IMDG/IMO

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IATA/ICAO

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity Not applicable.

EPA RCRA Hazardous Waste Classification If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class

E Corrosive Material
D2A Very Toxic Materials
Crystalline silica

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****