

# Safety Data Sheet

Revision Date: 07-13-2015  
Product Code: 1510-053

## 1. IDENTIFICATION

Product Name	STANTEST MULTI-PURPOSE ALKYD PRIMER RED
Product Code	1510-053
Document ID	G1510-053
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Primer
Restrictions On Use	For Industrial Use Only
Chemical Family	Phenolic Alkyd Primer
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



### GHS Classification

Skin Sensitisation Category 1  
Flammable Liquid Category 2  
Skin Corrosion/Irritation Category 2  
Carcinogenicity Category 2  
Reproductive Toxicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2

### Signal Word

Danger

### Hazard Statements

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statements

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing,

# Safety Data Sheet

Revision Date: 07-13-2015

Product Code: 1510-053

	eye protection and face protection. Use personal protective equipment as required.
Response	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable

## Additional Information

Not applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Light aliphatic solvent naphtha	64742-89-8	7 - 13
Iron Oxide	1332-37-2	3 - 7
Solvent naphtha (petroleum) medium aliphatic	64742-88-7	1 - 5
Stoddard solvent	8052-41-3	0.5 - 1.5
Quartz (Silica-Crystalline)	14808-60-7	0.1 - 1
Carbon black	1333-86-4	0.1 - 1
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST-AID MEASURES

Inhalation	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

Most Important Acute Symptoms and Effects Not Available

Most Important Delayed Symptoms and Effects Not Available

Special treatment needed: No additional first aid information available

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use alcohol resistant foam, carbon dioxide, or dry chemical

# Safety Data Sheet

Revision Date: 07-13-2015

Product Code: 1510-053

## Unsuitable Extinguishing Media Fire and/or Explosion Hazards

extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

No data available

## Hazardous Combustion Products

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

## Special Protective Equipment and Precautions for Fire-Fighters

Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons, Toxic gases

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

### Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

### Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

### Materials to Avoid/Chemical Incompatibility

Oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Limestone	15 mg/m <sup>3</sup> (total dust); 5 mg/m <sup>3</sup> (respirable fraction)		
Talc	2mg/m <sup>3</sup> (Respirable)	20 mppcf TWA	

# Safety Data Sheet

Revision Date: 07-13-2015  
Product Code: 1510-053

	Dust)		
Iron Oxide		10mg/m <sup>3</sup> TWA	
tert-butyl acetate	200ppm; 950mg/m <sup>3</sup> TWA	200ppm TWA	
Stoddard solvent	500 ppm TWA; 2900 mg/m <sup>3</sup> TWA	100 ppm TWA; 572 mg/m <sup>3</sup> TWA	
Kaolin	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	2 mg/m <sup>3</sup> TWA (respirable dust)	
Quartz (Silica-Crystalline)	see Table Z-3	0.05 mg/m <sup>3</sup> TWA (respirable fraction)	
Carbon black	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	

<b>Appropriate Engineering Controls</b>	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
<b>Respiratory Protection</b>	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
<b>Eye Protection</b>	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
<b>Skin Protection</b>	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
<b>General Hygiene Conditions</b>	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	
Physical State	Liquid
Color	Red
<b>Odor</b>	Aromatic
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting Point/Freezing Point (°F/°C)</b>	No data available / No data available
<b>Initial Boiling Point and Boiling Range</b>	
Low (°F)	245.0
High (°F)	302.0
<b>Flash Point (°F/°C)</b>	40 / 4
<b>Flammability (solid, gas)</b>	No data available
<b>Upper Flammable/Explosive Limit</b>	7.0
<b>Lower Flammable/Explosive Limit</b>	1.0
<b>Vapor Pressure</b>	< 10.00 (mm Hg @ 68°F / 20° C)
<b>Vapor Density</b>	3.50
<b>Relative Density</b>	0.760
<b>Solubility in Water</b>	Not Available
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition Temperature</b>	No data available
<b>Decomposition Temperature:</b>	No data available

# Safety Data Sheet

Revision Date: 07-13-2015  
Product Code: 1510-053

Viscosity 30 - 40 Z3  
Volatiles, % by volume 43.81  
Volatiles, % by weight 23.89  
Volatile Organic Chemicals (g/L)  
(Regulatory, Calculated) 304.26  
(Actual, Calculated) 286.14  
Density 11.69 - 11.89 lbs./Gal

## 10. STABILITY AND REACTIVITY

**Chemical stability** Stable under normal conditions.  
**Possibility of Hazardous Reactions** No data available  
**Conditions to Avoid** Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.  
**Incompatible Materials** Oxidizing agents  
**Hazardous Decomposition Products** Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons, Toxic gases

## 11. TOXICOLOGICAL INFORMATION

**Routes of Exposure** Inhalation  
Ingestion  
Skin contact  
Eye contact

### Immediate (Acute) Health Effects by Route of Exposure

**Inhalation Irritation** Causes nose and throat irritation.  
**Inhalation Toxicity** Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.  
**Skin Contact** Can cause moderate skin irritation.  
**Eye Contact** Causes eye irritation.  
**Ingestion Toxicity** Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Long-Term (Chronic) Health Effects

**Carcinogenicity** Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists.  
Possible cancer hazard. Contains carbon black which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)  
**Inhalation** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.  
Overexposure may cause lung damage.

### Product Toxicology Data

**Inhalation Dust/Mist Acute Toxicity Estimate (ATE)** 18.15 mg/L  
**Inhalation Vapor Acute Toxicity Estimate (ATE)** 68.77 mg/L

### Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	Oral LD50 Rat 6450 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.00 mg/L
Light aliphatic solvent naphtha	Oral LD50 Rat 5840 mg/kg	Dermal LD50 Rat 2920	

# Safety Data Sheet

Revision Date: 07-13-2015

Product Code: 1510-053

		mg/kg	
Talc	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Iron Oxide	Oral LD50 Rat > 5000 mg/kg		
Solvent naphtha (petroleum) medium aliphatic	Oral LD50 Rat > 6500 mg/kg	Dermal LD50 Rabbit > 3000 mg/kg	Inhalation LC50 (4h) Rat > 14.00 mg/L
tert-butyl acetate	Oral LD50 Rat 4100 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 4,000.00 ppm
Stoddard solvent	Oral LD50 Rat > 5 g/kg		Inhalation LC50 Rat > 6.10 mg/L
Kaolin	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rat > 5000 mg/kg	Inhalation LC50 Rat 36.00 mg/L
Quartz	Oral LD50 Rat > 22,500 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Carbon black	Oral LD50 Rat > 8000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	

## Carcinogen Information

### Chemical Name

### IARC Carcinogen

### OSHA Carcinogen

### NTP Carcinogen

Talc

2B

Quartz

1

1

Carbon black

2B

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity (aquatic and terrestrial, where available)** No data available

**Mobility in soil** No data available

## 13. DISPOSAL CONSIDERATIONS

### Safe Handling of Waste

Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

**DOT Basic Description:** Paint

**Hazard Class:** 3

**UN Number:** UN1263

**Packing Group:** II

**Other:** This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

# Safety Data Sheet

Revision Date: 07-13-2015

Product Code: 1510-053

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

## Regulated Components

### SARA EHS Chemicals

Not applicable

### CAS #

### %

### CERCLA

tert-Butyl acetate

540-88-5

1 - 5

### SARA 313

Not applicable

### SARA 311/312

Health (Acute): Y

Health (chronic): Y

Fire (Flammable): Y

Pressure: N

Reactivity: N

## U. S. State Regulations:

### California Prop 65 Chemicals

#### **Cancer**

### CAS #

### %

Crystalline Silica

14808-60-7

0.1 - 1

Carbon Black

1333-86-4

0.1 - 1

Ethyl Benzene

100-41-4

0.01 - 0.1

Cumene

98-82-8

0.001- 0.01

Naphthalene

91-20-3

0.001- 0.01

Benzene

71-43-2

< 10 ppm

Lead

7439-92-1

< 1 ppm

#### **Reproductive**

Hexanoic acid, 2-ethyl-

149-57-5

0.01 - 0.1

Toluene

108-88-3

0.001- 0.01

Benzene

71-43-2

< 10 ppm

Lead

7439-92-1

< 1 ppm

## Canadian Regulations:

### **CEPA DSL:**

The components of this product ARE listed on the Canadian Domestic Substances List.

### **WHMIS Hazard Class:**

B2 D2A

## 16. OTHER INFORMATION

### **Revision Date**

07-13-2015

### **Disclaimer**

This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.