

# Safety Data Sheet

Revision Date: 02-05-2016  
Product Code: 1570-006

## 1. IDENTIFICATION

---

Product Name	STANTEST 2.8 DUNES TAN
Product Code	1570-006
Document ID	G1570-006
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Coating
Restrictions On Use	For Industrial Use Only
Chemical Family	Alkyd Enamel
Chemical Manufacturer / Importer	Hempel (USA), Inc. Jones-Blair Division 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

---

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



### GHS Classification

Skin Sensitisation Category 1  
Flammable Liquid Category 2  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2  
Carcinogenicity Category 2

### Signal Word

Danger

### Hazard Statements

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.

### Precautionary Statements

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

# Safety Data Sheet

Revision Date: 02-05-2016

Product Code: 1570-006

<b>Response</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
<b>Storage</b>	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazards Not Otherwise Classified (HNOC)</b>	Not applicable
<b>Additional Information</b>	Not applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Titanium dioxide	13463-67-7	7 - 13
Ethylene glycol mono-n-butyl ether	111-76-2	3 - 7
Parachlorobenzotrifluoride (PCBTF)	98-56-6	3 - 7
Light aromatic solvent naphtha	64742-95-6	1 - 5
Xylene	1330-20-7	0.5 - 1.5
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST-AID MEASURES

<b>Inhalation</b>	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.
<b>Eye Contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
<b>Most Important Acute Symptoms and Effects</b>	Not Available
<b>Most Important Delayed Symptoms and Effects</b>	Not Available
<b>Special treatment needed:</b>	No additional first aid information available

## 5. FIRE-FIGHTING MEASURES

# Safety Data Sheet

Revision Date: 02-05-2016  
Product Code: 1570-006

## Suitable Extinguishing Media

Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

## Unsuitable Extinguishing Media Fire and/or Explosion Hazards

No data available  
Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

## Hazardous Combustion Products

Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Sulfur containing gases

## Special Protective Equipment and Precautions for Fire-Fighters

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

### Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Do not get in eyes, on skin and clothing.

### Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

### Materials to Avoid/Chemical Incompatibility

Oxidizing agents, Caustics (bases, alkalis), Acids

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
tert-butyl acetate	200ppm; 950mg/m <sup>3</sup> TWA	200ppm TWA	
Titanium dioxide	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Butoxy Ethanol	50 ppm TWA; 240	20 ppm TWA; 97	

# Safety Data Sheet

Revision Date: 02-05-2016  
 Product Code: 1570-006

	mg/m <sup>3</sup> TWA	mg/m <sup>3</sup> TWA	
Ferric oxide (Nuisance Dust)	10 mg/m <sup>3</sup> TWA	as Fe: 5 mg/m <sup>3</sup> TWA (welding fumes, dust, total particulate (N.O.C.))	
Xylene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	150 ppm STEL; 651 mg/m <sup>3</sup> STEL
1,2,4-Trimethylbenzene		25ppm; 123mg/m <sup>3</sup> TWA	
Ethylbenzene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	125 ppm STEL; 543 mg/m <sup>3</sup> STEL

<b>Appropriate Engineering Controls</b>	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
<b>Respiratory Protection</b>	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
<b>Eye Protection</b>	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
<b>Skin Protection</b>	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
<b>Other Protective Equipment</b>	Impervious rubber
<b>General Hygiene Conditions</b>	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Do not get in eyes, on skin and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	
<b>Physical State</b>	Liquid
<b>Color</b>	Tan
<b>Odor</b>	Sweet, Naphthalene-Like
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting Point/Freezing Point (°F/°C)</b>	No data available / No data available
<b>Initial Boiling Point and Boiling Range</b>	
<b>Low (°F)</b>	208.4
<b>High (°F)</b>	342.0
<b>Flash Point (°F/°C)</b>	40 / 4
<b>Evaporation Rate</b>	2.80
<b>Flammability (solid, gas)</b>	No data available
<b>Upper Flammable/Explosive Limit</b>	10.5
<b>Lower Flammable/Explosive Limit</b>	0.9
<b>Vapor Pressure</b>	~ 41.50 (mm Hg @ 77°F / 25° C)
<b>Vapor Density</b>	6.20 (air = 1)
<b>Relative Density</b>	1.154
<b>Solubility in Water</b>	Complete; 100%
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition Temperature</b>	No data available
<b>Decomposition Temperature:</b>	No data available
<b>Viscosity</b>	25 - 35 Z3
<b>Volatiles, % by volume</b>	64.91

# Safety Data Sheet

Revision Date: 02-05-2016  
Product Code: 1570-006

Volatiles, % by weight	50.57
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	336.70
(Actual, Calculated)	189.77
Density	9.43 - 9.83 lbs./Gal

## 10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination. Elevated temperatures.
Incompatible Materials	Oxidizing agents, Caustics (bases, alkalis), Acids
Hazardous Decomposition Products	Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Sulfur containing gases

## 11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Skin contact Eye contact Skin absorption Ingestion
<b>Immediate (Acute) Health Effects by Route of Exposure</b>	
Inhalation Irritation	Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Causes nose and throat irritation.
Inhalation Toxicity	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact	Causes skin irritation.
Skin Absorption	May be harmful if absorbed through skin.
Eye Contact	Causes eye irritation.
Ingestion Toxicity	Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
<b>Long-Term (Chronic) Health Effects</b>	
Carcinogenicity	Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)
Reproductive and Developmental Toxicity	Contains butoxy ethanol which has been shown to cause harm to the fetus in laboratory animal studies. The relevance of these findings to humans is uncertain. Xylene may cause adverse reproductive and/or developmental effects. Pregnant women may be at an increased risk from exposure. Xylene has been shown to be positive in mutagenicity assays.
Mutagenicity	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Inhalation	Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis).
Skin Contact	Upon prolonged or repeated exposure, harmful if absorbed through the skin. Prolonged or repeated overexposure may cause central nervous system,
Skin Absorption	
Ingestion	

# Safety Data Sheet

Revision Date: 02-05-2016  
Product Code: 1570-006

kidney and liver damage.

## Product Toxicology Data

Oral Acute Toxicity Estimate (ATE)	8,170.80 mg/kg
Inhalation Vapor Acute Toxicity Estimate (ATE)	43.55 mg/L
Dermal Acute Toxicity Estimate (ATE)	50,033.11 mg/kg

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
tert-butyl acetate	Oral LD50 Rat 4100 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 4,000.00 ppm
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Ethylene glycol mono-n-butyl ether	Oral LD50 Rat 1300 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 500.00 ppm
Parachlorobenzotrifluoride (PCBTF)	Oral LD50 Rat 11,500 mg/kg		Inhalation LC50 Rat 20.00 g/m3
Ferric oxide	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Methoxypropanol acetate	Oral LD50 Rat 8532 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Light aromatic solvent naphtha	Oral LD50 Rat 8400 mg/kg	Dermal LD50 Rat > 2000 mg/kg	Inhalation LC50 (4h) Rat 5.60 mg/L
Xylene	Oral LD50 Rat 3523 mg/kg	Dermal LD50 Rabbit 1100 mg/kg	Inhalation LC50 (4h) Rat 11.00 mg/L
1,2,4-Trimethylbenzene	Oral LD50 Rat 6000 mg/kg	Dermal LD50 Rat > 3440 mg/kg	Inhalation LC50 (4h) Rat 10.20 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L

## Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Titanium dioxide	2B		
Ethylbenzene	2B		

## 12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)	No data available
Mobility in soil	No data available

## 13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste	Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.
------------------------	---

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint  
Hazard Class: 3  
UN Number: UN1263

# Safety Data Sheet

Revision Date: 02-05-2016  
Product Code: 1570-006

**Packing Group:** II  
**Other:** This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### **Regulated Components**

#### **SARA EHS Chemicals**

Not applicable

**CAS #**

**%**

#### **CERCLA**

tert-Butyl acetate	540-88-5	10 - 30
Xylene (mixed isomers)	1330-20-7	0.5 - 1.5
Ethyl Benzene	100-41-4	0.1 - 1

#### **SARA 313**

Ethylene glycol mono-n-butyl ether	111-76-2	3 - 7
Xylene (mixed isomers)	1330-20-7	0.5 - 1.5
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5
Ethylbenzene	100-41-4	0.1 - 1

#### **SARA 311/312**

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	Y
Pressure:	N
Reactivity:	N

## **U. S. State Regulations:**

### **California Prop 65 Chemicals**

#### **Cancer**

Titanium dioxide	13463-67-7	7 - 13
Ethyl Benzene	100-41-4	0.1 - 1
Carbon Black	1333-86-4	0.01 - 0.1
Cumene	98-82-8	0.01 - 0.1
Benzene	71-43-2	0.001 - 0.01

#### **Reproductive**

N-Methyl-2-Pyrrolidone	872-50-4	0.01 - 0.1
Toluene	108-88-3	0.001 - 0.01
Benzene	71-43-2	0.001 - 0.01

## **Canadian Regulations:**

**CEPA DSL:** The components of this product ARE listed on the Canadian Domestic Substances List.

**WHMIS Hazard Class:** B2 D2A

## 16. OTHER INFORMATION

**Revision Date** 02-05-2016

**Disclaimer** This SDS has been prepared in accordance with the OSHA Hazard Communication

# **Safety Data Sheet**

**Revision Date:** 02-05-2016

**Product Code:** 1570-006

Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.