

Safety Data Sheet

Revision Date: 06-09-2015
Product Code: 21102

1. IDENTIFICATION

Product Name	FAST REDUCER
Product Code	21102
Document ID	G21102
Revision Number	1
Prior Version Date	None
Intended Use	Solvent, Containing Petroleum Distillates
Restrictions On Use	For Industrial Use Only
Chemical Family	Solvent Thinner
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification

Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2
Reproductive Toxicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Acute Toxicity - Inhalation Vapour Category 4

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective

Safety Data Sheet

Revision Date: 06-09-2015

Product Code: 21102

Response	gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
Storage	Store locked up. Store in a cool, well-ventilated place. Keep container tightly closed.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable
Additional Information	Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Methyl ethyl ketone	78-93-3	40 - 60
Toluene	108-88-3	10 - 30
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 30

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
Most Important Acute Symptoms and Effects	Not Available
Most Important Delayed Symptoms and Effects	Not Available
Special treatment needed:	No additional first aid information available

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for
-------------------------------------	--

Safety Data Sheet

Revision Date: 06-09-2015

Product Code: 21102

Unsuitable Extinguishing Media Fire and/or Explosion Hazards

extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

No data available

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

Carbon dioxide, Carbon monoxide

Hazardous Combustion Products Special Protective Equipment and Precautions for Fire-Fighters

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Explosive vapor could form.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Remove contaminated clothing and wash before reuse.

Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

Materials to Avoid/Chemical Incompatibility

Oxidizing agents, Caustics (bases, alkalis), Acids

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Methyl ethyl ketone	200 ppm TWA; 590 mg/m ³ TWA	200 ppm TWA; 590 mg/m ³ TWA	300 ppm STEL; 885 mg/m ³ STEL
Toluene	200 ppm TWA; C 300 ppm	50 ppm TWA; 188 mg/m ³ TWA	
Ethylene glycol monobutyl ether acetate		20ppm TWA	

Safety Data Sheet

Revision Date: 06-09-2015

Product Code: 21102

Appropriate Engineering Controls	Use local exhaust ventilation or other engineering controls to minimize exposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
Respiratory Protection	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres.
Eye Protection	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
Skin Protection	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
Other Protective Equipment	Nitrile Neoprene
General Hygiene Conditions	Use spark-proof tools and explosion-proof equipment. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Remove contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical State	Liquid
Color	Colorless
Odor	Ketone
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (°F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	174.0
High (°F)	380.0
Flash Point (°F/°C)	42 / 6
Evaporation Rate	5.70 (n-Butyl Acetate = 1.0)
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	11.5
Lower Flammable/Explosive Limit	0.5
Vapor Pressure	28.00
Vapor Density	5.50 (air = 1)
Relative Density	0.805
Solubility in Water	Moderate; 40-99%
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Volatiles, % by volume	100.00
Volatiles, % by weight	100.00
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	859.40
(Actual, Calculated)	859.40
Density	7.01 - 7.21 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Sparks, open flame, other ignition sources, and elevated

Safety Data Sheet

Revision Date: 06-09-2015

Product Code: 21102

Incompatible Materials
Hazardous Decomposition Products

temperatures. Contamination. Elevated temperatures.
Oxidizing agents, Caustics (bases, alkalis), Acids
Carbon dioxide, Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Exposure
Eye contact
Inhalation
Skin contact
Ingestion
Skin absorption

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Causes nose and throat irritation. Causes lung irritation.
Inhalation Toxicity Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact Causes skin irritation.
Skin Absorption May be harmful if absorbed through skin.
Eye Contact Causes eye irritation.
Ingestion Toxicity Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Long-Term (Chronic) Health Effects

Reproductive and Developmental Toxicity

Contains Methyl Ethyl Ketone, which in animal studies has shown to cause harm to the fetus only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Possible birth defect hazard. Contains toluene which may cause birth defects based on animal data. Case studies suggest that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

Inhalation Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin Contact Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

Ingestion Prolonged or repeated overexposure may cause central nervous system, kidney and liver damage.

Product Toxicology Data

Oral Acute Toxicity Estimate (ATE) 2,437.50 mg/kg

Inhalation Dust/Mist Acute Toxicity Estimate (ATE) 7.31 mg/L

Dermal Acute Toxicity Estimate (ATE) 5,362.50 mg/kg

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	Oral LD50 Rat 2737 mg/kg	Dermal LD50 Rabbit 6480 mg/kg	Inhalation LC50 (8h) Rat 23,500.00 mg/m ³
Methoxypropanol acetate	Oral LD50 Rat 8532 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 100.00 ppm
Ethylene glycol monobutyl ether acetate	Oral LD50 Rat 1880 mg/kg	Dermal LD50 Rabbit 1500 mg/kg	Inhalation LC50 (6h) Rat > 4.59 mg/L

Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
---------------	-----------------	-----------------	----------------

Safety Data Sheet

Revision Date: 06-09-2015
Product Code: 21102

Toluene 3

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available) No data available
Mobility in soil No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint Related Material
Hazard Class: 3
UN Number: UN1263
Packing Group: II
Other: This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

Regulated Components

<u>SARA EHS Chemicals</u>	<u>CAS #</u>	<u>%</u>
Not applicable		
<u>CERCLA</u>		
Methyl Ethyl Ketone	78-93-3	40 - 60
Toluene	108-88-3	10 - 30
<u>SARA 313</u>		
Toluene	108-88-3	10 - 30
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 30

SARA 311/312

Health (Acute): Y
Health (chronic): Y
Fire (Flammable): Y
Pressure: N
Reactivity: N

U. S. State Regulations:

California Prop 65 Chemicals

Safety Data Sheet

Revision Date: 06-09-2015
Product Code: 21102

Cancer	CAS #	%
Benzene	71-43-2	0.01 - 0.1
Reproductive		
Toluene	108-88-3	10 - 30
Benzene	71-43-2	0.01 - 0.1

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class: B2 D2A

16. OTHER INFORMATION

Revision Date	06-09-2015
Disclaimer	This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.