

# Safety Data Sheet

Revision Date: 10-12-2015  
Product Code: 33701

## 1. IDENTIFICATION

<b>Product Name</b>	<b>DTM PRIMER/SURFACER CSX BEIGE</b>
<b>Product Code</b>	33701
<b>Document ID</b>	G33701
<b>Revision Number</b>	1
<b>Prior Version Date</b>	None
<b>Intended Use</b>	Industrial Maintenance Primer
<b>Restrictions On Use</b>	For Industrial Use Only
<b>Chemical Family</b>	Urethane Primer
<b>Chemical Manufacturer / Importer</b>	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
<b>Emergency Telephone Number:</b>	ChemTrec Center 1-800-424-9300 <b>International:</b> 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



**GHS Classification** Flammable Liquid Category 2  
Carcinogenicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 2

**Signal Word** Danger

**Hazard Statements** Highly flammable liquid and vapour. Suspected of causing cancer. May cause damage to organs.

### Precautionary Statements

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

**Response** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical attention. IF exposed or if you feel unwell: Call a POISON CENTER or physician. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.

# Safety Data Sheet

Revision Date: 10-12-2015

Product Code: 33701

<b>Storage</b>	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazards Not Otherwise Classified (HNOC)</b>	Not applicable
<b>Additional Information</b>	Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Methyl Amyl Ketone	110-43-0	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Ethyl 3-ethoxypropionate	763-69-9	1 - 5
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5
Crystalline Aluminosilicate	1318-02-1	0.5 - 1.5
Zinc oxide	1314-13-2	0.5 - 1.5
Ethylbenzene	100-41-4	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST-AID MEASURES

<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
<b>Eye Contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
<b>Most Important Acute Symptoms and Effects</b>	Not Available
<b>Most Important Delayed Symptoms and Effects</b>	Not Available
<b>Special treatment needed:</b>	No additional first aid information available

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.
<b>Unsuitable Extinguishing Media</b>	No data available
<b>Fire and/or Explosion Hazards</b>	Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

# Safety Data Sheet

Revision Date: 10-12-2015

Product Code: 33701

**Hazardous Combustion Products**

Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Aldehydes

**Special Protective Equipment and Precautions for Fire-Fighters**

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment and Emergency Procedures**

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Methods and Material for Containment and Cleaning Up**

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

**7. HANDLING AND STORAGE**

**Precautions for Safe Handling**

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

**Conditions for Safe Storage**

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

**Materials to Avoid/Chemical Incompatibility**

Oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Calcium Metasilicate (Particles Not Otherwise Classified)	50 mppcf (15mg/m <sup>3</sup> ) TWA Total Dust; 15 mppcf (5mg/m <sup>3</sup> ) TWA Respirable fraction		
Talc	2mg/m <sup>3</sup> (Respirable Dust)	20 mppcf TWA	
Methyl Amyl Ketone	100ppm; 465mg/m <sup>3</sup> (TWA)	50ppm; 233mg/m <sup>3</sup> TWA	
Titanium dioxide	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
tert-butyl acetate	200ppm; 950mg/m <sup>3</sup> TWA	200ppm TWA	

# Safety Data Sheet

Revision Date: 10-12-2015  
Product Code: 33701

Ethylene glycol monobutyl ether acetate		20ppm TWA	
Zinc oxide	5 mg/m <sup>3</sup> TWA (respirable dust); 15 mg/m <sup>3</sup> TWA (total dust)	2 mg/m <sup>3</sup> TWA (respirable dust)	10 mg/m <sup>3</sup> (respirable dust)
Ethylbenzene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	125 ppm STEL; 543 mg/m <sup>3</sup> STEL

<b>Appropriate Engineering Controls</b>	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
<b>Respiratory Protection</b>	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
<b>Eye Protection</b>	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
<b>Skin Protection</b>	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
<b>General Hygiene Conditions</b>	As with all chemicals, good industrial hygiene practices should be followed when handling this material.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Physical State	Liquid
Color	Beige
Odor	Sweet
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (°F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	194.0
High (°F)	302.0
Flash Point (°F/°C)	40 / 4
Evaporation Rate	3.22 (n-Butyl Acetate = 1.0)
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	7.9 %
Lower Flammable/Explosive Limit	1.1 %
Vapor Pressure	~ 41.50 (mm Hg @ 77° F / 25° C)
Vapor Density	4.00 (air = 1)
Relative Density	2.750
Solubility in Water	Low; 10-39%
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	25 - 30 Z3
Volatiles, % by volume	45.85
Volatiles, % by weight	30.35
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	272.84
(Actual, Calculated)	217.29
Density	11.29 - 11.69 lbs./Gal

# Safety Data Sheet

Revision Date: 10-12-2015  
Product Code: 33701

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	No data available
<b>Conditions to Avoid</b>	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.
<b>Incompatible Materials</b>	Oxidizing agents
<b>Hazardous Decomposition Products</b>	Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases, Aldehydes

## 11. TOXICOLOGICAL INFORMATION

<b>Routes of Exposure</b>	Inhalation Skin absorption Skin contact Eye contact Ingestion
---------------------------	---

### Immediate (Acute) Health Effects by Route of Exposure

<b>Inhalation Irritation</b>	Harmful if inhaled. Causes nose and throat irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
<b>Inhalation Toxicity</b>	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
<b>Skin Contact</b>	Can cause moderate skin irritation.
<b>Skin Absorption</b>	May be harmful if absorbed through skin.
<b>Eye Contact</b>	Causes eye irritation.
<b>Ingestion Toxicity</b>	Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Long-Term (Chronic) Health Effects

<b>Carcinogenicity</b>	Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)
<b>Reproductive and Developmental Toxicity</b>	Contains Dimethyl carbonate which has shown teratogenic effects at very high doses (3000 ppm) in one mouse assay. No effects were observed at lower doses.
<b>Inhalation</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Skin Contact</b>	Prolonged or excessive exposure may result in adverse effects.

### Product Toxicology Data

<b>Oral Acute Toxicity Estimate (ATE)</b>	3,669.17 mg/kg
<b>Inhalation Dust/Mist Acute Toxicity Estimate (ATE)</b>	30.90 mg/L
<b>Inhalation Vapor Acute Toxicity Estimate (ATE)</b>	38.15 mg/L
<b>Dermal Acute Toxicity Estimate (ATE)</b>	54,337.76 mg/kg

### Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Metasilicate	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L

# Safety Data Sheet

Revision Date: 10-12-2015

Product Code: 33701

Talc	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Methyl Amyl Ketone	Oral LD50 Rat 1600 mg/kg	Dermal LD50 Rabbit 10,206 mg/kg	Inhalation LC50 (4h) Rat > 16.70 mg/L
Dimethyl Carbonate	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 Rat > 140.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
tert-butyl acetate	Oral LD50 Rat 4100 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 4,000.00 ppm
Ethyl 3-ethoxypropionate	Oral LD50 Male Rat > 5000 mg/kg Oral LD50 Female Rat ~ 4309 mg/kg	Dermal LD50 Rabbit ~ 4080 - 4680 mg/kg	Inhalation LC50 (6h) Male Rat > 998.00 mg/L
Ethylene glycol monobutyl ether acetate	Oral LD50 Rat 1880 mg/kg	Dermal LD50 Rabbit 1500 mg/kg	Inhalation LC50 (6h) Rat > 4.59 mg/L
Crystalline Aluminosilicate	Oral LD50 Rat > 5110 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 3.35 mg/L
Zinc oxide	Oral LD50 Mouse 7950 mg/kg		Inhalation LC50 Mouse 2,500.00 mg/m <sup>3</sup>
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L

## Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Talc	2B		
Titanium dioxide	2B		
Ethylbenzene	2B		

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity (aquatic and terrestrial, where available)** No data available

**Mobility in soil** No data available

## 13. DISPOSAL CONSIDERATIONS

**Safe Handling of Waste** Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

**DOT Basic Description:** Paint  
**Hazard Class:** 3  
**UN Number:** UN1263  
**Packing Group:** II  
**Other:** This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

# Safety Data Sheet

Revision Date: 10-12-2015  
Product Code: 33701

Marine Pollutant: No

## 15. REGULATORY INFORMATION

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### Regulated Components

#### SARA EHS Chemicals

Not applicable

#### CERCLA

	<u>CAS #</u>	<u>%</u>
tert-Butyl acetate	540-88-5	3 - 7
Ethyl Benzene	100-41-4	0.1 - 1

#### SARA 313

Ethylene glycol monobutyl ether acetate	112-07-2	1 - 5
Zinc Oxide	1314-13-2	0.5 - 1.5
Ethylbenzene	100-41-4	0.1 - 1

#### SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	Y
Pressure:	N
Reactivity:	N

### U. S. State Regulations:

#### California Prop 65 Chemicals

##### Cancer

	<u>CAS #</u>	<u>%</u>
Titanium dioxide	13463-67-7	5 - 10
Ethyl Benzene	100-41-4	0.1 - 1
Carbon Black	1333-86-4	0.001- 0.01

##### Reproductive

Methyl Alcohol	67-56-1	0.01 - 0.1
----------------	---------	------------

### Canadian Regulations:

**CEPA DSL:** The components of this product ARE listed on the Canadian Domestic Substances List.

**WHMIS Hazard Class:** B2 D2A

## 16. OTHER INFORMATION

**Revision Date** 10-12-2015

**Disclaimer** This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.