

# Safety Data Sheet

Revision Date: 09-18-2015  
Product Code: 4400-002

## 1. IDENTIFICATION

Product Name	ACRYLITHANE DTM NEUTRAL BASE
Product Code	4400-002
Document ID	G4400-002
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Coating
Restrictions On Use	For Industrial Use Only
Chemical Family	Acrylic Urethane Enamel
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



### GHS Classification

Skin Sensitisation Category 1  
Flammable Liquid Category 2  
Carcinogenicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 2

### Signal Word

Danger

### Hazard Statements

Highly flammable liquid and vapour. May cause an allergic skin reaction.  
Suspected of causing cancer. May cause damage to organs.

### Precautionary Statements

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

#### Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical attention. IF exposed or if you feel unwell: Call a POISON CENTER or physician. If skin

# Safety Data Sheet

Revision Date: 09-18-2015

Product Code: 4400-002

irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.

**Storage** Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards Not Otherwise Classified (HNOC)** Not applicable

## Additional Information

Not applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Methyl Amyl Ketone	110-43-0	10 - 30
Xylene	1330-20-7	3 - 7
n-Butyl acetate	123-86-4	1 - 5
Ethyl 3-ethoxypropionate	763-69-9	1 - 5
Ethylene glycol monobutyl ether acetate	112-07-2	0.5 - 1.5
Ethylbenzene	100-41-4	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST-AID MEASURES

**Inhalation** Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.

**Eye Contact** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**Skin Contact** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**Most Important Acute Symptoms and Effects** Not Available

**Most Important Delayed Symptoms and Effects** Not Available

**Special treatment needed:** No additional first aid information available

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

**Unsuitable Extinguishing Media** No data available

# Safety Data Sheet

Revision Date: 09-18-2015

Product Code: 4400-002

## Fire and/or Explosion Hazards

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

## Hazardous Combustion Products

Carbon dioxide, Carbon monoxide, Sulfur containing gases, Toxic fumes, Toxic gases

## Special Protective Equipment and Precautions for Fire-Fighters

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Isolate area. Keep unnecessary personnel away.

### Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Follow all protective equipment recommendations provided in Section VIII.

### Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

### Materials to Avoid/Chemical Incompatibility

Oxidizing agents, Caustics (bases, alkalis), Acids

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Methyl Amyl Ketone	100ppm; 465mg/m <sup>3</sup> (TWA)	50ppm; 233mg/m <sup>3</sup> TWA	
Xylene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	150 ppm STEL; 651 mg/m <sup>3</sup> STEL
n-Butyl acetate	150 ppm TWA; 710 mg/m <sup>3</sup> TWA	150 ppm TWA; 713 mg/m <sup>3</sup> TWA	200 ppm STEL; 950 mg/m <sup>3</sup> STEL
Ethylene glycol monobutyl ether acetate		20ppm TWA	
Ethylbenzene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	125 ppm STEL; 543 mg/m <sup>3</sup> STEL

# Safety Data Sheet

**Revision Date:** 09-18-2015  
**Product Code:** 4400-002

<b>Appropriate Engineering Controls</b>	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
<b>Respiratory Protection</b>	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
<b>Eye Protection</b>	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
<b>Skin Protection</b>	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
<b>Other Protective Equipment</b>	Nitrile
<b>General Hygiene Conditions</b>	Follow all protective equipment recommendations provided in Section VIII.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	
Physical State	Liquid
Color	Colorless
<b>Odor</b>	No data available
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting Point/Freezing Point (°F/°C)</b>	No data available / No data available
<b>Initial Boiling Point and Boiling Range</b>	
Low (°F)	282.0
High (°F)	302.0
<b>Flash Point (°F/°C)</b>	63 / 17
<b>Evaporation Rate</b>	0.60
<b>Flammability (solid, gas)</b>	No data available
<b>Upper Flammable/Explosive Limit</b>	7.9 %
<b>Lower Flammable/Explosive Limit</b>	1.1 % 1.1
<b>Vapor Pressure</b>	2.10 (air = 1)
<b>Vapor Density</b>	3.90 (air = 1)
<b>Relative Density</b>	4.500
<b>Solubility in Water</b>	Negligible; 0-1%
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition Temperature</b>	No data available
<b>Decomposition Temperature:</b>	No data available
<b>Viscosity</b>	15 - 20 Z3
<b>Volatiles, % by volume</b>	47.19
<b>Volatiles, % by weight</b>	32.20
<b>Volatile Organic Chemicals (g/L)</b>	
(Regulatory, Calculated)	389.33
(Actual, Calculated)	368.18
<b>Density</b>	10.56 - 10.96 lbs./Gal

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	No data available
<b>Conditions to Avoid</b>	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.

# Safety Data Sheet

Revision Date: 09-18-2015

Product Code: 4400-002

Incompatible Materials  
Hazardous Decomposition Products

Oxidizing agents, Caustics (bases, alkalis), Acids  
Carbon dioxide, Carbon monoxide, Sulfur containing gases,  
Toxic fumes, Toxic gases

## 11. TOXICOLOGICAL INFORMATION

**Routes of Exposure**  
Inhalation  
Skin absorption  
Skin contact  
Eye contact  
Ingestion

### Immediate (Acute) Health Effects by Route of Exposure

**Inhalation Irritation** Harmful if inhaled.  
**Inhalation Toxicity** Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.  
**Skin Contact** Can cause moderate skin irritation.  
**Skin Absorption** May be harmful if absorbed through skin.  
**Eye Contact** Causes eye irritation.  
**Ingestion Toxicity** Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Long-Term (Chronic) Health Effects

**Carcinogenicity** Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)  
**Reproductive and Developmental Toxicity** Xylene may cause adverse reproductive and/or developmental effects. Pregnant women may be at an increased risk from exposure. Contains Dimethyl carbonate which has shown teratogenic effects at very high doses (3000 ppm) in one mouse assay. No effects were observed at lower doses.  
**Mutagenicity** Xylene has been shown to be positive in mutagenicity assays.  
**Inhalation** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.  
**Skin Contact** Prolonged or excessive exposure may result in adverse effects.

### Product Toxicology Data

**Oral Acute Toxicity Estimate (ATE)** 2,999.13 mg/kg  
**Inhalation Dust/Mist Acute Toxicity Estimate (ATE)** 115.82 mg/L  
**Inhalation Vapor Acute Toxicity Estimate (ATE)** 43.73 mg/L  
**Dermal Acute Toxicity Estimate (ATE)** 17,392.35 mg/kg

### Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Methyl Amyl Ketone	Oral LD50 Rat 1600 mg/kg	Dermal LD50 Rabbit 10,206 mg/kg	Inhalation LC50 (4h) Rat > 16.70 mg/L
Xylene	Oral LD50 Rat 3523 mg/kg	Dermal LD50 Rabbit 1100 mg/kg	Inhalation LC50 (4h) Rat 11.00 mg/L
Dimethyl Carbonate	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 Rat > 140.00 mg/L
n-Butyl acetate	Oral LD50 Rat 10,760 mg/kg	Dermal LD50 Rat 12,789 mg/kg	Inhalation LC50 (4h) Rat > 21.00 mg/L
Ethyl 3-ethoxypropionate	Oral LD50 Male Rat > 5000 mg/kg	Dermal LD50 Rabbit ~ 4080 - 4680 mg/kg	Inhalation LC50 (6h) Male Rat > 998.00 mg/L

# Safety Data Sheet

Revision Date: 09-18-2015

Product Code: 4400-002

	Oral LD50 Female Rat ~ 4309 mg/kg		
Ethylene glycol monobutyl ether acetate	Oral LD50 Rat 1880 mg/kg	Dermal LD50 Rabbit 1500 mg/kg	Inhalation LC50 (6h) Rat > 4.59 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L

## Carcinogen Information

### **Chemical Name**

Ethylbenzene

### **IARC Carcinogen**

2B

### **OSHA Carcinogen**

### **NTP Carcinogen**

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity (aquatic and terrestrial, where available)**

No data available

### **Mobility in soil**

No data available

## 13. DISPOSAL CONSIDERATIONS

### **Safe Handling of Waste**

Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

**DOT Basic Description:** Paint

**Hazard Class:** 3

**UN Number:** UN1263

**Packing Group:** II

**Other:** This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### **Regulated Components**

#### **SARA EHS Chemicals**

Not applicable

#### **CAS #**

#### **%**

#### **CERCLA**

Xylene (mixed isomers)

1330-20-7

3 - 7

n-Butyl Acetate

123-86-4

1 - 5

Ethyl Benzene

100-41-4

0.1 - 1

#### **SARA 313**

Xylene (mixed isomers)

1330-20-7

3 - 7

Ethylene glycol monobutyl ether acetate

112-07-2

0.5 - 1.5

# Safety Data Sheet

Revision Date: 09-18-2015  
Product Code: 4400-002

Ethylbenzene 100-41-4 0.1 - 1

## SARA 311/312

Health (Acute): Y  
Health (chronic): Y  
Fire (Flammable): Y  
Pressure: N  
Reactivity: N

## U. S. State Regulations:

### California Prop 65 Chemicals

#### **Cancer**

	<u>CAS #</u>	<u>%</u>
Ethyl Benzene	100-41-4	0.1 - 1
Benzene	71-43-2	< 10 ppm

#### **Reproductive**

Toluene	108-88-3	0.01 - 0.1
Methyl Alcohol	67-56-1	0.001- 0.01
Benzene	71-43-2	< 10 ppm

## Canadian Regulations:

**CEPA DSL:** The components of this product ARE listed on the Canadian Domestic Substances List.

**WHMIS Hazard Class:** B2 D2A

## 16. OTHER INFORMATION

**Revision Date** 09-18-2015

**Disclaimer** This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.