

# MATERIAL SAFETY DATA SHEET

Date Issued: 7/8/2003 Supercedes: 7/15/2002

## I. Identification of the Substance/Preparation and the of the Company/Undertaking

### Identification of the product

Product Name: **GEL Cleanser**

### Company/undertaking identification:

Company:  
Odyssey Nail Systems Phone 1 407 522 5700  
6498 Wilcrest Dr Fax 1 407 522 5788  
Houston, TX 77072 Emergency Contact Information  
1 407 522 5700

## II. Composition on Ingredients

**Synonyms:** Acrylated urethane / acetone blend

	CAS #	WT%	OSHA TWA ppm	OSHA STEL ppm	CGIH TWA ppm	ACGIH STEL ppm
Isopropyl alcohol	67-63-0	95	---	---	---	---
Acetone	67-64-1	5	---	---	---	---

--- Not established

\*\*\* The specific chemical identity and/or weight percent is being withheld as a trade secret

## III. Hazard Identification

Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness, cracking or rash. Vapors may cause drowsiness and dizziness.

## IV. First Aid Measures

Eye Contact: Flush with plenty of water for at least 15 minutes and seek medical attention.  
Skin Contact: Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Particular attention should be paid to hair, nose, ears and other areas not easily cleaned. See section VIII. Note to physician: effects can be delayed 24-48 hours.  
Ingestion: If appreciable quantities are swallowed, seek medical attention.  
Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention

## V. Fire-Fighting Measures

Extinguishing Media:  
Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires  
Unusual Fire and Explosion Hazards:  
High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels and containers. Avoid the use of a stream of water to control fires since frothing can occur.  
Special Fire Fighting Procedure:  
Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined area where potential for exposure to vapors or products of combustion exists.

## VI. Accidental Release Measures

Steps to Be Taken in Case Material is Released or Spilled:  
Eliminate ignition & heat sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb with inert material and dispose. Flush area with water; prevent washings from entering waterways. Spills or releases to the environment may be reportable to the National Response Center (800- 424-8802) and to state and local agencies.  
Waste Disposal Method:  
For large spills: incinerate or use biological treatment in accordance with federal, state and local regulations. For small spills: dispose in accordance with federal, state and local regulations.

## VI. Handling & Storage

Stability: Normally Stable  
Conditions to Avoid:  
Storage >100F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.  
Materials to Avoid:  
Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.  
Hazardous Decomposition Products:  
Fumes produces when heated to decomposition may include: carbon monoxide, carbon dioxide, oxides of nitrogen.

## VIII. Exposure Controls/Personal Protection

Respiratory Protection:  
When exposed to aerosols or vapors, use full-face respirator with organic vapor cartridges that utilize a particulate pre-filter. In emergency situations, or when used in confined spaces, use self-contained breathing apparatus or other air-supplied full face respirator.  
Ventilation:  
Local exhaust - recommended to control exposure which may result from operations generating  
Mechanical - Not recommended to control exposure for operations generating aerosols or vapors.  
Protective Gloves:  
Impervious gloves (neoprene). A combination of barrier cream, applied before exposure, and gloves is recommended. Do not apply cream after exposure.  
Eye Protection:  
Chemical splash goggles or safety glasses when handling large quantities.  
Other Protective Equipment:  
None

## IX. Physical and Chemical Properties:

Manufacturer's ID:	Cleanser	Form:	liquid
Product Class:	Isopropanol / acetone blend	Color:	colorless
Boiling Range:	56.2 °C	Percent Volatile by Volume:	100

Vapor Density:	2.01		
Weight Per Gallon:	6.5 lbs		
Evaporation Rate:	> 1	Vapor Pressure at 20C:	233 hPa
Appearance and Odor:	Clear liquid with ketone odor	Solubility in Water:	soluble
Flashpoint:	<-20 °C Closed Cup		
Explosion Limits:	LEL: 2.6 Vol %	UEL: 13 Vol %	

**X. Stability and Reactivity**

Stability: Normally Stable  
Hazardous Polymerization: Will not occur.  
Conditions to Avoid: Storage >100F, contamination with incompatible materials.  
Materials to Avoid: Combustion can occur upon exposure to initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.  
Hazardous Decomposition Products: Fumes produces when heated to decomposition may include: carbon monoxide, carbon dioxide, oxides of nitrogen.

**XI. Toxicological Information**

Health Hazards: See section V  
Ingestion: LD<sub>50</sub> (oral, rat): 5800 mg/kg.  
Inhalation: LD<sub>50</sub> (inhalation, rat): 76 mg/l/4h.  
Skin Contact: LD<sub>50</sub> (dermal, rabbit): 20000 mg/kg.  
Allergy Sensitization: Mild skin and eye sensitization may be observed upon continued overexposure  
Carcinogenicity: Category E (evidence of non-carcinogenicity for humans)  
Mutagenicity: Negative in all tests

**XII. ECOLOGICAL INFORMATION**

Biologic Degredation: Biodegradation: 91% / 28 days Readily biodegradable  
Behavior in environmental compartments: Distribution: log p(o/w): -0.24 no bioaccumulation to be expected  
Ecotoxic effects:  
Biological effects:  
Fish toxicity: L. macrochirus LC<sub>50</sub>: 8300 mg/l/96 hr  
Daphnia toxicity: Daphnia magna EC<sub>50</sub>:12600-12700 mg/l/48 hr  
Maximum permissible toxic concentrations:  
Algal toxicity: Sc. Quadricauda ICs: 7500 mg/l/8 d  
Bacterial toxicity: M. aeruginosa ECs: 530 mg/l/8 d; Ps. Putida ECs: 1700 mg/l/16 hr  
Protzoa: E. sulcatum ECs: 28mg/l/72 hr  
Further ecological data:  
Degradability:  
BODs: 1.85 g/g  
COD: 2.07 g/g  
TOD: 2.20 g/g

**XIII. DISPOSAL INFORMATION**

Product: Chemicals must be disposed of in compliance with federal, state and local regulations.  
Container: Container must be disposed of in accordance with federal, state and local regulations.

**XIV. Transportation Information**

D.O.T. Shipping Name: ORM-D  
D.O.T. Hazard Class: Acetone  
D.O.T. Label(s): ORM-D  
D.O.T. UN/NA Number: Acetone, 3, UN 1090, II

**XV. Regulatory Information**

In The EU:  
Classification and Labeling (according to 88/379/EEV as amended): None

Threshold Limit Value:	OSHA PEL (USA)	ACGIH TLV (USA)	MAK (Germany)	HGV (Denmark)	Others
	n.a.	n.a.	n.a.	n.a.	---

Product Name: See section I  
Active Ingredient: urethane acrylate  
EPA Reg. No. n.a.

**XVI. Other Information**

All of the components of this product are included on the TSCA inventory

INVENTORY STATUS:  
Australia (AICS): Included on inventory  
Canada (DSL): Included on inventory  
European Economic Community (EINECS): Included on inventory  
Japan (MITT): Included on inventory  
Korea (MOE): Included on inventory