

AIROSOL COMPANY, INC.

1206 Illinois Street

Phone 620-325-2666

Neodesha KS 66757

MATERIAL SAFETY DATA SHEET**EMERGENCY INFORMATION**

MEDICAL: 1-800-633-9576

TRANSPORTATION: 1-800-535-5053

SECTION ONEPRODUCT NAME: **American Grease Stick (AGS) Greaseless Multi-Use Lubricant**PRODUCT CODE: **GLB-11 (37711)**

ISSUE DATE: 7/27/2012

SECTION TWO- HAZARDOUS COMPONENTS

HAZARDOUS COMPONENTS	OSHA PEL	EXPOSURE LIMITS			CAS NO
		ACGIH	OTHER	%	
Mineral Spirits	NE	200 ppm	N/A	20-25	64742-47-8
Severely Hydro treated Heavy Naphthenic Distillate	5 mg/m ³	5 mg/m ³	N/A	55-60	64742-52-5 64741-88-4 64741-89-5
Propane	1000 ppm	NE	N/A	15-20	74-98-6

Abbreviations

NE: None established, N/A: Not applicable, *: ACGIH "STEL" Guidelines, ND: Not Determined, STEL: Short Term Exposure Limits, : ExxonMobil exposure limits for total Hydrocarbon

SECTION THREE- PHYSICAL DATA

BOILING POINT: ND

VAPOR DENSITY (AIR=1): Heavier than

SOLUBILITY IN WATER % BY WT.: Negligible

EVAPORATION RATE (Butyl Acetate = 1): Slower than

APPEARANCE AND ODOR: Opaque amber liquid with a petroleum odor.

VAPOR PRESSURE (mmHg or psig @ 70F): 45-75 psig

SPECIFIC GRAVITY (H₂O=1): 0.81-0.85

VOC CONTENT % BY WT.: 39%

SECTION FOUR- FIRE AND EXPLOSION HAZARD DATA**FLASH POINT:** Not Determined **FLAMMABLE LIMITS:** UEL 9.5 % LEL 0.8 %**EXTINGUISHING MEDIUM:** AS APPROPRIATE FOR COMBUSTIBLES IN AREA.**FIRE AND EXPLOSION HAZARD DATA**

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Keep exposed containers cool with water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse any flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

PRODUCT NAME: **American Grease Stick (AGS) Greaseless Multi-Use Lubricant**

PRODUCT CODE: **GLB-11 (37711)**

SECTION FIVE - REACTIVITY DATA

STABILITY: Stable, avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition and direct sunlight.

INCOMPATIBILITY: Avoid contact with strong acids, alkalies, and oxidizers such as liquid chlorine, other halogens, hydrogen peroxide, and oxygen.

SECTION SIX- HEALTH HAZARD DATA

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

EFFECTS OF OVER EXPOSURE

EYE CONTACT: Considered moderately irritating to the eye. May cause stinging, watering, swelling, and redness. Vapors may irritate eyes.

SKIN CONTACT: Short single exposure not likely to cause significant skin irritation. Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying and flaking of skin. May cause allergic skin reaction in susceptible individuals.

SKIN ABSORPTION: A single prolonged skin exposure is not likely to result in harmful amounts.

INGESTION: This material may irritate the mucus membranes of the mouth, throat, and esophagus. It can be readily absorbed by the stomach and intestinal tract. Symptoms include a burning sensation of the mouth and esophagus, nausea and vomiting, dizziness, staggering gait, drowsiness, loss of consciousness, and delirium, as well as additional central nervous system effects. Aspiration of the material into the lungs can cause chemical pneumonitis which can be fatal. If aspirated, it may be rapidly absorbed through the lungs and result in injury to other body systems.

INHALATION: Mildly toxic by inhalation. Excessive inhalation of vapors can cause nasal and respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possibly unconsciousness, and even death. Progressively higher levels of concentrations can cause unconsciousness and death. These high levels may also cause cardiac arrhythmias (irregular heartbeats). In confined or poorly ventilated areas, vapors which readily accumulate and can cause unconsciousness and death.

SYSTEMIC AND OTHER EFFECTS:

HUMAN SYSTEMIC EFFECTS BY INGESTION AND INHALATION: None known.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with large amounts of water, occasionally lifting upper and lower eyelids. Get medical attention.

SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing and launder it before reuse. Should any irritation persist, get medical attention.

INHALATION: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get medical attention.

INGESTION: Ingestion is not considered a potential route of exposure as an aerosol but, if swallowed, **do not induce vomiting**. Call a physician or transport to an emergency facility.

SECTION SEVEN-ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO TAKE FOR SPILLS/LEAKS: Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

WASTE DISPOSAL METHOD: When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

PRODUCT NAME: **American Grease Stick (AGS) Greaseless Multi-Use Lubricant**
 PRODUCT CODE: **GLB-11 (37711)**

SECTION EIGHT-HANDLING AND STORAGE PRECAUTIONS

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapor, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

SECTION NINE - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION: Control airborne concentrations below the exposure limits in section two. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PROTECTIVE GLOVES: For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier)

OTHER PROTECTIVE EQUIPMENT: To prevent repeated or prolonged skin contact; use protective clothing impervious to this product. Selection of specific items such as gloves, boots, apron, or full body suit will depend on operation.

SECTION TEN - REGULATORY INFORMATION

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
None Listed		

FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
None Listed			
CALIFORNIA PROPOSITION 65	None listed		
MASSACHUSETTS RIGHT TO KNOW:	Yes		
Propane		74-98-6	15-20
PENNSYLVANIA RIGHT TO KNOW:	Yes		
Propane		74-98-6	15-20
NEW JERSEY RIGHT TO KNOW:	Yes		
Propane		74-98-6	15-20

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS: Listed

CALIFORNIA VOC'S: 39%

NFPA RATING AS AN AEROSOL: Level Three

HMIS: Health 2 Reactivity 0 Flammability 3

NOTE: THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED "AS IS" AND ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR THEIR PARTICULAR PURPOSE AND ON THE CONDITION THAT THEY ASSUME THE RISK OF THEIR USE THEREOF.