

MATERIAL SAFETY DATA SHEET

GUARDIAN SEAL

Pit and Fissure Sealant

1 - IDENTIFICATION

Manufacturer: Kerr Corporation
Address: 1717 West Collins Avenue
City, State, Zip: Orange, CA 92867-5422
Telephone: 1-800-KERR-123
Emergency: Chemtrec 1-800-424-9300
Date Prepared: June 6, 2005

2 - COMPOSITION INFORMATION

Hazardous Ingredients

	<u>CAS #</u>	<u>PEL</u>	<u>TLV</u>	<u>%</u>
Uncured Methacrylate Ester Monomers	109-16-0	NA	NA	60-65

Other Ingredients

Inert mineral fillers, photoinitiators and stabilizing additives.

3 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N/A
Specific Gravity (H₂O = 1): 2.0
Vapor Pressure (mm Hg): N/D
Vapor Density (AIR = 1): N/D
Solubility in Water: Insoluble
Reactivity in Water: N/A
Appearance and Odor: Colored liquid with fruity ester-like odor.

4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/D
Flammable Limits: LEL: N/D UEL: N/D
Extinguishing Media: Chemical foam, CO₂, dry chemical
Special Fire Fighting Procedures: Wear self contained breathing apparatus.
Unusual Fire and Explosion Hazards: None

5 - REACTIVITY DATA

Stability: Stable if stored as directed.
Conditions to Avoid: Heat, light, aging and contamination
Incompatibility (Material to Avoid): Reducing and oxidizing agents, peroxides and amines.
Hazardous Decomposition Products: Oxides of carbon
Hazardous Polymerization: May occur
Conditions to Avoid: Heat, light, aging and sources of contamination

6 - HEALTH HAZARD DATA

Routes of Entry:

Skin: Prolonged or repeated exposure to uncured material may cause irritation or skin rash especially in sensitive individuals.
Eyes: May cause irritation and damage if not removed promptly.
Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion: Uncured material may be harmful or fatal if swallowed.
Carcinogenicity - NTP: No
IARC Monographs: No **OSHA Regulated Carcinogen:** No

7 - EMERGENCY FIRST AID PROCEDURES

Skin: Wash thoroughly with soap and water.
Eyes: Flush with water for 15 minutes including under eyelids.
Inhalation: Remove to fresh air. Get medical attention if discomfort persists.
Ingestion: Rinse mouth out with water. Do not induce vomiting. Seek medical attention.

8 - PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken in case material is released or spilled: Absorb spills with inert material. Keep spilled material out of sewers.
Waste Disposal Method: Unpolymerized (uncured) material may be RCRA hazardous waste. Incinerate uncured material in accordance with federal, state and local regulations.
Precautions to be taken in handling and storing: Store in a cool, dry place away from heat light and ignition sources.

9 - CONTROL MEASURES

Respiratory Protection (Specify Type): Avoid prolonged or excessive breathing of vapors of uncured material.
VENTILATION:
Local Exhaust: Good general ventilation should be sufficient to control airborne levels of vapors released by uncured material.
Mechanical (General): Good general ventilation recommended.
Protective Gloves: Protective gloves recommended when contacting uncured material.
Eye Protection: Safety glasses recommended
Other Protective Clothing or Equipment: N/A
Work/Hygiene Practices: Handle in accordance with good personal hygiene and safety practices. These practices include avoiding unnecessary exposure to uncured material.

10 - TRANSPORTATION INFORMATION

Not DOT regulated.

11 - SPECIAL INFORMATION

HMIS(Hazardous Material Identification System) Rating:
H2 F0 R0
[HMIS Index: 4 - Severe Hazard; 3 - Serious Hazard;
2 - Moderate Hazard; 1 - Slight Hazard; 0 - Minimum Hazard]

Note: Hazard information contained on this MSDS form relates only to material in its uncured state. Thorough biocompatibility and toxicity testing of the cured material and its extracts have demonstrated that the material is non-toxic.